



TEST REPORT IEC 60335-2-80 Safety of household and similar electrical appliances Part 2 : Particular requirements for fans	
Report Number.....	150618181GZU-001
Date of issue.....	September 18, 2015; Modification 6: November 14, 2018
Total number of pages	181
Applicant's name	YUCAU HOME APPLIANCES CO.,LTD.
Address.....	Songyuanzui Industrial Zone, Dubi Village, Duruan Town, Jiangmen City, Guangdong Province, P.R.China
Test specification:	
Standard.....	IEC 60335-2-80:2002 (Second edition) + A1:2004 +A2:2008 in conj. With IEC 60335-1:2010 (Fifth Edition)
Test procedure	
Non-standard test method.....	N/A
Test Report Form No.	IEC60335_2_80E
Test Report Form(s) Originator	DEKRA Certification B.V.
Master TRF	Dated 2012-09
Copyright © 2012 Worldwide System for Conformity Testing and Certification of Electrotechnical Equipment and Components (IECEE), Geneva, Switzerland. All rights reserved. This publication may be reproduced in whole or in part for non-commercial purposes as long as the IECEE is acknowledged as copyright owner and source of the material. IECEE takes no responsibility for and will not assume liability for damages resulting from the reader's interpretation of the reproduced material due to its placement and context. If this Test Report Form is used by non-IECEE members, the IECEE/IEC logo and the reference to the CB Scheme procedure shall be removed. This report is not valid as a CB Test Report unless signed by an approved CB Testing Laboratory and appended to a CB Test Certificate issued by an NCB in accordance with IECEE 02.	
Test item description	Electric Fan
Trade Mark	---
Manufacturer.....	YUCAU HOME APPLIANCES CO.,LTD.

Model/Type reference	YH-40D, YH-40D1, YH-40D1-1, YH-30D, YH-30D1, YH-30D2, YH-30D1-1, YH-23D, YH-23D1, YH-23D1-1, YH-15D, YH-15D1, YH-15C, YH-15C1, YH-40A3, YH-40A3-1, YH-40A3-2, YH-40A3-0, YH-40A3-1-0, YH-40A3--2-0, YH-40I, YH-40I-0, YH-40A1, YH-40A1-1, YH-40A1-2, YH-40A1-0, YH-40A1-1-0, YH-40A1--2-0, YH-40A2, YH-40A2-1, YH-40A2-2, YH-40A2-0, YH-40A2-1-0, YH-40A2--2-0, YH-40I1, YH-40I1-0, YH-40R1-0, YH-40R1-1, YH-40R1-2, YH-40R-0, YH-40R-1, YH-40R-2, YH-40J-0, YH-40J-1, YH-40J-2, YH-40LK-0, YH-40LK-1, YH-40LK-2, YH-40D2, YH-30D3, YH-40x-y, YH-15C2, YH-15D2, YH-15CD2 (For model YH-40x-y: Variable x= A, B, C, E, F, S, S1, H; Variable y= 0, 1 or 2; Variables x stand for the shape of control box, variable y stand for the construction of stand base.)
Ratings	220-240V~ or 230V~, 50Hz, Class II; 60W for YH-40D1-1, YH-40A3, YH-40A3-1, YH-40A3-2, YH-40A3-0, YH-40A3-1-0, YH-40A3--2-0, YH-40I, YH-40I-0; 40W for YH-40x-y, YH-30D1-1, YH-40D, YH-40D1, YH-40A1, YH-40A1-1, YH-40A1-2, YH-40A1-0, YH-40A1-1-0, YH-40A1--2-0, YH-40A2, YH-40A2-1, YH-40A2-2, YH-40A2-0, YH-40A2-1-0, YH-40A2--2-0, YH-40I1, YH-40I1-0, YH-40R1-0, YH-40R1-1, YH-40R1-2, YH-40R-0, YH-40R-1, YH-40R-2, YH-40J-0, YH-40J-1, YH-40J-2, YH-40LK-0, YH-40LK-1, YH-40LK-2, YH-40D2; 35W for YH-30D, YH-30D1, YH-30D2, YH-30D3; 20W for YH-23D, YH-23D1, YH-23D1-1; 15W for YH-15D, YH-15D1, YH-15C, YH-15C1, YH-15C2, YH-15D2, YH-15CD2

Testing procedure and testing location:		
☒	CB Testing Laboratory:	Intertek Testing Services Shenzhen Ltd. Guangzhou Branch
Testing location/ address.....:		Block E, No.7-2 Guang Dong Software Science Park, Caipin Road, Guangzhou Science City, GETDD, Guangzhou, China
☐	Associated Laboratory:	N/A
Testing location/ address.....:		N/A
	Tested by (name + signature):	Ray Cen 
	Approved by (+ signature).....:	Marco Liang 
☐	Testing procedure: TMP	N/A
	Tested by (name + signature):	N/A
	Approved by (+ signature).....:	N/A
Testing location/ address.....:		N/A
☐	Testing procedure: WMT	N/A
	Tested by (name + signature):	N/A
	Witnessed by (+ signature):	N/A
	Approved by (+ signature).....:	N/A
Testing location/ address.....:		N/A
☐	Testing procedure: SMT	N/A
	Tested by (name + signature):	N/A
	Approved by (+ signature).....:	N/A
	Supervised by (+ signature)	N/A
Testing location/ address.....:		N/A
☐	Testing procedure: RMT	N/A
	Tested by (name + signature):	N/A
	Approved by (+ signature).....:	N/A
	Supervised by (+ signature)	N/A
Testing location/ address.....:		N/A

List of Attachments (including a total number of pages in each attachment): None	
Summary of testing: The products tested comply with the requirements of EN 60335-1: 2012 + A11:2014 + A13:2017; EN 60335-2-80:2003 + A1:2004 + A2:2009; EN 62233:2008	
Tests performed (name of test and test clause): Original: Full tests were conducted on models YH-15D, YH-23D1-1, YH-30D1, YH-40D1-1, YH-40E-0. Construction check was conducted on all models. The products tested comply with the requirements of these standards. Modification 1: After reviewed, no test was carried out. Modification 2: Test of clause 30.2 was carried on the alternative fan motor capacitor. Modification 3: Clause 20.1 was conducted on models YH-40S1-0, YH-40S1-1, YH-40S1-2, YH-40A3, YH-40A3-1, YH-40A3-2, YH-40A3-0, YH-40A3-1-0, YH-40A3--2-0, YH-40I, YH-40I-0, YH-40A1, YH-40A1-1, YH-40A1-2, YH-40A1-0, YH-40A1-1-0, YH-40A1--2-0, YH-40A2, YH-40A2-1, YH-40A2-2, YH-40A2-0, YH-40A2-1-0, YH-40A2--2-0, YH-40I1 and YH-40I1-0. Modification 4: Full tests were conducted on model YH-40R1-0 with motor '6614-1'. Clause 10, 11, 13 were conducted on model YH-40R-0 with motor '6614-1'. Clause 29 and 30 were conducted on model YH-40J-0 and YH-40LK-0. Construction check was conducted on all models. Modification 5: (for LVD only) Tests of clause 23.5 and 30 were conducted on the alternative components. Modification 6: Construction check was carried out on model YH-15C2, YH-15D2, YH-15CD2 and YH-40D. Test of clause 30.2 was carried out on alternative switch.	Testing location: Intertek Testing Services Shenzhen Ltd. Guangzhou Branch Block E, No.7-2 Guang Dong Software Science Park, Caipin Road, Guangzhou Science City, GETDD, Guangzhou, China
Summary of compliance with National Differences List of countries addressed: European group and Germany. Requirements in German legislation ProdSG and EK decisions for electrical equipment have been taken into account. Risk analysis and evaluation for PAH has been performed.	

☒ The product fulfils the requirements of EN 60335-1:2012+A11:2014+A13:2017; EN 60335-2-80:2003+A1:2004+A2:2009; EN 62233:2008

Copy of marking plate

The artwork below may be only a draft. The use of certification marks on a product must be authorized by the respective NCBs that own these marks.

English

YUCAU HOME APPLIANCES CO.,LTD.
Electric Fan
Model: YH-40D
220-240V~, 50Hz, 40W

Made in China

Songyuanzui Industrial Zone, Dubi Village, Duruan Town, Jiangmen City,
Guangdong Province, China

S/N:XXXXXXXXXX

German

YUCAU HOME APPLIANCES CO.,LTD.
Elektrischer ventilator
Modell: YH-40D
220-240V~, 50Hz, 40W

Made in China

Songyuanzui Industrial Zone, Dubi Village, Duruan Town, Jiangmen City,
Guangdong Province, China

S/N:XXXXXXXXXX

YUCAU HOME APPLIANCES CO.,LTD.
Electric Fan
Model: YH-40D
230V~, 50Hz, 40W

Made in China

Songyuanzui Industrial Zone, Dubi Village, Duruan Town, Jiangmen City,
Guangdong Province, China

S/N:XXXXXXXXXX

YUCAU HOME APPLIANCES CO.,LTD.
Elektrischer ventilator
Modell: YH-40D
230V~, 50Hz, 40W

Made in China

Songyuanzui Industrial Zone, Dubi Village, Duruan Town, Jiangmen City,
Guangdong Province, China

S/N:XXXXXXXXXX

Remark:

1. For the above two different version marking plates, they are all the same except different rated voltage.
2. The marking plates of other models are the same as YH-40D except the model name and rated power.
3. When placing these electrical equipments on the market, the importer and manufacturer should indicate on the electrical equipment his name, registered trade name or registered trade mark and the postal address at which he can be contacted.

Test item particulars

Classification of installation and use Portable appliances

Supply Connection Type Y; Non-detachable cord fitted with a plug

Possible test case verdicts:

- test case does not apply to the test object N/A
- test object does meet the requirement P (Pass)
- test object does not meet the requirement F (Fail)

Testing

Date of receipt of test item	October 23, 2018
Date (s) of performance of tests	October 23, 2018 – November 14, 2018

General remarks:

The test results presented in this report relate only to the object tested.
This report shall not be reproduced, except in full, without the written approval of the Issuing testing laboratory.
"(see Enclosure #)" refers to additional information appended to the report.
"(see appended table)" refers to a table appended to the report.

Throughout this report a ☒ comma / ☐ point is used as the decimal separator.
When determining the test result, measurement uncertainty has been considered.

This report is for the exclusive use of Intertek's Client and is provided pursuant to the agreement between Intertek and its Client. Intertek's responsibility and liability are limited to the terms and conditions of the agreement. Intertek assumes no liability to any party, other than to the Client in accordance with the agreement, for any loss, expense or damage occasioned by the use of this report. Only the Client is authorized to permit copying or distribution of this report and then only in its entirety. Any use of the Intertek name or one of its marks for the sale or advertisement of the tested material, product or service must first be approved in writing by Intertek. The observations and test results in this report are relevant only to the sample tested. This report by itself does not imply that the material, product, or service is or has ever been under an Intertek certification program.

The test report only allows to be revised only within the report defined retention period unless standard or regulation was withdrawn or invalid.

This test report is part of the product evaluation against the requirements of ProdSG in order to obtain the GS-Mark.

PAH test according to AfPS GS 2014:01 PAK is considered and passed, please refer to PAH test report 150618181GZU-PAH1 for details.

Manufacturer's Declaration per sub-clause 6.2.5 of IEC60335-1:

The application for obtaining a CB Test Certificate ☐ Yes
includes more than one factory location and a ☒ Not applicable
declaration from the Manufacturer stating that the
sample(s) submitted for evaluation is (are)
representative of the products from each factory
has been provided

When differences exist; they shall be identified in the General product information section.

Name and address of factory (ies) YUCAU HOME APPLIANCES CO.,LTD.
Songyuanzui Industrial Zone, Dubi Village, Duruan
Town, Jiangmen City, Guangdong Province, China

General product information:

Original:

The appliances are electric fans for household use only. All models have similar construction:

1. YH-15D series and YH-15C series are identical except YH-15C with clip and YH-15D is table fan.
2. YH-23 series, YH-30 series and YH-40D series have similar construction and same material except motor, fan blade size and fan blade quantity. Details refer to photo documents.
3. Models YH-40x-y are the same construction and same material, except the control panel. Details refer to photo documents.
(For model YH-40x-y: Variable x= A, B, C, E, F, S, H; Variable y= 0, 1 or 2;
Variables x stand for the shape of control box, variable y stand for the construction of stand base.)
4. There are two type fan guards for all the models: rhombus type and emanant type. Two fixed

methods are for emanant type fan guard: clip type and hoop type. Details refer to photo documents.
5.Except models YH-40x-1 and YH-40x-2, the other models are less than 3kg.

The details for all models:

Model	Rated power	Motor	Timer	Shape of stand type	Fan type	Fan blade quantity
YH-40A-0	40	6614	No	Cross shape	Stand fan	3
YH-40A-1	40	6614	No	Square shape	Stand fan	3
YH-40A-2	40	6614	No	Circle shape	Stand fan	3
YH-40B-0	40	6614	No	Cross shape	Stand fan	3
YH-40B-1	40	6614	No	Square shape	Stand fan	3
YH-40B-2	40	6614	No	Circle shape	Stand fan	3
YH-40C-0	40	6614	No	Cross shape	Stand fan	3
YH-40C-1	40	6614	No	Square shape	Stand fan	3
YH-40C-2	40	6614	No	Circle shape	Stand fan	3
YH-40E-0	40	6614	Yes	Cross shape	Stand fan	3
YH-40E-1	40	6614	Yes	Square shape	Stand fan	3
YH-40E-2	40	6614	Yes	Circle shape	Stand fan	3
YH-40F-0	40	6614	No	Cross shape	Stand fan	3
YH-40F-1	40	6614	No	Square shape	Stand fan	3
YH-40F-2	40	6614	No	Circle shape	Stand fan	3
YH-40S-0	40	6614	No	Cross shape	Stand fan	3
YH-40S-1	40	6614	No	Square shape	Stand fan	3
YH-40S-2	40	6614	No	Circle shape	Stand fan	3
YH-40H-0	40	6614	No	Cross shape	Stand fan	3
YH-40H-1	40	6614	No	Square shape	Stand fan	3
YH-40H-2	40	6614	No	Circle shape	Stand fan	3
YH-40D	40	6614	No	Circle shape	Table fan	3
YH-40D1	40	6614	No	Circle shape	Table fan	3
YH-40D1-1	60	7118	No	Circle shape	Table fan	5
YH-30D	35	6612	No	Circle shape	Table fan	3
YH-30D1	35	6612	No	Circle shape	Table fan	3
YH-30D1-1	40	6614	No	Circle shape	Table fan	5
YH-30D2	35	6612	No	Circle shape	Table fan	3
YH-23D	20	6016	No	Circle shape	Table fan	3

YH-23D1	20	6016	No	Circle shape	Table fan	3
YH-23D1-1	20	6016	No	Circle shape	Table fan	5
YH-15D	15	4815	No	Circle shape	Table fan	3
YH-15D1	15	4815	No	Circle shape	Table fan	3
YH-15C	15	4815	No	Clip	Clip fan	3
YH-15C1	15	4815	No	Clip	Clip fan	3

Modification 1: (for LVD only)

This test report bases on the original test report 150618181GZU-001 dated September 18, 2015. It is issued because of updating the Low Voltage Directive from 2006/95/EC to 2014/35/EU.

Modification 2:

This test report bases on the original test report 150618181GZU-001 dated September 18, 2015 and 150618181GZU-001 with modification 1 dated November 07, 2016. It is issued because of adding an alternative fan motor capacitor which is manufactured by "Xiongli" in components list. Details refer to table 24.1.

Modification 3:

This test report replaces the original test report 150618181GZU-001 with modification 2 dated December 29, 2016. It is issued because of following additions:

- Adding new models YH-40A3, YH-40A3-1, YH-40A3-2, YH-40A3-0, YH-40A3-1-0, YH-40A3--2-0, YH-40I, YH-40I-0, YH-40S1-0, YH-40S1-1 and YH-40S1-2, which are the same with YH-40D1-1 except control panel and stand base, while the former fans are stand type and the latter is table type;
- Adding new models YH-40A1, YH-40A1-1, YH-40A1-2, YH-40A1-0, YH-40A1-1-0, YH-40A1--2-0, YH-40A2, YH-40A2-1, YH-40A2-2, YH-40A2-0, YH-40A2-1-0, YH-40A2--2-0, YH-40I1 and YH-40I1-0, which are the same with YH-40E-0 except control panel and stand base.

The details for the models:

Model	Rated power	Motor	Timer	Shape of stand type	Fan type	Fan blade quantity
YH-40S1-0	40	6614	No	Cross shape	Stand fan	3
YH-40S1-1	40	6614	No	Square shape	Stand fan	3
YH-40S1-2	40	6614	No	Circle shape	Stand fan	3
YH-40A1	40	6614	No	Cross shape	Stand fan	3
YH-40A1-1	40	6614	No	Square shape	Stand fan	3
YH-40A1-2	40	6614	No	Circle shape	Stand fan	3
YH-40A1-0	40	6614	No	Cross shape	Stand fan	3
YH-40A1-1-0	40	6614	No	Circle shape	Stand fan	3
YH-40A1--2-0	40	6614	No	Circle shape	Stand fan	3
YH-40A2	40	6614	No	Cross shape	Stand fan	3
YH-40A2-1	40	6614	No	Square shape	Stand fan	3

TRF No. IEC60335_2_80E

Intertek Testing Services Shenzhen Ltd. Guangzhou Branch

Block E, No.7-2 Guang Dong Software Science Park, Caipin Road, Guangzhou Science City, GETDD, Guangzhou, China
Tel: 86 20 82139688 Fax: 86 20 32057538 www.intertek-etlsemko.com

YH-40A2-2	40	6614	No	Circle shape	Stand fan	3
YH-40A2-0	40	6614	No	Cross shape	Stand fan	3
YH-40A2-1-0	40	6614	No	Square shape	Stand fan	3
YH-40A2--2-0	40	6614	No	Circle shape	Stand fan	3
YH-40I1	40	6614	No	Circle shape	Stand fan	3
YH-40I1-0	40	6614	No	Circle shape	Stand fan	3
YH-40A3	60	7118	No	Cross shape	Stand fan	5
YH-40A3-1	60	7118	No	Square shape	Stand fan	5
YH-40A3-2	60	7118	No	Circle shape	Stand fan	5
YH-40A3-0	60	7118	No	Cross shape	Stand fan	5
YH-40A3-1-0	60	7118	No	Square shape	Stand fan	5
YH-40A3--2-0	60	7118	No	Circle shape	Stand fan	5
YH-40I	60	7118	No	Circle shape	Stand fan	5
YH-40I-0	60	7118	No	Circle shape	Stand fan	5

Modification 4:

This test report replaces the original test report 150618181GZU-001 with modification 3 dated May 9, 2017. It is issued because of following additions:

1. Add fourteen new models YH-40R1-0, YH-40R1-1, YH-40R1-2, YH-40R-0, YH-40R-1, YH-40R-2, YH-40J-0, YH-40J-1, YH-40J-2, YH-40LK-0, YH-40LK-1, YH-40LK-2, YH-40D2 and YH-30D3,
 - a) YH-40R1-0, YH-40R1-1 and YH-40R1-2 are electronic control type and equipped with synchronous motor and they are same except for stand base.
 - b) YH-40R-0, YH-40R-1 and YH-40R-2 are the same as YH-40R1-0, YH-40R1-1 and YH-40R1-2 respectively except the former don't equipped with synchronous motor.
 - c) YH-40J-0, YH-40J-1 and YH-40J-2 are same with model YH-40A-y except for appearance and speed switch.
 - d) YH-40LK-0, YH-40LK-1 and YH-40LK-2 are same with model YH-40A-y except for appearance.
 - e) YH-40D2 is same with model YH-40D1 except appearance and speed switch.
 - f) YH-30D3 is same with model YH-30D1 except appearance and speed switch.
2. Adding alternative appearance for model YH-15D1.
3. Adding alternative wiring connection construction for speed switch, while the original is soldering connection. Details refer to photo documents.
4. Adding alternative fan motor "6614-1" for models which equipped with the original fan motor "6614". The fan blade quantity may be different for the fan equipping different fan motor. Details refer to below table.
5. Adding alternative plug, supply cord and PVC tube, details refer to table 24.1.
6. Adding three cross shape stand bases and a square shape stand base for alternative. Details refer to photo documents.
7. Adding two alternative fan motor covers for all stand fans and table fans. Details refer to photo documents.
8. Deleted the P0 capacitor.
9. Adding alternative marking plate with rated voltage 230V which is all the same with marking plate

TRF No. IEC60335_2_80E

Intertek Testing Services Shenzhen Ltd. Guangzhou Branch

Block E, No.7-2 Guang Dong Software Science Park, Caipin Road, Guangzhou Science City, GETDD, Guangzhou, China
Tel: 86 20 82139688 Fax: 86 20 32057538 www.intertek-etlsemko.com

with rated voltage 220-240V. Details refer to marking plate.

Modification 5: (for LVD only)

This test report bases on the original test report 150618181GZU-001 with modification 4 dated January 17, 2018. It is issued because of following additions:

1. Add switch "ZD-418" for models YH-40LK-0, YH-40LK-1 and YH-40LK-2, details refer to table 24.1.
2. Add alternative internal wire and PCB, details refer to table 24.1.

The details for all models:

Model	Rated power	Motor	Timer	Shape of stand type	Fan type	Fan blade quantity
YH-40A-0	40	6614, 6614-1	No	Cross shape	Stand fan	3 or 5***
YH-40A-1	40	6614, 6614-1	No	Square shape	Stand fan	3 or 5***
YH-40A-2	40	6614, 6614-1	No	Circle shape	Stand fan	3 or 5***
YH-40B-0	40	6614, 6614-1	No	Cross shape	Stand fan	3 or 5***
YH-40B-1	40	6614, 6614-1	No	Square shape	Stand fan	3 or 5***
YH-40B-2	40	6614, 6614-1	No	Circle shape	Stand fan	3 or 5***
YH-40C-0	40	6614, 6614-1	No	Cross shape	Stand fan	3 or 5***
YH-40C-1	40	6614, 6614-1	No	Square shape	Stand fan	3 or 5***
YH-40C-2	40	6614, 6614-1	No	Circle shape	Stand fan	3 or 5***
YH-40E-0	40	6614, 6614-1	Yes	Cross shape	Stand fan	3 or 5***
YH-40E-1	40	6614, 6614-1	Yes	Square shape	Stand fan	3 or 5***
YH-40E-2	40	6614, 6614-1	Yes	Circle shape	Stand fan	3 or 5***
YH-40F-0	40	6614, 6614-1	No	Cross shape	Stand fan	3 or 5***
YH-40F-1	40	6614, 6614-1	No	Square shape	Stand fan	3 or 5***
YH-40F-2	40	6614, 6614-1	No	Circle shape	Stand fan	3 or 5***
YH-40S-0	40	6614, 6614-1	No	Cross shape	Stand fan	3 or 5***
YH-40S-1	40	6614, 6614-1	No	Square shape	Stand fan	3 or 5***
YH-40S-2	40	6614, 6614-1	No	Circle shape	Stand fan	3 or 5***
YH-40H-0	40	6614, 6614-1	No	Cross shape	Stand fan	3 or 5***
YH-40H-1	40	6614, 6614-1	No	Square shape	Stand fan	3 or 5***
YH-40H-2	40	6614, 6614-1	No	Circle shape	Stand fan	3 or 5***
YH-40D	40	6614, 6614-1	No	Circle shape	Table fan	3 or 5***
YH-40D1	40	6614, 6614-1	No	Circle shape	Table fan	3 or 5***
YH-40D1-1	60	7118	No	Circle shape	Table fan	5
YH-30D	35	6612	No	Circle shape	Table fan	3

YH-30D1	35	6612	No	Circle shape	Table fan	3
YH-30D1-1	40	6614, 6614-1	No	Circle shape	Table fan	5
YH-30D2	35	6612	No	Circle shape	Table fan	3
YH-23D	20	6016	No	Circle shape	Table fan	3
YH-23D1	20	6016	No	Circle shape	Table fan	3
YH-23D1-1	20	6016	No	Circle shape	Table fan	5
YH-15D	15	4815	No	Circle shape	Table fan	3
YH-15D1	15	4815	No	Circle shape	Table fan	3
YH-15C	15	4815	No	Clip	Clip fan	3
YH-15C1	15	4815	No	Clip	Clip fan	3
YH-40S1-0	40	6614, 6614-1	No	Cross shape	Stand fan	3 or 5***
YH-40S1-1	40	6614, 6614-1	No	Square shape	Stand fan	3 or 5***
YH-40S1-2	40	6614, 6614-1	No	Circle shape	Stand fan	3 or 5***
YH-40A1	40	6614, 6614-1	No	Cross shape	Stand fan	3 or 5***
YH-40A1-1	40	6614, 6614-1	No	Square shape	Stand fan	3 or 5***
YH-40A1-2	40	6614, 6614-1	No	Circle shape	Stand fan	3 or 5***
YH-40A1-0	40	6614, 6614-1	No	Cross shape	Stand fan	3 or 5***
YH-40A1-1-0	40	6614, 6614-1	No	Circle shape	Stand fan	3 or 5***
YH-40A1--2-0	40	6614, 6614-1	No	Circle shape	Stand fan	3 or 5***
YH-40A2	40	6614, 6614-1	No	Cross shape	Stand fan	3 or 5***
YH-40A2-1	40	6614, 6614-1	No	Square shape	Stand fan	3 or 5***
YH-40A2-2	40	6614, 6614-1	No	Circle shape	Stand fan	3 or 5***
YH-40A2-0	40	6614, 6614-1	No	Cross shape	Stand fan	3 or 5***
YH-40A2-1-0	40	6614, 6614-1	No	Square shape	Stand fan	3 or 5***
YH-40A2--2-0	40	6614, 6614-1	No	Circle shape	Stand fan	3 or 5***
YH-40I1	40	6614, 6614-1	No	Circle shape	Stand fan	3 or 5***
YH-40I1-0	40	6614, 6614-1	No	Circle shape	Stand fan	3 or 5***
YH-40A3	60	7118	No	Cross shape	Stand fan	5
YH-40A3-1	60	7118	No	Square shape	Stand fan	5
YH-40A3-2	60	7118	No	Circle shape	Stand fan	5
YH-40A3-0	60	7118	No	Cross shape	Stand fan	5
YH-40A3-1-0	60	7118	No	Square shape	Stand fan	5
YH-40A3--2-0	60	7118	No	Circle shape	Stand fan	5
YH-40I	60	7118	No	Circle shape	Stand fan	5

YH-40I-0	60	7118	No	Circle shape	Stand fan	5
YH-40R-0	40	6614, 6614-1	No	Cross shape	Stand fan	3 or 5***
YH-40R-1	40	6614, 6614-1	No	Square shape	Stand fan	3 or 5***
YH-40R-2	40	6614, 6614-1	No	Circle shape	Stand fan	3 or 5***
YH-40R1-0	40	6614, 6614-1	No	Cross shape	Stand fan	3 or 5***
YH-40R1-1	40	6614, 6614-1	No	Square shape	Stand fan	3 or 5***
YH-40R1-2	40	6614, 6614-1	No	Circle shape	Stand fan	3 or 5***
YH-40J-0	40	6614, 6614-1	No	Cross shape	Stand fan	3 or 5***
YH-40J-1	40	6614, 6614-1	No	Square shape	Stand fan	3 or 5***
YH-40J-2	40	6614, 6614-1	No	Circle shape	Stand fan	3 or 5***
YH-40LK-0	40	6614, 6614-1	No	Cross shape	Stand fan	3 or 5***
YH-40LK-1	40	6614, 6614-1	No	Square shape	Stand fan	3 or 5***
YH-40LK-2	40	6614, 6614-1	No	Circle shape	Stand fan	3 or 5***
YH-40D2	40	6614, 6614-1	No	Circle shape	Table fan	3 or 5***
YH-30D3	35	6612	No	Circle shape	Table fan	3

Remark:

- Models YH-40R1-0, YH-40R1-1 and YH-40R1-2 are equipped with synchronous motor, while the other models are not equipped.
- Models YH-40R1-0, YH-40R1-1, YH-40R1-2, YH-40R1-0, YH-40R1-1 and YH-40R1-2 are electronic control type, while the other models are mechanical control type.
- Mass is less than 3kg for all models except the stand fans with square shape or circle shape stand base.

***: the quantity of fan blade is '3' or '5' for fan motor '6614-1', but only '3' for fan motor '6614'.

Modification 6:

This test report replaces the test report 150618181GZU-001 with modification 4 dated January 17, 2018 and 150618181GZU-001 with modification 5 dated April 02, 2018. It is issued because of following additions:

- Update the standards from "EN 60335-1: 2012+A11:2014" to "EN 60335-1: 2012+A11:2014+A13:2017".
- Add alternative plug, supply cord and switch in component list. Refer to table 24.1 for details.
- Add three new models YH-15C2, YH-15D2 and YH-15CD2 which have the same fan motor cover.
 - New model YH-15CD2 is same as model YH-15C except the shape of stand type and fan motor cover
 - New model YH-15C2 is same as new model YH-15CD2 except model YH-15C2 without the decorate cover.
 - New model YH-15D2 is same as model YH-15D except the shape of stand type and fan motor cover.
- Add alternative fan motor cover for model YH-40D.

The details for all models:

Model	Rated power	Motor	Timer	Shape of stand type	Fan type	Fan blade quantity
YH-40A-0	40	6614, 6614-1	No	Cross shape	Stand fan	3 or 5***
YH-40A-1	40	6614, 6614-1	No	Square shape	Stand fan	3 or 5***
YH-40A-2	40	6614, 6614-1	No	Circle shape	Stand fan	3 or 5***

YH-40B-0	40	6614, 6614-1	No	Cross shape	Stand fan	3 or 5***
YH-40B-1	40	6614, 6614-1	No	Square shape	Stand fan	3 or 5***
YH-40B-2	40	6614, 6614-1	No	Circle shape	Stand fan	3 or 5***
YH-40C-0	40	6614, 6614-1	No	Cross shape	Stand fan	3 or 5***
YH-40C-1	40	6614, 6614-1	No	Square shape	Stand fan	3 or 5***
YH-40C-2	40	6614, 6614-1	No	Circle shape	Stand fan	3 or 5***
YH-40E-0	40	6614, 6614-1	Yes	Cross shape	Stand fan	3 or 5***
YH-40E-1	40	6614, 6614-1	Yes	Square shape	Stand fan	3 or 5***
YH-40E-2	40	6614, 6614-1	Yes	Circle shape	Stand fan	3 or 5***
YH-40F-0	40	6614, 6614-1	No	Cross shape	Stand fan	3 or 5***
YH-40F-1	40	6614, 6614-1	No	Square shape	Stand fan	3 or 5***
YH-40F-2	40	6614, 6614-1	No	Circle shape	Stand fan	3 or 5***
YH-40S-0	40	6614, 6614-1	No	Cross shape	Stand fan	3 or 5***
YH-40S-1	40	6614, 6614-1	No	Square shape	Stand fan	3 or 5***
YH-40S-2	40	6614, 6614-1	No	Circle shape	Stand fan	3 or 5***
YH-40H-0	40	6614, 6614-1	No	Cross shape	Stand fan	3 or 5***
YH-40H-1	40	6614, 6614-1	No	Square shape	Stand fan	3 or 5***
YH-40H-2	40	6614, 6614-1	No	Circle shape	Stand fan	3 or 5***
YH-40D	40	6614, 6614-1	No	Circle shape	Table fan	3 or 5***
YH-40D1	40	6614, 6614-1	No	Circle shape	Table fan	3 or 5***
YH-40D1-1	60	7118	No	Circle shape	Table fan	5
YH-30D	35	6612	No	Circle shape	Table fan	3
YH-30D1	35	6612	No	Circle shape	Table fan	3
YH-30D1-1	40	6614, 6614-1	No	Circle shape	Table fan	5
YH-30D2	35	6612	No	Circle shape	Table fan	3
YH-23D	20	6016	No	Circle shape	Table fan	3
YH-23D1	20	6016	No	Circle shape	Table fan	3
YH-23D1-1	20	6016	No	Circle shape	Table fan	5
YH-15D	15	4815	No	Circle shape	Table fan	3
YH-15D1	15	4815	No	Circle shape	Table fan	3
YH-15C	15	4815	No	Clip	Clip fan	3
YH-15C1	15	4815	No	Clip	Clip fan	3
YH-15C2	15	4815	No	Clip	Clip fan	3
YH-15CD2	15	4815	No	Clip	Clip fan	3
YH-15D2	15	4815	No	Circle shape	Table fan	3
YH-40S1-0	40	6614, 6614-1	No	Cross shape	Stand fan	3 or 5***
YH-40S1-1	40	6614, 6614-1	No	Square shape	Stand fan	3 or 5***
YH-40S1-2	40	6614, 6614-1	No	Circle shape	Stand fan	3 or 5***
YH-40A1	40	6614, 6614-1	No	Cross shape	Stand fan	3 or 5***

YH-40A1-1	40	6614, 6614-1	No	Square shape	Stand fan	3 or 5***
YH-40A1-2	40	6614, 6614-1	No	Circle shape	Stand fan	3 or 5***
YH-40A1-0	40	6614, 6614-1	No	Cross shape	Stand fan	3 or 5***
YH-40A1-1-0	40	6614, 6614-1	No	Circle shape	Stand fan	3 or 5***
YH-40A1--2-0	40	6614, 6614-1	No	Circle shape	Stand fan	3 or 5***
YH-40A2	40	6614, 6614-1	No	Cross shape	Stand fan	3 or 5***
YH-40A2-1	40	6614, 6614-1	No	Square shape	Stand fan	3 or 5***
YH-40A2-2	40	6614, 6614-1	No	Circle shape	Stand fan	3 or 5***
YH-40A2-0	40	6614, 6614-1	No	Cross shape	Stand fan	3 or 5***
YH-40A2-1-0	40	6614, 6614-1	No	Square shape	Stand fan	3 or 5***
YH-40A2--2-0	40	6614, 6614-1	No	Circle shape	Stand fan	3 or 5***
YH-40I1	40	6614, 6614-1	No	Circle shape	Stand fan	3 or 5***
YH-40I1-0	40	6614, 6614-1	No	Circle shape	Stand fan	3 or 5***
YH-40A3	60	7118	No	Cross shape	Stand fan	5
YH-40A3-1	60	7118	No	Square shape	Stand fan	5
YH-40A3-2	60	7118	No	Circle shape	Stand fan	5
YH-40A3-0	60	7118	No	Cross shape	Stand fan	5
YH-40A3-1-0	60	7118	No	Square shape	Stand fan	5
YH-40A3--2-0	60	7118	No	Circle shape	Stand fan	5
YH-40I	60	7118	No	Circle shape	Stand fan	5
YH-40I-0	60	7118	No	Circle shape	Stand fan	5
YH-40R-0	40	6614, 6614-1	No	Cross shape	Stand fan	3 or 5***
YH-40R-1	40	6614, 6614-1	No	Square shape	Stand fan	3 or 5***
YH-40R-2	40	6614, 6614-1	No	Circle shape	Stand fan	3 or 5***
YH-40R1-0	40	6614, 6614-1	No	Cross shape	Stand fan	3 or 5***
YH-40R1-1	40	6614, 6614-1	No	Square shape	Stand fan	3 or 5***
YH-40R1-2	40	6614, 6614-1	No	Circle shape	Stand fan	3 or 5***
YH-40J-0	40	6614, 6614-1	No	Cross shape	Stand fan	3 or 5***
YH-40J-1	40	6614, 6614-1	No	Square shape	Stand fan	3 or 5***
YH-40J-2	40	6614, 6614-1	No	Circle shape	Stand fan	3 or 5***
YH-40LK-0	40	6614, 6614-1	No	Cross shape	Stand fan	3 or 5***
YH-40LK-1	40	6614, 6614-1	No	Square shape	Stand fan	3 or 5***
YH-40LK-2	40	6614, 6614-1	No	Circle shape	Stand fan	3 or 5***
YH-40D2	40	6614, 6614-1	No	Circle shape	Table fan	3 or 5***
YH-30D3	35	6612	No	Circle shape	Table fan	3

Remark:

1. Models YH-40R1-0, YH-40R1-1 and YH-40R1-2 are equipped with synchronous motor, while the other models are not equipped.
2. Models YH-40R1-0, YH-40R1-1, YH-40R1-2, YH-40R1-0, YH-40R1-1 and YH-40R1-2 are electronic control type, while the other models are mechanical control type.
3. Mass is less than 3kg for all models except the stand fans with square shape or circle shape stand base.

***: the quantity of fan blade is '3' or '5' for fan motor '6614-1', but only '3' for fan motor '6614'.

IEC 60335-2-80			
Clause	Requirement - Test		Verdict
5	GENERAL CONDITIONS FOR THE TESTS		----
	Tests performed according to clause 5, e.g. nature of supply, sequence of testing, etc.		P
5.7	A Fans to be used in tropical climates, the tests of clause 10,11 and 13 are carried out at 40 °C +/- 2 °C (IEC 60335-2-8)		N/A
	A Fans marked with ambient operating temperature, the tests of clause 10, 11 and 13 are carried out at marked value +/- 2 °C (IEC 60335-2-80/A1)		N/A
6	CLASSIFICATION		----
6.1	Protection against electric shock: Class 0, 0I, I, II, III	Class II	P
6.2	Protection against harmful ingress of water	IPX0	N/A
	A At least IPX2 for Duct fans (IEC 60335-2-80)		N/A
6.101	Classification to climatic conditions : temperate climates, tropical climates (IEC 60335-2-80)	temperate climates	P
7	MARKING AND INSTRUCTIONS		----
7.1	Rated voltage or voltage range (V)..... :	See marking plates	P
	Symbol for nature of supply, or..... :	~	P
	Rated frequency (Hz)..... :	50	P
	Rated power input (W), or..... :	See marking plates	P
	Rated current (A)		N/A
	Manufacturer's or responsible vendor's name, trademark or identification mark	Yucau Electrical Appliances Co., Ltd	P
	Model or type reference		P
	Symbol IEC 60417-5172, for class II appliances		P
	IP number, other than IPX0	IPX0	N/A
	Symbol IEC 60417-5180, for class III appliances, unless		N/A
	the appliance is operated by batteries only		N/A
	Symbol IEC 60417-5036, for the enclosure of electrically-operated water valves in external hose-sets for connection of an appliance to the water mains, if the working voltage exceeds extra-low voltage		N/A

IEC 60335-2-80			
Clause	Requirement - Test	Result - Remark	Verdict
A	For tropical climates marked with letter T (IEC 60335-2-8)		N/A
A	Fans intended for operation in location where the local temperature exceeds 40 °C shall be marked with the ambient operating temperature. (IEC 60335-2-80/A1)		N/A
7.2	Warning for stationary appliances for multiple supply		N/A
	Warning placed in vicinity of terminal cover		N/A
7.3	Range of rated values marked with the lower and upper limits separated by a hyphen		P
	Different rated values marked with the values separated by an oblique stroke		N/A
7.4	Appliances adjustable for different rated voltages, the voltage setting is clearly discernible		N/A
	Requirement met if frequent changes are not required and the rated voltage to which the appliance is to be adjusted is determined from a wiring diagram		N/A
7.5	Appliances with more than one rated voltage or one or more rated voltage ranges, marked with rated input or rated current for each rated voltage or range, unless		N/A
	the power input is related to the arithmetic mean value of the rated voltage range		N/A
	Relation between marking for upper and lower limits of rated power input or rated current and voltage is clear		N/A
7.6	Correct symbols used		P
	Symbol for nature of supply placed next to rated voltage		P
	Symbol for class II appliances placed unlikely to be confused with other marking		P
	Units of physical quantities and their symbols according to international standardized system		P
7.7	Connection diagram fixed to appliances to be connected to more than two supply conductors and appliances for multiple supply, unless		N/A
	correct mode of connection is obvious		N/A
7.8	Except for type Z attachment, terminals for connection to the supply mains indicated as follows:		---
	- marking of terminals exclusively for the neutral conductor (letter N)		N/A

TRF No. IEC60335_2_80E

Intertek Testing Services Shenzhen Ltd. Guangzhou Branch

Block E, No.7-2 Guang Dong Software Science Park, Caipin Road, Guangzhou Science City, GETDD, Guangzhou, China
Tel: 86 20 82139688 Fax: 86 20 32057538 www.intertek-etlsemko.com

IEC 60335-2-80			
Clause	Requirement - Test	Result - Remark	Verdict
	- marking of protective earthing terminals (symbol IEC 60417-5019)		N/A
	- marking not placed on removable parts		N/A
7.9	Marking or placing of switches which may cause a hazard		P
7.10	Indications of switches on stationary appliances and controls on all appliances by use of figures, letters or other visual means..... :	By figures and letters	P
	This applies also to switches which are part of a control		P
	If figures are used, the off position indicated by the figure 0		P
	The figure 0 indicates only OFF position, unless no confusion with the OFF position		P
7.11	Indication for direction of adjustment of controls		P
7.12	Instructions for safe use provided		P
	Details concerning precautions during user maintenance		P
	The instructions state that:		----
	- the appliance is not to be used by persons (including children) with reduced physical, sensory or mental capabilities, or lack of experience and knowledge, unless they have been given supervision or instruction	Replaced by EN 60335-1:2012	N/A
	- children being supervised not to play with the appliance	Replaced by EN 60335-1:2012	N/A
	For a part of class III construction supplied from a detachable power supply unit, the instructions state that the appliance is only to be used with the unit provided		N/A
	Instructions for class III appliances state that it must only be supplied at SELV, unless		N/A
	it is a battery-operated appliance, the battery being charged outside the appliance		N/A
A	For the guards have to be removed purpose for cleaning should: (IEC 60335-2-80/A1)		----
	Ensure that the fan is switched off from the supply mains before removing the guard.		P
7.12.1	Sufficient details for installation supplied		P
	For an appliance intended to be permanently connected to the water mains and not connected by a hose-set, this is stated		N/A

IEC 60335-2-80			
Clause	Requirement - Test	Result - Remark	Verdict
A	The installation instructions include the substance of the following: (IEC 60335-2-8)		----
	- the model or type reference of a luminaire		N/A
	- mounting location for partition fans		N/A
	- The installation height for fans intended to be mounted at high level		N/A
	- that precautions for duct and partition fans.		N/A
7.12.2	Stationary appliances not fitted with means for disconnection from the supply mains having a contact separation in all poles that provide full disconnection under overvoltage category III, the instructions state that means for disconnection must be incorporated in the fixed wiring in accordance with the wiring rules		N/A
7.12.3	Insulation of the fixed wiring in contact with parts exceeding 50 K during clause 11; instructions state that the fixed wiring must be protected		N/A
7.12.4	Instructions for built-in appliances:		----
	- dimensions of space		N/A
	- dimensions and position of supporting and fixing		N/A
	- minimum distances between parts and surrounding structure		N/A
	- minimum dimensions of ventilating openings and arrangement		N/A
	- connection to supply mains and interconnection of separate components		N/A
	- allow disconnection of the appliance after installation, by accessible plug or a switch in the fixed wiring, unless		N/A
	a switch complying with 24.3		N/A
7.12.5	Replacement cord instructions, type X attachment with a specially prepared cord		N/A
	Replacement cord instructions, type Y attachment		P
	Replacement cord instructions, type Z attachment		N/A
7.12.6	Caution in the instructions for appliances incorporating a non-self-resetting thermal cut-out that is reset by disconnection of the supply mains, if this cut-out is required to comply with the standard		N/A
7.12.7	Instructions for fixed appliances stating how the appliance is to be fixed		N/A
7.12.8	Instructions for appliances connected to the water mains:		----
	- max. inlet water pressure (Pa)..... :		N/A

IEC 60335-2-80			
Clause	Requirement - Test	Result - Remark	Verdict
	- min. inlet water pressure, if necessary (Pa) :		N/A
	Instructions concerning new and old hose-sets for appliances connected to the water mains by detachable hose-sets		N/A
7.13	Instructions and other texts in an official language	English and German	P
7.14	Marking clearly legible and durable, rubbing test as specified		P
7.15	Markings on a main part		P
	Marking clearly discernible from the outside, if necessary after removal of a cover		P
	For portable appliances, cover can be removed or opened without a tool		P
	For stationary appliances, name, trademark or identification mark and model or type reference visible after installation		N/A
	For fixed appliances, name, trademark or identification mark and model or type reference visible after installation according to the instructions		N/A
	Indications for switches and controls placed on or near the components. Marking not on parts which can be positioned or repositioned in such a way that the marking is misleading		P
7.16	Marking of a possible replaceable thermal link or fuse link clearly visible with regard to replacing the link		N/A
8	PROTECTION AGAINST ACCESS TO LIVE PARTS		----
8.1	Adequate protection against accidental contact with live parts		P
8.1.1	Requirement applies for all positions, detachable parts removed		P
	Lamps behind a detachable cover not removed, if conditions met		N/A
	Insertion or removal of lamps, protection against contact with live parts of the lamp cap		N/A
	Use of test probe B of IEC 61032, with a force not exceeding 1 N: no contact with live parts		P
A	Lamps are not removed. However, during insertion or removal of lamps, no contact with live parts of the lamp cap. (IEC 60335-2-8)		N/A
8.1.2	Use of test probe 13 of IEC 61032, with a force not exceeding 1 N, through openings in class 0 appliances and class II appliances/constructions: no contact with live parts		P

IEC 60335-2-80			
Clause	Requirement - Test	Result - Remark	Verdict
	Test probe 13 also applied through openings in earthed metal enclosures having a non-conductive coating: no contact with live parts		N/A
8.1.3	For appliances other than class II, use of test probe 41 of IEC 61032, with a force not exceeding 1 N: no contact with live parts of visible glowing heating elements		N/A
8.1.4	Accessible part not considered live if:		----
	- safety extra-low a.c. voltage: peak value not exceeding 42.4 V		N/A
	- safety extra-low d.c. voltage: not exceeding 42.4 V		N/A
	- or separated from live parts by protective impedance		N/A
	If protective impedance: d.c. current not exceeding 2 mA, and		N/A
	a.c. peak value not exceeding 0.7 mA		N/A
	- for peak values over 42.4 V up to and including 450 V, capacitance not exceeding 0,1 µF		N/A
	- for peak values over 450 V up to and including 15 kV, discharge not exceeding 45 µC		N/A
	- for peak values over 15kV, the energy in the discharge not exceeding 350 mJ		N/A
8.1.5	Live parts protected at least by basic insulation before installation or assembly:		----
	- built-in appliances		N/A
	- fixed appliances		N/A
	- appliances delivered in separate units		N/A
8.2	Class II appliances and constructions constructed so that there is adequate protection against accidental contact with basic insulation and metal parts separated from live parts by basic insulation only		P
	Only possible to touch parts separated from live parts by double or reinforced insulation		P
8.2	A Remove the detachable parts for user maintenance purpose, the basic insulation of internal wiring may be touched provide the equivalent insulating of cords complying with IEC 60227 or IEC 60245. (IEC 60335-2-80/A1)		N/A
9	STARTING OF MOTOR-OPERATED APPLIANCES		----
	Requirements and tests are specified in part 2 when necessary		N/A

IEC 60335-2-80			
Clause	Requirement - Test	Result - Remark	Verdict
10	POWER INPUT AND CURRENT		----
10.1	Power input at normal operating temperature, rated voltage and normal operation not deviating from rated power input by more than shown in table 1. :	(see appended table)	P
	Test carried out at upper and lower limits of the ranges for appliances with one or more rated voltage ranges, unless		N/A
	the rated power input is related to the arithmetic mean value		P
A	Appliances are tested with shutters or similar devices in the open position.(IEC 60335-2-80)		N/A
10.2	Current at normal operating temperature, rated voltage and normal operation not deviating from rated current by more than shown in table 2 :	(see appended table)	N/A
	Test carried out at upper and lower limits of the ranges for appliances with one or more rated voltage ranges, unless		N/A
	the rated current is related to the arithmetic mean value of the range		N/A
A	Appliances are tested with shutters or similar devices in the open position. (IEC 60335-2-80)		N/A
11	HEATING		----
11.1	No excessive temperatures in normal use		P
11.2	The appliance is held, placed or fixed in position as described :		P
11.3	Temperature rises, other than of windings, determined by thermocouples		P
	Temperature rises of windings determined by resistance method, unless		P
	the windings are non-uniform or it is difficult to make the necessary connections		N/A
11.4	Heating appliances operated under normal operation at 1.15 times rated power input (W) :		N/A
11.5	Motor-operated appliances operated under normal operation at most unfavourable voltage between 0.94 and 1.06 times rated voltage (V) :	240X1,06=254,4 V	P
11.6	Combined appliances operated under normal operation at most unfavourable voltage between 0.94 and 1.06 times rated voltage (V) :		N/A
11.7 R	Appliances are operated until steady conditions are established. (IEC 60335-2-80)		P
11.8	Temperature rises monitored continuously and not exceeding the values in table 3 :	(see appended table)	P

TRF No. IEC60335_2_80E

Intertek Testing Services Shenzhen Ltd. Guangzhou Branch

Block E, No.7-2 Guang Dong Software Science Park, Caipin Road, Guangzhou Science City, GETDD, Guangzhou, China
Tel: 86 20 82139688 Fax: 86 20 32057538 www.intertek-etlsemko.com

IEC 60335-2-80			
Clause	Requirement - Test	Result - Remark	Verdict
	If the temperature rise of a motor winding exceeds the value of table 3, or		N/A
	if there is doubt with regard to classification of insulation,		N/A
	tests of Annex C are carried out		N/A
	Sealing compound does not flow out		P
	Protective devices do not operate, except		P
	components in protective electronic circuits tested for the number of cycles specified in 24.1.4		N/A
A	The temperature rise limits for appliances for tropical climates are reduced by 15 K. (IEC 60335-2-80)		N/A
A	The temperature rise limits for fans marked with an ambient operating temperature are reduced by the difference between the marked value and 25 °C. (IEC 60335-2-80/A1)		N/A
13	LEAKAGE CURRENT AND ELECTRIC STRENGTH AT OPERATING TEMPERATURE		----
13.1	Leakage current not excessive and electric strength adequate		P
	Heating appliances operated at 1.15 times the rated power input (W)		N/A
	Motor-operated appliances and combined appliances supplied at 1.06 times the rated voltage (V)	240X1,06=254,4 V	P
	Protective impedance and radio interference filters disconnected before carrying out the tests		N/A
13.2	For class 0, class II and class III appliances, leakage current measured by means of the circuit described in figure 4 of IEC 60990		P
	For other appliances, a low impedance ammeter may be used		N/A
	Leakage current measurements	(see appended table)	P
13.3	The appliance is disconnected from the supply		P
	Electric strength tests according to table 4.....	(see appended table)	P
	No breakdown during the tests		P
14	TRANSIENT OVERVOLTAGES		----
	Appliances withstand the transient over-voltages to which they may be subjected		N/A

IEC 60335-2-80			
Clause	Requirement - Test	Result - Remark	Verdict
	Clearances having a value less than specified in table 16 subjected to an impulse voltage test, the test voltage specified in table 6..... :	(see appended table)	N/A
	No flashover during the test, unless		N/A
	of functional insulation if the appliance complies with clause 19 with the clearance short-circuited		N/A
15	MOISTURE RESISTANCE		----
15.1	Enclosure provides the degree of moisture protection according to classification of the appliance		N/A
	Compliance checked as specified in 15.1.1, taking into account 15.1.2, followed by the electric strength test of 16.3		N/A
	No trace of water on insulation which can result in a reduction of clearances or creepage distances below values specified in clause 29		N/A
15.1.1	Appliances, other than IPX0, subjected to tests as specified in IEC 60529..... :		N/A
	Water valves containing live parts in external hoses for connection of an appliance to the water mains tested as specified for IPX7 appliances		N/A
A	The outer part of fans to be installed in the external structure is subjected to subclause 14.2.4(a) of IEC 60529. The outer part of fans is not to be installed in the external structure is protected against the water. (IEC 60335-2-80/A1)		N/A
A	The fans supplied as rated voltage with shutters or similar devices being the open position. (IEC 60335-2-80/A1)		N/A
15.1.2	Hand-held appliance turned continuously through the most unfavourable positions during the test		N/A
	Built-in appliances installed according to the instructions		N/A
	Appliances placed or used on the floor or table placed on a horizontal unperforated support		N/A
	Appliances normally fixed to a wall and appliances with pins for insertion into socket-outlets are mounted on a wooden board		N/A
	For IPX3 appliances, the base of wall mounted appliances is placed at the same level as the pivot axis of the oscillating tube		N/A
	For IPX4 appliances, the horizontal centre line of the appliance is aligned with the pivot axis of the oscillating tube, and		N/A

IEC 60335-2-80			
Clause	Requirement - Test	Result - Remark	Verdict
	for appliances normally used on the floor or table, the movement is limited to two times 90° for a period of 5 min, the support being placed at the level of the pivot axis of the oscillating tube		N/A
	Wall-mounted appliances, take into account the distance to the floor stated in the instructions		N/A
	Appliances normally fixed to a ceiling are mounted underneath a horizontal unperforated support, the pivot axis of the oscillating tube located at the level of the underside of the support, and		N/A
	for IPX4 appliances, the movement of the tube is limited to two times 90° from the vertical for a period of 5 min		N/A
	Appliances with type X attachment fitted with a flexible cord as described		N/A
	Detachable parts subjected to the relevant treatment with the main part		N/A
	However, if a part has to be removed for user maintenance and a tool is needed, this part is not removed		N/A
15.2	Spillage of liquid does not affect the electrical insulation		N/A
	Appliances with type X attachment fitted with a flexible cord as described		N/A
	Appliances incorporating an appliance inlet tested with or without an connector, whichever is most unfavourable		N/A
	Detachable parts are removed		N/A
	Overfilling test with additional amount of water, over a period of 1 min (I) :		N/A
	The appliance withstands the electric strength test of 16.3		N/A
	No trace of water on insulation that can result in a reduction of clearances or creepage distances below values specified in clause 29		N/A
15.3	Appliances proof against humid conditions		P
	Checked by test Cab: Damp heat steady state in IEC 60068-2-78		P
	Detachable parts removed and subjected, if necessary, to the humidity test with the main part		P
	Humidity test for 48 h in a humidity cabinet		P
	Reassembly of those parts that may have been removed		P

IEC 60335-2-80			
Clause	Requirement - Test	Result - Remark	Verdict
	The appliance withstands the tests of clause 16		P
16	LEAKAGE CURRENT AND ELECTRIC STRENGTH		----
16.1	Leakage current not excessive and electric strength adequate		P
	Protective impedance disconnected from live parts before carrying out the tests		N/A
	Tests carried out at room temperature and not connected to the supply		P
16.2	Single-phase appliances: test voltage 1.06 times rated voltage (V)	240X1,06=254,4 V	P
	Three-phase appliances: test voltage 1.06 times rated voltage divided by $\sqrt{3}$ (V)		N/A
	Leakage current measurements	(see appended table)	P
	Limit values doubled if:		----
	- all controls have an off position in all poles, or		N/A
	- the appliance has no control other than a thermal cut-out, or		N/A
	- all thermostats, temperature limiters and energy regulators do not have an off position, or		N/A
	- the appliance has radio interference filters		N/A
	With the radio interference filters disconnected, the leakage current do not exceed limits specified		N/A
16.3	Electric strength tests according to table 7	(see appended table)	P
	Test voltage applied between the supply cord and inlet bushing and cord guard and cord anchorage as specified	(see appended table)	P
	No breakdown during the tests		P
17	OVERLOAD PROTECTION OF TRANSFORMERS AND ASSOCIATED CIRCUITS		----
	No excessive temperatures in transformer or associated circuits in event of short-circuits likely to occur in normal use		N/A
	Appliance supplied with 1.06 or 0.94 times rated voltage under the most unfavourable short-circuit or overload likely to occur in normal use (V).....		N/A
	Basic insulation is not short-circuited		N/A
	Temperature rise of insulation of the conductors of safety extra-low voltage circuits not exceeding the relevant value specified in table 3 by more than 15 K		N/A
	Temperature of the winding not exceeding the value specified in table 8		N/A

TRF No. IEC60335_2_80E

Intertek Testing Services Shenzhen Ltd. Guangzhou Branch

Block E, No.7-2 Guang Dong Software Science Park, Caipin Road, Guangzhou Science City, GETDD, Guangzhou, China
Tel: 86 20 82139688 Fax: 86 20 32057538 www.intertek-etlsemko.com

IEC 60335-2-80			
Clause	Requirement - Test	Result - Remark	Verdict
	However, limits do not apply to fail-safe transformers complying with sub-clause 15.5 of IEC 61558-1		N/A
18	ENDURANCE		----
	Requirements and tests are specified in part 2 when necessary		N/A
19	ABNORMAL OPERATION		----
19.1	The risk of fire, mechanical damage or electric shock under abnormal or careless operation obviated		P
	Electronic circuits so designed and applied that a fault will not render the appliance unsafe :		P
	Appliances incorporating heating elements subjected to the tests of 19.2 and 19.3, and		N/A
	if the appliance also has a control that limit the temperature during clause 11 it is subjected to the test of 19.4, and		N/A
	if applicable, to the test of 19.5		N/A
	Appliances incorporating PTC heating elements are also subjected to the test of 19.6		N/A
	Appliances incorporating motors subjected to the tests of 19.7 to 19.10, as applicable		P
	Appliances incorporating electronic circuits subjected to the tests of 19.11 and 19.12, as applicable		P
	Appliances incorporating contactors or relays subjected to the test of 19.14, being carried out before the tests of 19.11		N/A
	Appliances incorporating voltage selector switches subjected to the test of 19.15		N/A
	Unless otherwise specified, the tests are continued until a non-self-resetting thermal cut-out operates, or		P
	until steady conditions are established		P
	If a heating element or intentionally weak part becomes open-circuited, the relevant test is repeated on a second sample		N/A
A	Fans incorporating shutters or similar subjected to the test of cl. 19.101 (IEC 60335-2-80)		N/A
19.2	Test of appliances with heating elements with restricted heat dissipation; test voltage (V), power input of 0.85 times rated power input (W)..... :		N/A

IEC 60335-2-80			
Clause	Requirement - Test	Result - Remark	Verdict
19.3	Test of 19.2 repeated; test voltage (V), power input of 1.24 times rated power input (W)		N/A
19.4	Test conditions as in clause 11, any control limiting the temperature during tests of clause 11 short-circuited		N/A
19.5	Test of 19.4 repeated on Class 0I and I appliances with tubular sheathed or embedded heating elements. No short-circuiting, but one end of the element connected to the sheath		N/A
	The test repeated with reversed polarity and the other end of the heating element connected to the sheath		N/A
	The test is not carried out on appliances intended to be permanently connected to fixed wiring and on appliances where an all-pole disconnection occurs during the test of 19.4		N/A
19.6	Appliances with PTC heating elements tested at rated voltage, establishing steady conditions		N/A
	The working voltage of the PTC heating element is increased by 5% and the appliance is operated until steady conditions are re-established. The voltage is then increased in similar steps until 1.5 times working voltage or until the PTC heating element ruptures (V)		N/A
19.7	Stalling test by locking the rotor if the locked rotor torque is smaller than the full load torque, or		P
	locking moving parts of other appliances		P
	Locked rotor, capacitors open-circuited one at a time		P
	Test repeated with capacitors short-circuited one at a time, unless		N/A
	capacitor is of class P2 of IEC 60252-1		P
	Appliances with timer or programmer supplied with rated voltage for each of the tests, for a period equal to the maximum period allowed		N/A
	Other appliances supplied with rated voltage for a period as specified		P
	Winding temperatures not exceeding values specified in table 8	(see appended table)	P

IEC 60335-2-80			
Clause	Requirement - Test	Result - Remark	Verdict
A	Mounting of separate control (IEC 60335-2-8)		N/A
	Approximately 50 % of the area of each ventilating opening is blocked. (IEC 60335-2-8)		N/A
	Winding temperatures not exceeding values specified in table 8 (IEC 60335-2-8)	(see appended table)	N/A
	The temperature rise of the board not exceed: (IEC 60335-2-8)		----
	– 50 K, for appliances with T marking;		N/A
	– 65 K, for other appliances.		N/A
19.8	Multi-phase motors operated at rated voltage with one phase disconnected		N/A
19.9	Not applicable. (IEC 60335-2-8)		N/A
19.10	Series motor operated at 1.3 times rated voltage for 1 min (V)		N/A
	During the test, parts not being ejected from the appliance		N/A
19.11	Electronic circuits, compliance checked by evaluation of the fault conditions specified in 19.11.2 for all circuits or parts of circuits, unless		P
	they comply with the conditions specified in 19.11.1		P
	Appliances incorporating an electronic circuit that relies upon a programmable component to function correctly, subjected to the test of 19.11.4.8, unless		N/A
	restarting does not result in a hazard		N/A
	Appliances having a device with an off position obtained by electronic disconnection, or a device placing the appliance in a stand-by mode, subjected to the tests of 19.11.4	No dangerous malfunction	N/A
	If the safety of the appliance under any of the fault conditions depends on the operation of a miniature fuse-link complying with IEC 60127, the test of 19.12 is carried out		P
	During and after each test the following is checked:		----
	- the temperature of the windings do not exceed the values specified in table 8		P
	- the appliance complies with the conditions specified in 19.13		P
	- any current flowing through protective impedance not exceeding the limits specified in 8.1.4		N/A
	If a conductor of a printed board becomes open-circuited, the appliance is considered to have withstood the particular test, provided both of the following conditions are met:		----

IEC 60335-2-80			
Clause	Requirement - Test	Result - Remark	Verdict
	- the base material of the printed circuit board withstands the test of Annex E		N/A
	- any loosened conductor does not reduce clearance or creepage distances between live parts and accessible metal parts below the values specified in clause 29		N/A
19.11.1	Fault conditions a) to g) in 19.11.2 are not applied to circuits or parts of circuits meeting both of the following conditions:		----
	- the electronic circuit is a low-power circuit, that is, the maximum power at low-power points does not exceed 15 W according to the tests specified	For YH-40R1-0: After EC1: 0,26 W	P
	- the protection against electric shock, fire hazard, mechanical hazard or dangerous malfunction of other parts of the appliance does not rely on the correct functioning of the electronic circuit		P
19.11.2	Fault conditions applied one at a time, the appliance operating under conditions specified in clause 11, but supplied at rated voltage, duration of the tests as specified:		----
	a) short circuit of functional insulation if clearances or creepage distances are less than the values specified in clause 29		P
	b) open circuit at the terminals of any component		P
	c) short circuit of capacitors, unless		P
	they comply with IEC 60384-14		P
	d) short circuit of any two terminals of an electronic component, other than integrated circuits		P
	This fault condition is not applied between the two circuits of an optocoupler		N/A
	e) failure of triacs in the diode mode		N/A
	f) failure of microprocessors and integrated circuits		N/A
	g) failure of an electronic power switching device		N/A
	Each low power circuit is short-circuited by connecting the low-power point to the pole of the supply source from which the measurements were made		P
19.11.3	If the appliance incorporates a protective electronic circuit which operates to ensure compliance with clause 19, the relevant test is repeated with a single fault simulated, as indicated in a) to g) of 19.11.2		N/A
19.11.4	Appliances having a device with an off position obtained by electronic disconnection, or		N/A
	a device that can be placed in the stand-by mode,		N/A

IEC 60335-2-80			
Clause	Requirement - Test	Result - Remark	Verdict
	subjected to the tests of 19.11.4.1 to 19.11.4.7, the device being set in the off position or in the stand-by mode		N/A
	Appliances incorporating a protective electronic circuit subjected to the tests of 19.11.4.1 to 19.11.4.7, the tests being carried out after the protective electronic circuit has operated, except that		N/A
	appliances operated for 30 s or 5 min during the test of 19.7 are not subjected to the tests for electromagnetic phenomena.		N/A
	Surge protective devices disconnected, unless		N/A
	They incorporate spark gaps		N/A
19.11.4.1	The appliance is subjected to electrostatic discharges in accordance with IEC 61000-4-2, test level 4		N/A
19.11.4.2	The appliance is subjected to radiated fields in accordance with IEC 61000-4-3, test level 3		N/A
19.11.4.3	The appliance is subjected to fast transient bursts in accordance with IEC 61000-4-4, test level 3 or 4 as specified		N/A
19.11.4.4	The power supply terminals of the appliance subjected to voltage surges in accordance with IEC 61000-4-5, test level 3 or 4 as specified		N/A
	Earthed heating elements in class I appliances disconnected		N/A
19.11.4.5	The appliance is subjected to injected currents in accordance with IEC 61000-4-6, test level 3		N/A
19.11.4.6	Appliances having a rated current not exceeding 16 A are subjected to the Class 3 voltage dips and interruptions in accordance with IEC 61000-4-11		N/A
	Appliances having a rated current exceeding 16 A are subjected to the Class 3 voltage dips and interruptions in accordance with IEC 61000-4-34		N/A
19.11.4.7	The appliance is subjected to mains signals in accordance with IEC 61000-4-13, test level class 2		N/A
19.11.4.8	The appliance is supplied at rated voltage and operated under normal operation. After 60s the power supply is reduced to a level such that the appliance ceases to respond or parts controlled by the programmable component cease to operate		N/A
	The appliance continues to operate normally, or		N/A
	requires a manual operation to restart		N/A

IEC 60335-2-80			
Clause	Requirement - Test	Result - Remark	Verdict
19.12	If the safety of the appliance for any of the fault conditions specified in 19.11.2 depends on the operation of a miniature fuse-link complying with IEC 60127, the test is repeated, measuring the current flowing through the fuse-link; measured current (A); rated current of the fuse-link (A) :	Rated: 2A, Measured: >10A	P
19.13	During the tests the appliance does not emit flames, molten metal, poisonous or ignitable gas in hazardous amounts		P
	Temperature rises not exceeding the values shown in table 9 :	(see appended table)	P
	Compliance with clause 8 not impaired		P
	If the appliance can still be operated it complies with 20.2		P
	Insulation, other than of class III appliances or class III constructions that do not contain live parts, withstands the electric strength test of 16.3, the test voltage as specified in table 4:		----
	- basic insulation (V) :	1000	P
	- supplementary insulation (V) :	1750	P
	- reinforced insulation (V) :	3000	P
	After operation or interruption of a control, clearances and creepage distances across the functional insulation withstand the electric strength test of 16.3, the test voltage being twice the working voltage		P
	The appliance does not undergo a dangerous malfunction, and		P
	no failure of protective electronic circuits, if the appliance is still operable		N/A
	Appliances tested with an electronic switch in the off position, or in the stand-by mode:		----
	- do not become operational, or		N/A
	- if they become operational, do not result in a dangerous malfunction during or after the tests of 19.11.4		N/A
	If the appliance contains lids or doors that are controlled by one or more interlocks, one of the interlocks may be released provided that:		----
	- the lid or door does not move automatically to an open position when the interlock is released, and		N/A
	- the appliance does not start after the cycle in which the interlock was released		N/A

IEC 60335-2-80			
Clause	Requirement - Test	Result - Remark	Verdict
19.14	Appliances operated under the conditions of clause 11, any contactor or relay contact operating under the conditions of clause 11 being short-circuited		N/A
	For a relay or contactor with more than one contact, all contacts are short-circuited at the same time		N/A
	A relay or contactor operating only to ensure the appliance is energized for normal use is not short-circuited		N/A
	If more than one relay or contactor operates in clause 11, they are short-circuited in turn		N/A
19.15	For appliances with a mains voltage selector switch, the switch is set to the lowest rated voltage position and the highest value of rated voltage is applied		N/A
19.101	Fans incorporating shutters or similar that are operated automatically are supplied at rated voltage in the closed or open position, whichever is more unfavourable (IEC 60335-2-80)		N/A
20	STABILITY AND MECHANICAL HAZARDS		----
20.1	Appliances having adequate stability		P
	Tilting test through an angle of 10°, appliance placed on an inclined plane/horizontal support, not connected to the supply mains; appliance does not overturn		P
	Tilting test repeated on appliances with heating elements, angle of inclination increased to 15°		N/A
	Possible heating test in overturned position; temperature rise does not exceed values shown in table 9		N/A
A	Portable pedestal fans exceeding 1,7 m and exceeding 10 kg tested with a force of 40 N at 1,5 m. (IEC 60335-2-80)		N/A
20.2	Moving parts adequately arranged or enclosed as to provide protection against personal injury		P
	Protective enclosures, guards and similar parts are non-detachable, and		P
	have adequate mechanical strength		P
	Enclosures that can be opened by overriding an interlock are considered to be detachable parts		N/A
	Self-resetting thermal cut-outs and overcurrent protective devices not causing a hazard by unexpected closure		N/A
	Not possible to touch dangerous moving parts with the test probe described		P

TRF No. IEC60335_2_80E

Intertek Testing Services Shenzhen Ltd. Guangzhou Branch

Block E, No.7-2 Guang Dong Software Science Park, Caipin Road, Guangzhou Science City, GETDD, Guangzhou, China
Tel: 86 20 82139688 Fax: 86 20 32057538 www.intertek-etlsemko.com

IEC 60335-2-80			
Clause	Requirement - Test	Result - Remark	Verdict
20.101	Fan blades, other than those for mounting at high level, shall be guarded, unless: (IEC 60335-2-80)		P
	-they have a hardness less than D 60 Shore, or		N/A
	-they have a peripheral speed less than 15 m/s when the fan is supplied at rated voltage, or		N/A
	-the fan has a power output not exceeding 2 W when supplied at rated voltage.		N/A
21	MECHANICAL STRENGTH		----
21.1	Appliance has adequate mechanical strength and is constructed as to withstand rough handling		P
	Checked by applying 3 blows to every point of the enclosure like to be weak, in accordance with test Ehb of IEC 60068-2-75, spring hammer test, with an impact energy of 0,5 J		P
	The appliance shows no damage impairing compliance with this standard, and		P
	compliance with 8.1, 15.1 and clause 29 not impaired		P
	If doubt, supplementary or reinforced insulation subjected to the electric strength test of 16.3		N/A
	If necessary, repetition of groups of three blows on a new sample		N/A
21.2	Accessible parts of solid insulation having strength to prevent penetration by sharp implements		P
	Test not applicable if the thickness of supplementary insulation is at least 1 mm and reinforced insulation at least 2 mm		P
	The insulation is tested as specified, and does withstand the electric strength test of 16.3		N/A
21.101	Fan guards are subjected to a push and pull force of 20 N. Dangerous moving parts are not accessible (IEC 60335-2-80)		P
	The test probe is applied with a force not exceeding 5N. (IEC 60335-2-80/A2)		P
21.102	Ceiling fans have adequate strength. Load four times mass (.....) (IEC 60335-2-80)		N/A
22	CONSTRUCTION		----
22.1	Appliance marked with the first numeral of the IP system, relevant requirements of IEC 60529 are fulfilled		N/A

IEC 60335-2-80			
Clause	Requirement - Test	Result - Remark	Verdict
A	NOTE 101 The enclosure defined in IEC 60529 does not include guards for fan blades. (IEC 60335-2-80)		N/A
22.2	Stationary appliance: means to ensure all-pole disconnection from the supply being provided:		----
	- a supply cord fitted with a plug, or		N/A
	- a switch complying with 24.3, or		N/A
	- a statement in the instruction sheet that a disconnection incorporated in the fixed wiring is to be provided, or		N/A
	- an appliance inlet		N/A
	Singe-pole switches and single-pole protective devices for the disconnection of heating elements in single-phase, permanently connected class 01 and class I appliances, connected to the phase conductor		N/A
22.3	Appliance provided with pins: no undue strain on socket-outlets		N/A
	Applied torque not exceeding 0.25 Nm		N/A
	Pull force of 50N to each pin after the appliance has being placed in the heating cabinet; when cooled to room temperature the pins are not displaced by more than 1mm		N/A
	Each pin subjected to a torque of 0.4Nm; the pins are not rotating, unless		N/A
	rotating does not impair compliance with this standard		N/A
22.4	Appliance for heating liquids and appliance causing undue vibration not provided with pins for insertion into socket-outlets		P
22.5	No risk of electric shock when touching the pins of the plug, for appliances having a capacitor with rated capacitance exceeding 0,1μF, the appliance being disconnected from the supply at the instant of voltage peak		P
	Voltage not exceeding 34 V (V) :	Max. 28V	P
22.6	Electrical insulation not affected by condensing water or leaking liquid		N/A
	Electrical insulation of Class II appliances not affected if a hose ruptures or seal leaks		N/A
	In case of doubt, test as described		N/A

IEC 60335-2-80			
Clause	Requirement - Test	Result - Remark	Verdict
22.7	Adequate safeguards against the risk of excessive pressure in appliances containing liquid or gases or having steam-producing devices		N/A
22.8	Electrical connections not subject to pulling during cleaning of compartments to which access can be gained without the aid of a tool, and that are likely to be cleaned in normal use		N/A
22.9	Insulation, internal wiring, windings, commutators and slip rings not exposed to oil, grease or similar substances, unless		P
	the substance has adequate insulating properties		N/A
22.10	Not possible to reset voltage-maintained non-self-resetting thermal cut-outs by the operation of an automatic switching device incorporated within the appliance, if:		N/A
	- a non-self-resetting thermal cut-out is required by the standard, and		N/A
	- a voltage maintained non-self-resetting thermal cut-out is used to meet it		N/A
	Non-self-resetting thermal motor protectors have a trip-free action, unless		N/A
	they are voltage maintained		N/A
	Reset buttons of non-self-resetting controls so located or protected that accidental resetting is unlikely		N/A
22.11	Reliable fixing of non-detachable parts that provide the necessary degree of protection against electric shock, moisture or contact with moving parts		P
	Obvious locked position of snap-in devices used for fixing such parts		P
	No deterioration of the fixing properties of snap-in devices used in parts that are likely to be removed during installation or servicing		P
M	The 50 N force is not applied to clips used to fasten fan guards. (IEC 60335-2-80)		P
	Instead, a force of 15 N is applied in any direction to the clips in an attempt to release them. (IEC 60335-2-80)		P
	Tests as described		P
22.12	Handles, knobs etc. fixed in a reliable manner		P
	Fixing in wrong position of handles, knobs etc. indicating position of switches or similar components not possible		P

IEC 60335-2-80			
Clause	Requirement - Test	Result - Remark	Verdict
	Axial force 15 N applied to parts, the shape being so that an axial pull is unlikely to be applied		N/A
	Axial force 30 N applied to parts, the shape being so that an axial pull is likely to be applied		P
22.13	Unlikely that handles, when gripped as in normal use, make the operator's hand touch parts having a temperature rise exceeding the value specified for handles which are held for short periods only		N/A
22.14	No ragged or sharp edges creating a hazard for the user in normal use, or during user maintenance		P
	No exposed pointed ends of self-tapping screws or other fasteners, likely to be touched by the user in normal use or during user maintenance		P
22.15	Storage hooks and the like for flexible cords smooth and well rounded		N/A
22.16	Automatic cord reels cause no undue abrasion or damage to the sheath of the flexible cord, no breakage of conductors strands and no undue wear of contacts		N/A
	Cord reel tested with 6000 operations, as specified		N/A
	Electric strength test of 16.3, voltage of 1000 V applied		N/A
22.17	Spacers not removable from the outside by hand or by means of a screwdriver or a spanner		N/A
22.18	Current-carrying parts and other metal parts resistant to corrosion		N/A
22.19	Driving belts not relied upon to provide the required level of insulation, unless		N/A
	constructed to prevent inappropriate replacement		N/A
22.20	Direct contact between live parts and thermal insulation effectively prevented, unless		N/A
	material used is non-corrosive, non-hygroscopic and non-combustible		N/A
22.21	Wood, cotton, silk, ordinary paper and fibrous or hygroscopic material not used as insulation, unless		P
	impregnated		N/A
	This requirement does not apply to magnesium oxide and mineral ceramic fibres used for the electrical insulation of heating elements		N/A
22.22	Appliances not containing asbestos		P
22.23	Oils containing polychlorinated biphenyl (PCB) not used		N/A

IEC 60335-2-80			
Clause	Requirement - Test	Result - Remark	Verdict
22.24	Bare heating elements, except in class III appliances or class III constructions that do not contain live parts, adequately supported		N/A
	In case of rupture, the heating conductor is unlikely to come in contact with accessible metal parts		N/A
22.25	Sagging heating conductors, except in class III appliances or class III constructions that do not contain live parts, cannot come into contact with accessible metal parts		N/A
22.26	For class III constructions the insulation between parts operating at safety extra-low voltage and other live parts complies with the requirements for double or reinforced insulation		N/A
22.27	Parts connected by protective impedance separated by double or reinforced insulation		N/A
22.28	Metal parts of Class II appliances conductively connected to gas pipes or in contact with water, separated from live parts by double or reinforced insulation		N/A
22.29	Class II appliances permanently connected to fixed wiring so constructed that the required degree of access to live parts is maintained after installation		N/A
22.30	Parts serving as supplementary or reinforced insulation fixed so that they cannot be removed without being seriously damaged, or		P
	so constructed that they cannot be replaced in an incorrect position, and so that if they are omitted, the appliance is rendered inoperable or manifestly incomplete		P
22.31	Neither clearances nor creepage distances over supplementary and reinforced insulation reduced below values specified in clause 29 as a result of wear		P
	Neither clearances nor creepage distances between live parts and accessible parts reduced below values for supplementary insulation if wires, screws etc. become loose		P
22.32	Supplementary and reinforced insulation constructed or protected against pollution so that clearances or creepage distances are not reduced below the values in clause 29		P
	Supplementary insulation of natural or synthetic rubber resistant to ageing, or arranged and dimensioned so that creepage distances are not reduced below values specified in 29.2		N/A

IEC 60335-2-80			
Clause	Requirement - Test	Result - Remark	Verdict
	Ceramic material not tightly sintered, similar materials or beads alone not used as supplementary or reinforced insulation		N/A
	Insulating material in which heating conductors are embedded is considered to be basic insulation, not reinforced insulation		N/A
	Oxygen bomb test at 70 °C for 96 h and 16 h at room temperature		N/A
22.33	Conductive liquids that are or may become accessible in normal use and conductive liquids that are in contact with unearthed accessible metal parts are not in direct contact with live parts		N/A
	Electrodes not used for heating liquids		N/A
	For class II constructions, conductive liquids that are or may become accessible in normal use and conductive liquids that are in contact with unearthed accessible metal parts, not in direct contact with basic or reinforced insulation, unless		N/A
	the reinforced insulation consists of at least 3 layers		N/A
	For class II constructions, conductive liquids which are in contact with live parts, not in direct contact with reinforced insulation, unless		N/A
	the reinforced insulation consists of at least 3 layers		N/A
	An air layer not used as basic or supplementary insulation in a double insulation system if likely to be bridged by leaking liquid		N/A
22.34	Shafts of operating knobs, handles, levers etc. not live, unless		P
	the shaft is not accessible when the part is removed		N/A
22.35	For other than class III constructions, handles, levers and knobs, held or actuated in normal use, not becoming live in the event of a failure of basic insulation		P
	Such parts being of metal, and their shafts or fixings are likely to become live in the event of a failure of basic insulation, are either adequately covered by insulation material or their accessible parts are separated from their shafts or fixings by supplementary insulation		N/A
	This requirement does not apply to handles, levers and knobs on stationary appliances, other than those of electrical components, provided they are reliably connected to an earthing terminal or earthing contact, or separated from live parts by earthed metal		N/A

TRF No. IEC60335_2_80E

Intertek Testing Services Shenzhen Ltd. Guangzhou Branch

Block E, No.7-2 Guang Dong Software Science Park, Caipin Road, Guangzhou Science City, GETDD, Guangzhou, China
Tel: 86 20 82139688 Fax: 86 20 32057538 www.intertek-etlsemko.com

IEC 60335-2-80			
Clause	Requirement - Test	Result - Remark	Verdict
	Insulating material covering metal handles, levers and knobs withstand the electric strength test of 16.3 for supplementary insulation		N/A
22.36	For appliances other than class III, handles continuously held in the hand in normal use so constructed that when gripped as in normal use, the operators hand is not likely to touch metal parts, unless		N/A
	they are separated from live parts by double or reinforced insulation		N/A
22.37	Capacitors in Class II appliances not connected to accessible metal parts and their casings, if of metal, separated from accessible metal parts by supplementary insulation, unless		P
	the capacitors comply with 22.42		N/A
22.38	Capacitors not connected between the contacts of a thermal cut-out		P
22.39	Lamp holders used only for the connection of lamps		N/A
22.40	Motor-operated appliances and combined appliances intended to be moved while in operation, or having accessible moving parts, fitted with a switch to control the motor. The actuating member of the switch being easily visible and accessible		N/A
	If the appliance cannot operate continuously, automatically or remotely without giving rise to a hazard, appliances for remote operation being fitted with a switch for stopping the operation. The actuating member of the switch being easily visible and accessible		N/A
22.41	No components, other than lamps, containing mercury		P
22.42	Protective impedance consisting of at least two separate components		N/A
	Values specified in 8.1.4 not exceeded if any one of the components are short-circuited or open-circuited		N/A
	Resistors checked by the test of 14.1 a) in IEC 60065		N/A
	Capacitors checked by the tests for class Y capacitors in IEC 60384-14		N/A
22.43	Appliances adjustable for different voltages, accidental changing of the setting of the voltage unlikely to occur		N/A

IEC 60335-2-80			
Clause	Requirement - Test	Result - Remark	Verdict
22.44	Appliances not having an enclosure that is shaped or decorated like a toy		P
22.45	When air is used as reinforced insulation, clearances not reduced below the values specified in 29.1.3 due to deformation as a result of an external force applied to the enclosure		P
22.46	For programmable protective electronic circuits used to ensure compliance with the standard, the software contains measures to control the fault/error conditions in table R.1		N/A
	Software that contains measures to control the fault/error conditions specified in table R.2 is to be specified in parts 2 for particular constructions or to address specific hazards		N/A
	These requirements are not applicable to software used for functional purpose or compliance with clause 11		N/A
22.47	Appliances connected to the water mains withstand the water pressure expected in normal use		N/A
	No leakage from any part, including any inlet water hose		N/A
22.48	Appliances connected to the water mains constructed to prevent backsiphonage of non-potable water		N/A
22.49	For remote operation, the duration of operation is to be set before the appliance can be started, unless		N/A
	the appliance switches off automatically or can operate continuously without hazard		N/A
22.50	Controls incorporated in the appliance take priority over controls actuated by remote operation		N/A
22.51	There is a control on the appliance manually adjusted to the setting for remote operation before the appliance can be operated in this mode		N/A
	There is a visual indication showing that the appliance is adjusted for remote operation		N/A
	These requirements not necessary on appliances that can operate as follows, without giving rise to a hazard:		----
	- continuously, or		N/A
	- automatically, or		N/A
	- remotely		N/A
22.52	Socket-outlets on appliances accessible to the user in accordance with the socket-outlet system used in the country in which the appliance is sold		N/A

IEC 60335-2-80			
Clause	Requirement - Test	Result - Remark	Verdict
22.101	Appliances having provision for attaching a luminaire incorporate appropriate terminals and internal wiring. (IEC 60335-2-80)		N/A
23	INTERNAL WIRING		----
23.1	Wireways smooth and free from sharp edges		P
	Wires protected against contact with burrs, cooling fins etc.		P
	Wire holes in metal well-rounded or provided with bushings		P
	Wiring effectively prevented from coming into contact with moving parts		P
23.2	Beads etc. on live wires cannot change their position, and are not resting on sharp edges		N/A
	Beads inside flexible metal conduits contained within an insulating sleeve		N/A
23.3	Electrical connections and internal conductors movable relatively to each other not exposed to undue stress		P
	Flexible metallic tubes not causing damage to insulation of conductors		P
	Open-coil springs not used		N/A
	Adequate insulating lining provided inside a coiled spring, the turns of which touch one another		N/A
M	No damage after 100 000 flexings for conductors flexed during normal use and at rated voltage, or (IEC 60335-2-80)		P
	100 flexings for conductors flexed during user maintenance		N/A
	Electric strength test of 16.3, 1000 V between live parts and accessible metal parts		P
	Not more than 10% of the strands of any conductor broken, and		P
	not more than 30% for wiring supplying circuits that consume no more than 15W		P
23.4	Bare internal wiring sufficiently rigid and fixed		N/A
23.5	The insulation of internal wiring subjected to the supply mains voltage withstanding the electrical stress likely to occur in normal use		P
	Basic insulation electrically equivalent to the basic insulation of cords complying with IEC 60227 or IEC 60245, or		P

IEC 60335-2-80			
Clause	Requirement - Test	Result - Remark	Verdict
	no breakdown when a voltage of 2000 V is applied for 15 min between the conductor and metal foil wrapped around the insulation		P
23.6	Sleeving used as supplementary insulation on internal wiring retained in position by clamping at both ends, or		P
	be such that it can only be removed by breaking or cutting		P
23.7	The colour combination green/yellow only used for earthing conductors		N/A
23.8	Aluminium wires not used for internal wiring		N/A
23.9	Stranded conductors not consolidated by soldering where they are subjected to contact pressure, unless		P
	the contact pressure is provided by spring terminals		N/A
23.10	The insulation and sheath of internal wiring, incorporated in external hoses for the connection of an appliance to the water mains, at least equivalent to that of light polyvinyl chloride sheathed flexible cord (60227 IEC 52)		N/A
24	COMPONENTS		----
24.1	Components comply with safety requirements in relevant IEC standards		P
	List of components..... :	(see appended table)	P
	If components have not been tested and found to comply with relevant IEC standard for the number of cycles specified, they are tested in accordance with 24.1.1 to 24.1.9		P
	For components mentioned in 24.1.1 to 24.1.9 no additional tests specified in the relevant component standard are necessary other than those specified in 24.1.1 to 24.1.9		P
	Components not tested and found to comply with relevant IEC standard and components not marked or not used in accordance with its marking, tested under the conditions occurring in the appliance		P
	Lampholders and starterholders that have not being tested and found to comply with the relevant IEC standard, tested as a part of the appliance and additionally according to the gauging and interchangeability requirements of the relevant IEC standard		N/A

IEC 60335-2-80			
Clause	Requirement - Test	Result - Remark	Verdict
	No additional tests specified for nationally standardized plugs such as those detailed in IEC/TR 60083 or connectors complying with the standard sheets of IEC 60320-1 and IEC 60309		P
24.1.1	Capacitors likely to be permanently subjected to the supply voltage and used for radio interference suppression or for voltage dividing, complying with IEC 60384-14		P
	If the capacitors have to be tested, they are tested according to Annex F		N/A
24.1.2	Safety isolating transformers complying with IEC 61558-2-6		N/A
	If they have to be tested, they are tested according to Annex G		N/A
24.1.3	Switches complying with IEC 61058-1, the number of cycles of operation being at least 10 000		P
	If they have to be tested, they are tested according to Annex H		N/A
	If the switch operates a relay or contactor, the complete switching system is subjected to the test		N/A
	If the switch only operates a motor starting relay complying with IEC 60730-2-10 with the number of cycles of a least 10 000 as specified, the complete switching system need not be tested		N/A
24.1.4	Automatic controls complying with IEC 60730-1 with the relevant part 2. The number of cycles of operation being at least:		----
	- thermostats: 10 000		N/A
	- temperature limiters: 1 000		N/A
	- self-resetting thermal cut-outs: 300		N/A
	- voltage maintained non-self-resetting thermal cut-outs: 1 000		N/A
	- other non-self-resetting thermal cut-outs: 30		N/A
	- timers: 3 000		N/A
	- energy regulators: 10 000		N/A
	The number of cycles for controls operating during clause 11 need not be declared, if the appliance meets the requirements of this standard when they are short-circuited		N/A
	Thermal motor protectors are tested in combination with their motor under the conditions specified in Annex D		N/A

IEC 60335-2-80			
Clause	Requirement - Test	Result - Remark	Verdict
	For water valves containing live parts and that are incorporated in external hoses for connection of an appliance to the water mains, the degree of protection declared for subclause 6.5.2 of IEC 60730-2-8 is IPX7		N/A
24.1.5	Appliance couplers complying with IEC 60320-1		N/A
	However, for appliances classified higher than IPX0, the appliance couplers complying with IEC 60320-2-3		N/A
	Interconnection couplers complying with IEC 60320-2-2		N/A
24.1.6	Small lamp holders similar to E10 lampholders complying with IEC 60238, the requirements for E10 lampholders being applicable		N/A
24.1.7	For remote operation of the appliance via a telecommunication network, the relevant standard for the telecommunication interface circuitry in the appliance is IEC 62151		N/A
24.1.8	The relevant standard for thermal links is IEC 60691		P
	Thermal links not complying with IEC 60691 are considered to be an intentionally weak part for the purposes of Clause 19		N/A
24.1.9	Contactors and relays, other than motor starting relays, tested as part of the appliance		N/A
	They are also tested in accordance with Clause 17 of IEC 60730-1, the number of cycles of operations in 24.1.4 selected according to the contactor or relay function in the appliance		N/A
24.2	Appliances not fitted with:		----
	- switches or automatic controls in flexible cords		P
	- devices causing the protective device in the fixed wiring to operate in the event of a fault in the appliance		P
	- thermal cut-outs that can be reset by soldering, unless		P
	the solder has a melting point of at least 230 °C		N/A
A	Switches or automatic controls in flexible cords are allowed for appliances not exceeding 25 W. (IEC 60335-2-80)		N/A

IEC 60335-2-80			
Clause	Requirement - Test	Result - Remark	Verdict
24.3	Switches intended for all-pole disconnection of stationary appliances are directly connected to the supply terminals and have a contact separation in all poles, providing full disconnection under overvoltage category III conditions		N/A
24.4	Plugs and socket-outlets for extra-low voltage circuits and heating elements, not interchangeable with plugs and socket-outlets listed in IEC/TR 60083 or IEC 60906-1 or with connectors and appliance inlets complying with the standard sheets of IEC 60320-1		N/A
24.5	Capacitors in auxiliary windings of motors marked with their rated voltage and capacitance, and used accordingly		P
	Voltage across capacitors in series with a motor winding does not exceed 1,1 times rated voltage, when the appliance is supplied at 1,1 times rated voltage under minimum load		P
24.6	Working voltage of motors connected to the supply mains and having basic insulation that is inadequate for the rated voltage of the appliance, not exceeding 42 V		N/A
	In addition, the motors comply with the requirements of Annex I		N/A
24.7	Detachable hose-sets for connection of appliances to the water mains comply with IEC 61770		N/A
	They are supplied with the appliance		N/A
	Appliances intended to be permanently connected to the water mains not connected by a detachable hose-set		N/A
24.8	Motor running capacitors in appliances for which 30.2.3 is applicable and that are permanently connected in series with a motor winding, not causing a hazard in event of a failure		P
	One or more of the following conditions are to be met:		----
	- the capacitors are of class P2 according to IEC 60252-1		P
	- the capacitors are housed within a metallic or ceramic enclosure		N/A
	- the distance of separation of the outer surface to adjacent non-metallic parts exceeds 50 mm		N/A
	- adjacent non-metallic parts within 50 mm withstand the needle-flame test of Annex E		N/A

IEC 60335-2-80			
Clause	Requirement - Test	Result - Remark	Verdict
	- adjacent non-metallic parts within 50 mm classified as at least V-1 according to IEC 60695-11-10		N/A
24.101	Thermal cut-outs in duct fans in order to comply with cl. 19 are not self-resetting (IEC 60335-2-80)		N/A
25	SUPPLY CONNECTION AND EXTERNAL FLEXIBLE CORDS		----
25.1	Appliance not intended for permanent connection to fixed wiring, means for connection to the supply:		----
	- supply cord fitted with a plug,		P
	- an appliance inlet having at least the same degree of protection against moisture as required for the appliance, or		N/A
	- pins for insertion into socket-outlets		N/A
25.2	Appliance not provided with more than one means of connection to the supply mains		P
	Stationary appliance for multiple supply may be provided with more than one means of connection, provided electric strength test of 1250 V for 1 min between each means of connection causes no breakdown		N/A
25.3	Appliance intended to be permanently connected to fixed wiring provided with one of the following means for connection to the supply mains:		----
	- a set of terminals allowing the connection of a flexible cord		N/A
	- a fitted supply cord		N/A
	- a set of supply leads accommodated in a suitable compartment		N/A
	- a set of terminals for the connection of cables of fixed wiring, cross-sectional areas specified in 26.6, and the appliance allows the connection of the supply conductors after the appliance has been fixed to its support		N/A
	- a set of terminals and cable entries, conduit entries, knock-outs or glands, allowing connection of appropriate types of cable or conduit, and the appliance allows the connection of the supply conductors after the appliance has been fixed to its support		N/A
	For a fixed appliance constructed so that parts can be removed to facilitate easy installation, this requirement is met if it is possible to connect the fixed wiring without difficulty after a part of the appliance has been fixed to its support		N/A

IEC 60335-2-80			
Clause	Requirement - Test	Result - Remark	Verdict
25.4	Cable and conduit entries, rated current of appliance not exceeding 16 A, dimension according to table 10 (mm)..... :		N/A
	Introduction of conduit or cable does not reduce clearances or creepage distances below values specified in clause 29		N/A
25.5	Method for assembling the supply cord to the appliance:		----
	- type X attachment		N/A
	- type Y attachment		P
	- type Z attachment, if allowed in relevant part 2		N/A
	Type X attachment, other than those with a specially prepared cord, not used for flat twin tinsel cords		N/A
	For multi-phase appliances supplied with a supply cord and that are intended to be permanently connected to fixed wiring, the supply cord is assembled to the appliance by type Y attachment		N/A
A	- type Z attachment is allowed for portable fans (IEC 60335-2-80)		N/A
25.6	Plugs fitted with only one flexible cord		P
25.7	Supply cords, other than for class III appliances, being one of the following types:		----
	- rubber sheathed (at least 60245 IEC 53)		N/A
	- polychloroprene sheathed (at least 60245 IEC 57)		N/A
	- cross-linked polyvinyl chloride sheathed (at least 60245 IEC 88)		N/A
	- polyvinyl chloride sheathed. Not used if they are likely to touch metal parts having a temperature rise exceeding 75 K during the test of clause 11		----
	light polyvinyl chloride sheathed cord (60227 IEC 52), for appliances not exceeding 3 kg	H03VV-F, H03VVH2-F	P
	ordinary polyvinyl chloride sheathed cord (60227 IEC 53), for other appliances	H05VV-F, H05VVH2-F	P
	- heat resistant polyvinyl chloride sheathed. Not used for type X attachment other than specially prepared cords		----
	heat-resistant light polyvinyl chloride sheathed cord (60227 IEC 56), for appliances not exceeding 3 kg		N/A
	heat-resistant polyvinyl chloride sheathed cord (60227 IEC 57), for other appliances		N/A
	Supply cords for class III appliances adequately insulated		N/A

IEC 60335-2-80			
Clause	Requirement - Test	Result - Remark	Verdict
	Test with 500 V for 2 min for supply cords of class III appliances that contain live parts		N/A
25.8	Nominal cross-sectional area of supply cords not less than table 11; rated current (A); cross-sectional area (mm ²)	Max. measured rated current: 0,226A Cross-sectional: 0,5 mm ² or 0,75mm ²	P
25.9	Supply cords not in contact with sharp points or edges		P
25.10	Supply cord of class I appliances have a green/yellow core for earthing		N/A
25.11	Conductors of supply cords not consolidated by soldering where they are subject to contact pressure, unless		P
	the contact pressure is provided by spring terminals		N/A
25.12	Insulation of the supply cord not damaged when moulding the cord to part of the enclosure		N/A
25.13	Inlet openings so constructed as to prevent damage to the supply cord		P
	If the enclosure at the inlet opening is not of insulating material, a non-detachable lining or bushing complying with 29.3 for supplementary insulation provided		N/A
	If unsheathed supply cord, a similar additional bushing or lining is required, unless the appliance is		N/A
	class 0, or		N/A
	a class III appliance not containing live parts		N/A
25.14	Supply cords moved while in operation adequately protected against excessive flexing		N/A
	Flexing test, as described:		----
	- applied force (N)		N/A
	- number of flexings		N/A
	The test does not result in:		----
	- short-circuit between the conductors, such that the current exceeds a value of twice the rated current		N/A
	- breakage of more than 10% of the strands of any conductor		N/A
	- separation of the conductor from its terminal		N/A
	- loosening of any cord guard		N/A
	- damage to the cord or the cord guard		N/A

IEC 60335-2-80			
Clause	Requirement - Test	Result - Remark	Verdict
	- broken strands piercing the insulation and becoming accessible		N/A
25.15	For appliances with supply cord and appliances to be permanently connected to fixed wiring by a flexible cord, conductors of the supply cord relieved from strain, twisting and abrasion by use of cord anchorage		P
	The cord cannot be pushed into the appliance to such an extent that the cord or internal parts of the appliance can be damaged		P
	Pull and torque test of supply cord, values shown in table 12: mass (kg); pull (N); torque (not on automatic cord reel) (Nm) :		P
	Cord not damaged and max. 2 mm displacement of the cord		P
25.16	Cord anchorages for type X attachments constructed and located so that:		----
	- replacement of the cord is easily possible		N/A
	- it is clear how the relief from strain and the prevention of twisting are obtained		N/A
	- they are suitable for different types of supply cord		N/A
	- cord cannot touch the clamping screws of cord anchorage if these screws are accessible, unless		N/A
	they are separated from accessible metal parts by supplementary insulation		N/A
	- the cord is not clamped by a metal screw which bears directly on the cord		N/A
	- at least one part of the cord anchorage securely fixed to the appliance, unless		N/A
	it is part of a specially prepared cord		N/A
	- screws which have to be operated when replacing the cord do not fix any other component, unless		N/A
	the appliance becomes inoperative or incomplete or the parts cannot be removed without a tool		N/A
	- if labyrinths can be bypassed the test of 25.15 is nevertheless withstood		N/A
	- for class 0, 0I and I appliances they are of insulating material or are provided with an insulating lining, unless		N/A
	failure of the insulation of the cord does not make accessible metal parts live		N/A
	- for class II appliances they are of insulating material, or		N/A

IEC 60335-2-80			
Clause	Requirement - Test	Result - Remark	Verdict
	if of metal, they are insulated from accessible metal parts by supplementary insulation		N/A
	After the test of 25.15, under the conditions specified, the conductors have not moved by more than 1 mm in the terminals		N/A
25.17	Adequate cord anchorages for type Y and Z attachment, test with the cord supplied with the appliance		P
25.18	Cord anchorages only accessible with the aid of a tool, or		P
	Constructed so that the cord can only be fitted with the aid of a tool		N/A
25.19	Type X attachment, glands not used as cord anchorage in portable appliances		N/A
	Tying the cord into a knot or tying the cord with string not used		N/A
25.20	The insulated conductors of the supply cord for type Y and Z attachment additionally insulated from accessible metal parts		P
25.21	Space for supply cord for type X attachment or for connection of fixed wiring constructed:		----
	- to permit checking of conductors with respect to correct positioning and connection before fitting any cover		N/A
	- so there is no risk of damage to the conductors or their insulation when fitting the cover		N/A
	- for portable appliances, so that the uninsulated end of a conductor, if it becomes free from the terminal, prevented from contact with accessible metal parts		N/A
	2 N test to the conductor for portable appliances; no contact with accessible metal parts		N/A
25.22	Appliance inlets:		----
	- live parts not accessible during insertion or removal		N/A
	Requirement not applicable to appliance inlets complying with IEC 60320-1		N/A
	- connector can be inserted without difficulty		N/A
	- the appliance is not supported by the connector		N/A
	- not for cold conditions if temp. rise of external metal parts exceeds 75 K during clause 11, unless		N/A
	the supply cord is unlikely to touch such metal parts		N/A

IEC 60335-2-80			
Clause	Requirement - Test	Result - Remark	Verdict
25.23	Interconnection cords comply with the requirements for the supply cord, except that:		N/A
	- the cross-sectional area of the conductors is determined on the basis of the maximum current during clause 11		N/A
	- the thickness of the insulation may be reduced		N/A
	If necessary, electric strength test of 16.3		N/A
25.24	Interconnection cords not detachable without the aid of a tool if compliance with this standard is impaired when they are disconnected		N/A
25.25	Dimensions of pins that are inserted into socket-outlets compatible with the dimensions of the relevant socket-outlet.		N/A
	Dimensions of pins and engagement face in accordance with the dimensions of the relevant plug in IEC/TR 60083		N/A
26	TERMINALS FOR EXTERNAL CONDUCTORS		----
26.1	Appliances provided with terminals or equally effective devices for connection of external conductors		P
	Terminals only accessible after removal of a non-detachable cover, except		P
	for class III appliances that do not contain live parts		N/A
	Earthing terminals may be accessible if a tool is required to make the connections and means are provided to clamp the wire independently from its connection		N/A
26.2	Appliances with type X attachment and appliances for the connection of cables to fixed wiring provided with terminals in which connections are made by means of screws, nuts or similar devices, unless		N/A
	the connections are soldered		N/A
	Screws and nuts not used to fix any other component, except		N/A
	internal conductors, if so arranged that they are unlikely to be displaced when fitting the supply conductors		N/A
	If soldered connections used, the conductor so positioned or fixed that reliance is not placed on soldering alone, unless		N/A

IEC 60335-2-80			
Clause	Requirement - Test	Result - Remark	Verdict
	barriers provided so that neither clearances nor creepage distances between live parts and other metal parts reduced below the values for supplementary insulation if the conductor becomes free at the soldered joint		N/A
26.3	Terminals for type X attachment and for connection of cables of fixed wiring so constructed that the conductor is clamped between metal surfaces with sufficient contact pressure but without damaging the conductor		N/A
	Terminals fixed so that when the clamping means is tightened or loosened:		----
	- the terminal does not become loose		N/A
	- internal wiring is not subjected to stress		N/A
	- neither clearances nor creepage distances are reduced below the values in clause 29		N/A
	Compliance checked by inspection and by the test of subclause 9.6 of IEC 60999-1, the torque applied being equal to two-thirds of the torque specified (Nm)		N/A
	No deep or sharp indentations of the conductors		N/A
26.4	Terminals for type X attachment, except those having a specially prepared cord and those for the connection of cables of fixed wiring, no special preparation of conductors such as by soldering, use of cable lugs, eyelets or similar, and		N/A
	so constructed or placed that conductors prevented from slipping out when clamping screws or nuts are tightened		N/A
26.5	Terminals for type X attachment so located or shielded that if a wire of a stranded conductor escapes, no risk of accidental connection to other parts that result in a hazard		N/A
	Stranded conductor test, 8 mm insulation removed		N/A
	No contact between live parts and accessible metal parts and,		N/A
	for class II constructions, between live parts and metal parts separated from accessible metal parts by supplementary insulation only		N/A
26.6	Terminals for type X attachment and for connection of cables of fixed wiring suitable for connection of conductors with cross-sectional area according to table 13; rated current (A); nominal cross-sectional area (mm ²)		N/A
	If a specially prepared cord is used, terminals need only be suitable for that cord		N/A

TRF No. IEC60335_2_80E

Intertek Testing Services Shenzhen Ltd. Guangzhou Branch

Block E, No.7-2 Guang Dong Software Science Park, Caipin Road, Guangzhou Science City, GETDD, Guangzhou, China
Tel: 86 20 82139688 Fax: 86 20 32057538 www.intertek-etlsemko.com

IEC 60335-2-80			
Clause	Requirement - Test	Result - Remark	Verdict
26.7	Terminals for type X attachment, except in class III appliances not containing live parts, accessible after removal of a cover or part of the enclosure		N/A
26.8	Terminals for the connection of fixed wiring, including the earthing terminal, located close to each other		N/A
26.9	Terminals of the pillar type constructed and located as specified		N/A
26.10	Terminals with screw clamping and screwless terminals not used for flat twin tinsel cords, unless		N/A
	conductors ends fitted with means suitable for screw terminals		N/A
	Pull test of 5 N to the connection		N/A
26.11	For type Y and Z attachment, soldered, welded, crimped or similar connections may be used		P
	For Class II appliances, the conductor so positioned or fixed that reliance is not placed on soldering, welding or crimping alone		P
	If soldering, welding or crimping alone used, barriers provided so that clearances and creepage distances between live parts and other metal parts are not reduced below the values for supplementary insulation if the conductor becomes free		N/A
27	PROVISION FOR EARTHING		----
27.1	Accessible metal parts of Class 0I and I appliances permanently and reliably connected to an earthing terminal or earthing contact of the appliance inlet		N/A
	Earthing terminals and earthing contacts not connected to the neutral terminal		N/A
	Class 0, II and III appliances have no provision for earthing	Class II	P
	Safety extra-low voltage circuits not earthed, unless		N/A
	protective extra-low voltage circuits		N/A
27.2	Clamping means of earthing terminals adequately secured against accidental loosening		N/A
	Terminals for the connection of external equipotential bonding conductors allow connection of conductors of 2.5 to 6 mm ² , and		N/A
	do not provide earthing continuity between different parts of the appliance, and		N/A
	conductors cannot be loosened without the aid of a tool		N/A

IEC 60335-2-80			
Clause	Requirement - Test	Result - Remark	Verdict
27.3	For a detachable part having an earth connection and being plugged into another part of the appliance, the earth connection is made before and separated after current-carrying connections when removing the part		N/A
	For appliances with supply cords, current-carrying conductors become taut before earthing conductor, if the cord slips out of the cord anchorage		N/A
27.4	No risk of corrosion resulting from contact between parts of the earthing terminal and the copper of the earthing conductor or other metal		N/A
	Parts providing earthing continuity, other than parts of a metal frame or enclosure, have adequate resistance to corrosion		N/A
	If of steel, these parts provided with an electroplated coating with a thickness at least 5 μm		N/A
	Adequate protection against rusting of parts of coated or uncoated steel, only intended to provide or transmit contact pressure		N/A
	In the body of the earthing terminal is a part of a frame or enclosure of aluminium or aluminium alloys, precautions taken to avoid risk of corrosion		N/A
27.5	Low resistance of connection between earthing terminal and earthed metal parts		N/A
	This requirement does not apply to connections providing earthing continuity in the protective extra-low voltage circuit, provided the clearances of basic insulation are based on the rated voltage of the appliance		N/A
	Resistance not exceeding 0,1 Ω at the specified low-resistance test (Ω)		N/A
27.6	The printed conductors of printed circuit boards not used to provide earthing continuity in hand-held appliances.		N/A
	They may be used to provide earthing continuity in other appliances if at least two tracks are used with independent soldering points and the appliance complies with 27.5 for each circuit		N/A
28	SCREWS AND CONNECTIONS		----
28.1	Fixings, electrical connections and connections providing earthing continuity withstand mechanical stresses		P
	Screws not of soft metal liable to creep, such as zinc or aluminium		P

IEC 60335-2-80			
Clause	Requirement - Test	Result - Remark	Verdict
	Diameter of screws of insulating material min. 3 mm		N/A
	Screws of insulating material not used for any electrical connections or connections providing earthing continuity		N/A
	Screws used for electrical connections or connections providing earthing continuity screwed into metal		N/A
	Screws not of insulating material if their replacement by a metal screw can impair supplementary or reinforced insulation		N/A
	For type X attachment, screws to be removed for replacement of supply cord or for user maintenance, not of insulating material if their replacement by a metal screw impairs basic insulation		N/A
	For screws and nuts; torque-test as specified in table 14	(see appended table)	P
28.2	Electrical connections and connections providing earthing continuity constructed so that contact pressure is not transmitted through non-ceramic insulating material liable to shrink or distort, unless		N/A
	there is resiliency in the metallic parts to compensate for shrinkage or distortion of the insulating material		N/A
	This requirement does not apply to electrical connections in circuits of appliances for which:		----
	30.2.2 is applicable and that carry a current not exceeding 0,5 A		N/A
	30.2.3 is applicable and that carry a current not exceeding 0,2 A		N/A
28.3	Space-threaded (sheet metal) screws only used for electrical connections if they clamp the parts together		N/A
	Thread-cutting (self-tapping) screws and thread rolling screws only used for electrical connections if they generate a full form standard machine screw thread		N/A
	Thread-cutting (self-tapping) screws not used if they are likely to be operated by the user or installer		N/A
	Thread-cutting, thread rolling and space threaded screws may be used in connections providing earthing continuity provided it is not necessary to disturb the connection:		----
	- in normal use,		N/A

TRF No. IEC60335_2_80E

Intertek Testing Services Shenzhen Ltd. Guangzhou Branch

Block E, No.7-2 Guang Dong Software Science Park, Caipin Road, Guangzhou Science City, GETDD, Guangzhou, China
Tel: 86 20 82139688 Fax: 86 20 32057538 www.intertek-etlsemko.com

IEC 60335-2-80			
Clause	Requirement - Test	Result - Remark	Verdict
	- during user maintenance,		N/A
	- when replacing a supply cord having a type X attachment, or		N/A
	- during installation		N/A
	At least two screws being used for each connection providing earthing continuity, unless		N/A
	the screw forms a thread having a length of at least half the diameter of the screw		N/A
28.4	Screws and nuts that make mechanical connection secured against loosening if they also make electrical connections or connections providing earthing continuity		N/A
	This requirement does not apply to screws in the earthing circuit if at least two screws are used, or		N/A
	if an alternative earthing circuit is provided		N/A
	Rivets for electrical connections or connections providing earthing continuity secured against loosening if the connections are subjected to torsion		N/A
29	CLEARANCES, CREEPAGE DISTANCES AND SOLID INSULATION		----
	Clearances, creepage distances and solid insulation withstand electrical stress		P
	For coatings used on printed circuits boards to protect the microenvironment (Type 1) or to provide basic insulation (Type 2), Annex J applies		N/A
	The microenvironment is pollution degree 1 under type 1 protection		N/A
	For type 2 protection, the spacing between the conductors before the protection is applied is not less than the values specified in Table 1 of IEC 60664-3		N/A
	These values apply to functional, basic, supplementary and reinforced insulation		N/A
29.1	Clearances not less than the values specified in table 16, taking into account the rated impulse voltage for the overvoltage categories of table 15, unless.....	(see appended table)	P
	for basic insulation and functional insulation they comply with the impulse voltage test of clause 14		N/A
	However, if the distances are affected by wear, distortion, movement of the parts or during assembly, the clearances for rated impulse voltages of 1500V and above are increased by 0,5 mm and the impulse voltage test is not applicable		N/A

TRF No. IEC60335_2_80E

Intertek Testing Services Shenzhen Ltd. Guangzhou Branch

Block E, No.7-2 Guang Dong Software Science Park, Caipin Road, Guangzhou Science City, GETDD, Guangzhou, China
Tel: 86 20 82139688 Fax: 86 20 32057538 www.intertek-etlsemko.com

IEC 60335-2-80			
Clause	Requirement - Test	Result - Remark	Verdict
	Impulse voltage test is not applicable:		----
	- when the microenvironment is pollution degree 3, or		N/A
	- for basic insulation of class 0 and class 01 appliances		N/A
	Appliances are in overvoltage category II		P
	A force of 2 N is applied to bare conductors, other than heating elements		P
	A force of 30 N is applied to accessible surfaces		P
29.1.1	Clearances of basic insulation withstand the overvoltages, taking into account the rated impulse voltage		P
	The values of table 16 or the impulse voltage test of clause 14 are applicable	(see appended table)	P
	Clearance at the terminals of tubular sheathed heating elements may be reduced to 1,0 mm if the microenvironment is pollution degree 1		N/A
	Lacquered conductors of windings considered to be bare conductors		P
29.1.2	Clearances of supplementary insulation not less than those specified for basic insulation in table 16:	(see appended table)	P
29.1.3	Clearances of reinforced insulation not less than those specified for basic insulation in table 16, using the next higher step for rated impulse voltage	(see appended table)	P
	For double insulation, with no intermediate conductive part between basic and supplementary insulation, clearances are measured between live parts and the accessible surface, and the insulation system is treated as reinforced insulation		P
29.1.4	Clearances for functional insulation are the largest values determined from:		----
	- table 16 based on the rated impulse voltage..... :	(see appended table)	P
	- table F.7a in IEC 60664-1, frequency not exceeding 30 kHz		N/A
	- clause 4 of IEC 60664-4, frequency exceeding 30 kHz		N/A
	If values of table 16 are largest, the impulse voltage test of clause 14 may be applied instead, unless		N/A
	the microenvironment is pollution degree 3, or		N/A
	the distances can be affected by wear, distortion, movement of the parts or during assembly		N/A

IEC 60335-2-80			
Clause	Requirement - Test	Result - Remark	Verdict
	However, clearances are not specified if the appliance complies with clause 19 with the functional insulation short-circuited		N/A
	Lacquered conductors of windings considered to be bare conductors		P
	However, clearances at crossover points are not measured		P
	Clearance between surfaces of PTC heating elements may be reduced to 1mm		N/A
29.1.5	Appliances having higher working voltages than rated voltage, clearances for basic insulation are the largest values determined from:		----
	- table 16 based on the rated impulse voltage..... :		P
	- table F.7a in IEC 60664-1, frequency not exceeding 30 kHz		N/A
	- clause 4 of IEC 60664-4, frequency exceeding 30 kHz		N/A
	If clearances for basic insulation are selected from Table F.7a of IEC 60664-1 or Clause 4 of IEC 60664-4, the clearances of supplementary insulation are not less than those specified for basic insulation		N/A
	If clearances for basic insulation are selected from Table F.7a of IEC 60664-1, the clearances of reinforced insulation dimensioned as specified in Table F.7a are to withstand 160% of the withstand voltage required for basic insulation		N/A
	If clearances for basic insulation are selected from Clause 4 of IEC 60664-4, the clearances of reinforced insulation are twice the value required for basic insulation		N/A
	If the secondary winding of a step-down transformer is earthed, or if there is an earthed screen between the primary and secondary windings, clearances of basic insulation on the secondary side not less than those specified in table 16, but using the next lower step for rated impulse voltage		N/A
	Circuits supplied with a voltage lower than rated voltage, clearances of functional insulation are based on the working voltage used as the rated voltage in table 15		N/A
29.2	Creepage distances not less than those appropriate for the working voltage, taking into account the material group and the pollution degree :	(see appended table)	P
	Pollution degree 2 applies, unless		P

IEC 60335-2-80			
Clause	Requirement - Test	Result - Remark	Verdict
	- precautions taken to protect the insulation; pollution degree 1		N/A
	- insulation subjected to conductive pollution; pollution degree 3		P
A	Microenvironment is pollution degree 3 unless insulation is enclosed or located that it is unlikely to be exposed to pollution during normal use. (IEC 60335-2-80)		P
	A force of 2 N is applied to bare conductors, other than heating elements		P
	A force of 30 N is applied to accessible surfaces		P
	In a double insulation system, the working voltage for both the basic and supplementary insulation is taken as the working voltage across the complete double insulation system		P
29.2.1	Creepage distances of basic insulation not less than specified in table 17	(see appended table)	P
	However, if the working voltage is periodic and has a frequency exceeding 30 kHz, the creepage distances are also determined from table 2 of IEC 60664-4, these values being used if exceeding the values in table 17		N/A
	Except for pollution degree 1, corresponding creepage distance not less than the minimum specified for the clearance in table 16, if the clearance has been checked according to the test of clause 14.....		N/A
29.2.2	Creepage distances of supplementary insulation at least those specified for basic insulation in table 17, or	(see appended table)	P
	Table 2 of IEC 60664-4, as applicable		N/A
29.2.3	Creepage distances of reinforced insulation at least double those specified for basic insulation in table 17, or	(see appended table)	P
	Table 2 of IEC 60664-4, as applicable		N/A
29.2.4	Creepage distances of functional insulation not less than specified in table 18	(see appended table)	P
	However, if the working voltage is periodic and has a frequency exceeding 30 kHz, the creepage distances are also determined from table 2 of IEC 60664-4, these values being used if exceeding the values in table 18		N/A
	Creepage distances may be reduced if the appliance complies with clause 19 with the functional insulation short-circuited		N/A

IEC 60335-2-80			
Clause	Requirement - Test	Result - Remark	Verdict
29.3	Supplementary and reinforced insulation have adequate thickness, or a sufficient number of layers, to withstand the electrical stresses		P
	Compliance checked:		----
	- by measurement, in accordance with 29.3.1, or		P
	- by an electric strength test in accordance with 29.3.2, or		N/A
	- by an assessment of the thermal quality of the material combined with an electric strength test, in accordance with 29.3.3, and		N/A
	for accessible parts of reinforced insulation consisting of a single layer, by measurement in accordance with 29.3.4, or		N/A
	- as specified in subclause 6.3 of IEC 60664-4 for insulation that is subjected to any periodic voltage having a frequency exceeding 30 kHz		N/A
29.3.1	Supplementary insulation have a thickness of at least 1 mm	1,0mm thickness for cover of control panel	P
	Reinforced insulation have a thickness of at least 2 mm		N/A
29.3.2	Each layer of material withstand the electric strength test of 16.3 for supplementary insulation		N/A
	Supplementary insulation consist of at least 2 layers		N/A
	Reinforced insulation consist of at least 3 layers		N/A
29.3.3	The insulation is subjected to the dry heat test Bb of IEC 60068-2-2, followed by		N/A
	the electric strength test of 16.3		N/A
	If the temperature rise during the tests of clause 19 does not exceed the value specified in table 3, the test of IEC 60068-2-2 is not carried out		N/A
29.3.4	Thickness of accessible parts of reinforced insulation consisting of a single layer not less than specified in table 19		N/A
30	RESISTANCE TO HEAT AND FIRE		----
30.1	External parts of non-metallic material,		P
	parts supporting live parts, and		P
	parts of thermoplastic material providing supplementary or reinforced insulation		P
	sufficiently resistant to heat		P
	Ball-pressure test according to IEC 60695-10-2		P

IEC 60335-2-80			
Clause	Requirement - Test	Result - Remark	Verdict
	External parts tested at 40 °C plus the maximum temperature rise determined during the test of clause 11, or at 75 °C, whichever is the higher; temperature (°C)	(see appended table)	P
	Parts supporting live parts tested at 40°C plus the maximum temperature rise determined during the test of clause 11, or at 125 °C, whichever is the higher; temperature (°C)	(see appended table)	P
	Parts of thermoplastic material providing supplementary or reinforced insulation tested at 25 °C plus the maximum temperature rise determined during clause 19, if higher; temperature (°C)	(see appended table)	P
30.2	Parts of non-metallic material resistant to ignition and spread of fire		P
	This requirement does not apply to:		----
	parts having a mass not exceeding 0,5 g, provided the cumulative effect is unlikely to propagate flames that originate inside the appliance by propagating flames from one part to another, or		P
	decorative trims, knobs and other parts unlikely to be ignited or to propagate flames that originate inside the appliance		P
	Compliance checked by the tests of 30.2.1 and 30.2.3		P
	For base material of printed circuit boards, 30.2.4 applies		P
30.2.1	Parts of non-metallic material subjected to the glow-wire test of IEC 60695-2-11 at 550 °C		P
	However, test not carried out if the material is classified as having a glow-wire flammability index according to IEC 60695-2-12 of at least 550 °C, or		N/A
	the material is classified at least HB40 according to IEC 60695-11-10		N/A
	Parts for which the glow-wire test cannot be carried out need to meet the requirements in ISO 9772 for material classified HBF		N/A
30.2.2	Not applicable. (IEC 60335-2-80)		P
30.2.3	Appliances operated while unattended, tested as specified in 30.2.3.1 and 30.2.3.2		P
	The tests are not applicable to conditions as specified		P
30.2.3.1	Parts of non-metallic material supporting connections carrying a current exceeding 0,2 A during normal operation, and		P

IEC 60335-2-80			
Clause	Requirement - Test	Result - Remark	Verdict
	parts of non-metallic material, other than small parts, within a distance of 3 mm,		N/A
	subjected to the glow-wire test of IEC 60695-2-11 with a test severity of 850 °C		P
	Glow-wire applied to an interposed shielding material, if relevant		N/A
	The glow-wire test is not carried out on parts of material classified as having a glow-wire flammability index according to IEC 60695-2-12 of at least 850 °C		N/A
30.2.3.2	Parts of non-metallic material supporting connections, and		P
	parts of non-metallic material within a distance of 3mm,		N/A
	subjected to glow-wire test of IEC 60695-2-11		P
	The test severity is:		----
	- 750 °C, for connections carrying a current exceeding 0,2 A during normal operation		P
	- 650 °C, for other connections		P
	Glow-wire applied to an interposed shielding material, if relevant		P
	However, the glow-wire test of 750 °C or 650 °C as appropriate, is not carried out on parts of material fulfilling both or either of the following classifications:		----
	- a glow-wire ignition temperature according to IEC 60695-2-13 of at least:		N/A
	775 °C, for connections carrying a current exceeding 0,2 A during normal operation		N/A
	675 °C, for other connections		N/A
	- a glow-wire flammability index according to IEC 60695-2-12 of at least:		N/A
	- 750 °C, for connections carrying a current exceeding 0,2 A during normal operation		N/A
	- 650 °C, for other connections		N/A
	The glow-wire test is also not carried out on small parts. These parts are to:		----
	- comprise material having a glow-wire ignition temperature of at least 775 °C or 675 °C as appropriate, or		N/A
	- comprise material having a glow-wire flammability index of at least 750 °C or 650 °C as appropriate, or		N/A
	- comply with the needle-flame test of Annex E, or		N/A

TRF No. IEC60335_2_80E

Intertek Testing Services Shenzhen Ltd. Guangzhou Branch

Block E, No.7-2 Guang Dong Software Science Park, Caipin Road, Guangzhou Science City, GETDD, Guangzhou, China
Tel: 86 20 82139688 Fax: 86 20 32057538 www.intertek-etlsemko.com

IEC 60335-2-80			
Clause	Requirement - Test	Result - Remark	Verdict
	- comprise material classified as V-0 or V-1 according to IEC 60695-11-10		N/A
	The consequential needle-flame test of Annex E applied to non-metallic parts that encroach within the vertical cylinder placed above the centre of the connection zone and on top of the non-metallic parts supporting current-carrying connections, and parts of non-metallic material within a distance of 3 mm of such connections if these parts are those:		----
	- parts that withstood the glow-wire test of IEC 60695-2-11 of 750 °C or 650 °C as appropriate, but produce a flame that persist longer than 2 s, or		N/A
	- parts that comprised material having a glow-wire flammability index of at least 750 °C or 650 °C as appropriate, or		N/A
	- small parts, that comprised material having a glow-wire flammability index of at least 750 °C or 650 °C as appropriate, or		N/A
	- small parts for which the needle-flame test of Annex E was applied, or		N/A
	- small parts for which a material classification of V-0 or V-1 was applied		N/A
	However, the consequential needle-flame test is not carried out on non-metallic parts, including small parts, within the cylinder that are:		----
	- parts having a glow-wire ignition temperature of at least 775 °C or 675 °C as appropriate, or		N/A
	- parts comprising material classified as V-0 or V-1 according to IEC 60695-11-10, or		N/A
	- parts shielded by a flame barrier that meets the needle-flame test of Annex E or that comprises material classified as V-0 or V-1 according to IEC 60695-11-10		N/A
30.2.4	Base material of printed circuit boards subjected to the needle-flame test of Annex E		P
	Test not applicable to conditions as specified :		N/A
31	RESISTANCE TO RUSTING		----
	Relevant ferrous parts adequately protected against rusting		P
	Tests specified in part 2 when necessary		P
32	RADIATION, TOXICITY AND SIMILAR HAZARDS		----
	Appliance does not emit harmful radiation or present a toxic or similar hazard due to their operation in normal use		P
	Compliance is checked by the limits or tests specified in part 2, if relevant		N/A

TRF No. IEC60335_2_80E

Intertek Testing Services Shenzhen Ltd. Guangzhou Branch

Block E, No.7-2 Guang Dong Software Science Park, Caipin Road, Guangzhou Science City, GETDD, Guangzhou, China
Tel: 86 20 82139688 Fax: 86 20 32057538 www.intertek-etlsemko.com

IEC 60335-2-80			
Clause	Requirement - Test	Result - Remark	Verdict
A	ANNEX A (INFORMATIVE) ROUTINE TESTS		----
	Description of routine tests to be carried out by the manufacturer		P
B	ANNEX B (NORMATIVE) APPLIANCES POWERED BY RECHARGEABLE BATTERIES		----
	The following modifications to this standard are applicable for appliances powered by batteries that are recharged in the appliance		N/A
	This annex does not apply to battery chargers		N/A
3.1.9	Appliance operated under the following conditions:		----
	- the appliance, supplied by its fully charged battery, operated as specified in relevant part 2		N/A
	- the battery is charged, the battery being initially discharged to such an extent that the appliance cannot operate		N/A
	-if possible, the appliance is supplied from the supply mains through its battery charger, the battery being initially discharged to such an extent that the appliance cannot operate. The appliance is operated as specified in relevant part 2		N/A
	- if the appliance incorporates inductive coupling between two parts that are detachable from each other, the appliance is supplied from the supply mains with the detachable part removed		N/A
3.6.2	Part to be removed in order to discard the battery is not considered to be detachable		N/A
5.B.101	Appliances supplied from the supply mains tested as specified for motor-operated appliances		N/A
7.1	Battery compartment for batteries intended to be replaced by the user, marked with battery voltage and polarity of the terminals		N/A
	The positive terminal indicated by symbol IEC 60417-5005 and the negative terminal by symbol IEC 60417-5006		N/A
7.6	Symbols 60417-5005 and IEC 60417-5006		N/A
7.12	The instructions give information regarding charging		N/A
	The instructions for appliances incorporating batteries intended to be replaced by the user includes required information		N/A
	Details about how to remove batteries containing materials hazardous to the environment given		N/A

IEC 60335-2-80			
Clause	Requirement - Test	Result - Remark	Verdict
7.15	Markings placed on the part of the appliance connected to the supply mains		N/A
8.2	Appliances having batteries that according to the instruction may be replaced by the user need only have basic insulation between live parts and the inner surface of the battery compartment		N/A
	If the appliance can be operated without batteries, double or reinforced insulation required		N/A
11.7	The battery is charged for the period stated in the instructions or 24 h :		N/A
19.1	Appliances subjected to tests of 19.B.101, 19.B.102 and 19.B.103		N/A
19.10	Not applicable		N/A
19.B.101	Appliances supplied at rated voltage for 168 h, the battery being continually charged		N/A
19.B.102	For appliances having batteries that can be removed without the aid of a tool, short-circuit of the terminals of the battery, the battery being fully charged,		N/A
19.B.103	Appliances having batteries replaceable by the user supplied at rated voltage under normal operation with the battery removed or in any position allowed by the construction		N/A
21.B.101	Appliances having pins for insertion into socket-outlets have adequate mechanical strength		N/A
	Part of the appliance incorporating the pins subjected to the free fall test, procedure 2, of IEC 60068-2-31, the number of falls being:		----
	- 100, if the mass of the part does not exceed 250 g (g)..... :		N/A
	- 50, if the mass of the part exceeds 250 g :		N/A
	After the test, the requirements of 8.1, 15.1.1, 16.3 and clause 29 are met		N/A
22.3	Appliances having pins for insertion into socket-outlets tested as fully assembled as possible		N/A
25.13	An additional lining or bushing not required for interconnection cords in class III appliances or class III constructions operating at safety extra-low voltage not containing live parts		N/A
30.2	For parts of the appliance connected to the supply mains during the charging period, 30.2.3 applies		N/A
	For other parts, 30.2.2 applies		N/A
C	ANNEX C (NORMATIVE) AGEING TEST ON MOTORS		----

IEC 60335-2-80			
Clause	Requirement - Test	Result - Remark	Verdict
	Tests, as described, carried out when doubt with regard to the temperature classification of the insulation of a motor winding		N/A
	Test conditions as specified		N/A
D	ANNEX D (NORMATIVE) THERMAL MOTOR PROTECTORS		----
	Applicable to appliances having motors that incorporate thermal motor protectors necessary for compliance with the standard		N/A
	Test conditions as specified		N/A
E	ANNEX E (NORMATIVE) NEEDLE-FLAME TEST		----
	Needle-flame test carried out in accordance with IEC 60695-11-5, with the following modifications:		----
7	Severities		----
	The duration of application of the test flame is 30 s $\pm$ 1 s		P
9	Test procedure		----
9.1	The specimen so arranged that the flame can be applied to a vertical or horizontal edge as shown in the examples of Figure 1		P
9.2	The first paragraph does not apply		P
	If possible, the flame is applied at least 10 mm from a corner		P
9.3	The test is carried out on one specimen		P
	If the specimen does not withstand the test, the test may be repeated on two additional specimens, both withstanding the test		N/A
11	Evaluation of test results		----
	The duration of burning not exceeding 30 s		N/A
	However, for printed circuit boards, the duration of burning not exceeding 15 s		P
F	ANNEX F (NORMATIVE) CAPACITORS		----
	Capacitors likely to be permanently subjected to the supply voltage, and used for radio interference suppression or voltage dividing, comply with the following clauses of IEC 60384-14, with the following modifications:		----
1.5	Terms and definitions		----
1.5.3	Class X capacitors tested according to subclass X2		N/A
1.5.4	This subclause is applicable		N/A
1.6	Marking		----

TRF No. IEC60335_2_80E

Intertek Testing Services Shenzhen Ltd. Guangzhou Branch

Block E, No.7-2 Guang Dong Software Science Park, Caipin Road, Guangzhou Science City, GETDD, Guangzhou, China
Tel: 86 20 82139688 Fax: 86 20 32057538 www.intertek-etlsemko.com

IEC 60335-2-80			
Clause	Requirement - Test	Result - Remark	Verdict
	Items a) and b) are applicable		N/A
3.4	Approval testing		----
3.4.3.2	Table 3 is applicable as described		N/A
4.1	Visual examination and check of dimensions		----
	This subclause is applicable		N/A
4.2	Electrical tests		----
4.2.1	This subclause is applicable		N/A
4.2.5	This subclause is applicable		N/A
4.2.5.2	Only table 11 is applicable		N/A
	Values for test A apply		N/A
	However, for capacitors in heating appliances the values for test B or C apply		N/A
4.12	Damp heat, steady state		----
	This subclause is applicable		N/A
	Only insulation resistance and voltage proof are checked		N/A
4.13	Impulse voltage		----
	This subclause is applicable		N/A
4.14	Endurance		----
	Subclauses 4.14.1, 4.14.3, 4.14.4 and 4.14.7 are applicable		N/A
4.14.7	Only insulation resistance and voltage proof are checked		N/A
	No visible damage		N/A
4.17	Passive flammability test		----
	This subclause is applicable		N/A
4.18	Active flammability test		----
	This subclause is applicable		N/A
G	ANNEX G (NORMATIVE) SAFETY ISOLATING TRANSFORMERS		----
	The following modifications to this standard are applicable for safety isolating transformers:		----
7	Marking and instructions		----
7.1	Transformers for specific use marked with:		----
	-name, trademark or identification mark of the manufacturer or responsible vendor		N/A
	-model or type reference.....		N/A

TRF No. IEC60335_2_80E

Intertek Testing Services Shenzhen Ltd. Guangzhou Branch

Block E, No.7-2 Guang Dong Software Science Park, Caipin Road, Guangzhou Science City, GETDD, Guangzhou, China
Tel: 86 20 82139688 Fax: 86 20 32057538 www.intertek-etlsemko.com

IEC 60335-2-80			
Clause	Requirement - Test	Result - Remark	Verdict
17	Overload protection of transformers and associated circuits		----
	Fail-safe transformers comply with subclause 15.5 of IEC 61558-1		N/A
22	Construction		----
	Subclauses 19.1 and 19.1.2 of IEC 61558-2-6 are applicable		N/A
29	Clearances, creepage distances and solid insulation		----
29.1, 29.2, 29.3	The distances specified in items 2a, 2c and 3 in table 13 of IEC 61558-1 apply		N/A
	For insulated winding wires complying with subclause 19.12.3 of IEC 61558-1 there are no requirements for clearances or creepage distances		N/A
	For windings providing reinforced insulation, the distance specified in item 2c of table 13 of IEC 61558-1 is not assessed		N/A
	For safety isolating transformers subjected to periodic voltages with a frequency exceeding 30 kHz, the clearances, creepage distances and solid insulation values specified in IEC 60664-4 are applicable, if greater than the values specified in items 2a, 2c and 3 in table 13 of IEC 61558-1		N/A
H	ANNEX H (NORMATIVE) SWITCHES		----
	Switches comply with the following clauses of IEC 61058-1, as modified below:		----
	The tests of IEC 61058-1 carried out under the conditions occurring in the appliance		N/A
	Before being tested, switches are operated 20 times without load		N/A
8	Marking and documentation		----
	Switches are not required to be marked		N/A
	However, a switch that can be tested separately from the appliance marked with the manufacturer's name or trade mark and the type reference		N/A
13	Mechanism		----
	The tests may be carried out on a separate sample		N/A
15	Insulation resistance and dielectric strength		----
15.1	Not applicable		N/A
15.2	Not applicable		N/A
15.3	Applicable for full disconnection and micro-disconnection		N/A
17	Endurance		----

TRF No. IEC60335_2_80E

Intertek Testing Services Shenzhen Ltd. Guangzhou Branch

Block E, No.7-2 Guang Dong Software Science Park, Caipin Road, Guangzhou Science City, GETDD, Guangzhou, China
Tel: 86 20 82139688 Fax: 86 20 32057538 www.intertek-etlsemko.com

IEC 60335-2-80			
Clause	Requirement - Test	Result - Remark	Verdict
	Compliance is checked on three separate appliances or switches		N/A
	For 17.2.4.4, the number of cycles declared according to 7.1.4 is 10 000, unless		N/A
	otherwise specified in 24.1.3 of the relevant part 2 of IEC 60335		N/A
	Switches for operation under no load and which can be operated only by a tool, and		N/A
	switches operated by hand that are interlocked so that they cannot be operated under load,		N/A
	are not subjected to the tests		N/A
	However, switches without this interlock are subjected to the test of 17.2.4.4 for 100 cycles of operation		N/A
	Subclauses 17.2.2 and 17.2.5.2 not applicable		N/A
	The ambient temperature during the test is that occurring in the appliance during the test of Clause 11 in IEC 60335-1		N/A
	The temperature rise of the terminals not more than 30 K above the temperature rise measured in clause 11 of IEC 60335-1 (K)		N/A
20	Clearances, creepage distances, solid insulation and coatings of rigid printed board assemblies		----
	This clause is applicable to clearances and creepage distances for functional insulation, across full disconnection and micro-disconnection, as stated in table 24		N/A
I	ANNEX I (NORMATIVE) MOTORS HAVING BASIC INSULATION THAT IS INADEQUATE FOR THE RATED VOLTAGE OF THE APPLIANCE		----
	The following modifications to this standard are applicable for motors having basic insulation that is inadequate for the rated voltage of the appliance:		----
8	Protection against access to live parts		----
8.1	Metal parts of the motor are considered to be bare live parts		N/A
11	Heating		----
11.3	The temperature rise of the body of the motor is determined instead of the temperature rise of the windings		N/A
11.8	The temperature rise of the body of the motor, where in contact with insulating material, not exceeding values in table 3 for the relevant insulating material		N/A

IEC 60335-2-80			
Clause	Requirement - Test	Result - Remark	Verdict
16	Leakage current and electric strength		----
16.3	Insulation between live parts of the motor and its other metal parts is not subjected to the test		N/A
19	Abnormal operation		----
19.1	The tests of 19.7 to 19.9 are not carried out		N/A
19.1.101	Appliance operated at rated voltage with each of the following fault conditions:		----
	- short circuit of the terminals of the motor, including any capacitor incorporated in the motor circuit		N/A
	- short circuit of each diode of the rectifier		N/A
	- open circuit of the supply to the motor		N/A
	- open circuit of any parallel resistor, the motor being in operation		N/A
	Only one fault simulated at a time, the tests carried out consecutively		N/A
22	Construction		----
22.1.101	For class I appliances incorporating a motor supplied by a rectifier circuit, the d.c. circuit being insulated from accessible parts of the appliance by double or reinforced insulation		N/A
	Compliance checked by the tests specified for double and reinforced insulation		N/A
J	ANNEX J (NORMATIVE) COATED PRINTED CIRCUIT BOARDS		----
	Testing of protective coatings of printed circuit boards carried out in accordance with IEC 60664-3 with the following modifications:		----
5.7	Conditioning of the test specimens		----
	When production samples are used, three samples of the printed circuit board are tested		N/A
5.7.1	Cold		----
	The test is carried out at -25 °C		N/A
5.7.3	Rapid change of temperature		----
	Severity 1 is specified		N/A
5.9	Additional tests		----
	This subclause is not applicable		N/A
K	ANNEX K (NORMATIVE) OVERVOLTAGE CATEGORIES		----
	The information on overvoltage categories is extracted from IEC 60664-1		P

IEC 60335-2-80			
Clause	Requirement - Test	Result - Remark	Verdict
	Overvoltage category is a numeral defining a transient overvoltage condition		P
	Equipment of overvoltage category IV is for use at the origin of the installation		N/A
	Equipment of overvoltage category III is equipment in fixed installations and for cases where the reliability and the availability of the equipment is subject to special requirements		N/A
	Equipment of overvoltage category II is energy consuming equipment to be supplied from the fixed installation		P
	If such equipment is subjected to special requirements with regard to reliability and availability, overvoltage category III applies		N/A
	Equipment of overvoltage category I is equipment for connection to circuits in which measures are taken to limit transient overvoltages to an appropriate low level		N/A
L	ANNEX L (INFORMATIVE) GUIDANCE FOR THE MEASUREMENT OF CLEARANCES AND CREEPAGE DISTANCES		----
	Information for the determination of clearances and creepage distances		P
M	ANNEX M (NORMATIVE) POLLUTION DEGREE		----
	The information on pollution degrees is extracted from IEC 60664-1		P
	Pollution		----
	The microenvironment determines the effect of pollution on the insulation, taking into account the microenvironment		P
	Means may be provided to reduce pollution at the insulation by effective enclosures or similar		N/A
	Minimum clearances specified where pollution may be present in the microenvironment		P
	Degrees of pollution in the microenvironment		----
	For evaluating creepage distances, the following degrees of pollution in the microenvironment are established:		----
	- pollution degree 1: no pollution or only dry, non-conductive pollution occurs. The pollution has no influence		N/A

IEC 60335-2-80			
Clause	Requirement - Test	Result - Remark	Verdict
	- pollution degree 2: only non-conductive pollution occurs, except that occasionally a temporary conductivity caused by condensation is to be expected		P
	- pollution degree 3: conductive pollution occurs or dry non-conductive pollution occurs that becomes conductive due to condensation that is to be expected		P
	- pollution degree 4: the pollution generates persistent conductivity caused by conductive dust or by rain or snow		N/A
N	ANNEX N (NORMATIVE) PROOF TRACKING TEST		----
	The proof tracking test is carried out in accordance with IEC 60112 with the following modifications:		----
7	Test apparatus		----
7.3	Test solutions		----
	Test solution A is used		P
10	Determination of proof tracking index (PTI)		----
10.1	Procedure		----
	The proof voltage is 100V, 175V, 400V or 600V .. :	175V	P
	The test is carried out on five specimens		P
	In case of doubt, additional test with proof voltage reduced by 25V, the number of drops increased to 100		N/A
10.2	Report		----
	The report states if the PTI value was based on a test using 100 drops with a test voltage of (PTI-25) V		P
O	ANNEX O (INFORMATIVE) SELECTION AND SEQUENCE OF THE TESTS OF CLAUSE 30		----
	Description of tests for determination of resistance to heat and fire		P
P	ANNEX P (INFORMATIVE) GUIDANCE FOR THE APPLICATION OF THIS STANDARD TO APPLIANCES USED IN WARM DAMP EQUABLE CLIMATES		----
	Modifications applicable for class 0 and 01 appliances having a rated voltage exceeding 150V, intended to be used in countries having a warm damp equable climate and that are marked WDaE		----
	Modifications may also be applied to class 1 appliances having a rated voltage exceeding 150V, intended to be used in countries having a warm damp equable climate and that are marked WDaE, if liable to be connected to a supply mains that excludes the protective earthing conductor		----

TRF No. IEC60335_2_80E

Intertek Testing Services Shenzhen Ltd. Guangzhou Branch

Block E, No.7-2 Guang Dong Software Science Park, Caipin Road, Guangzhou Science City, GETDD, Guangzhou, China
Tel: 86 20 82139688 Fax: 86 20 32057538 www.intertek-etlsemko.com

IEC 60335-2-80			
Clause	Requirement - Test	Result - Remark	Verdict
5.7	The ambient temperature for the tests of clauses 11 and 13 is 40 +3/0 °C		N/A
7.1	The appliance marked with the letters WDaE		N/A
7.12	The instructions state that the appliance is to be supplied through a residual current device (RCD) having a rated residual operating current not exceeding 30 mA		N/A
	The instructions state that the appliance is considered to be suitable for use in countries having a warm damp equable climate, but may also be used in other countries		N/A
11.8	The values of Table 3 are reduced by 15 K		N/A
13.2	The leakage current for class I appliances not exceeding 0,5 mA		N/A
15.3	The value of t is 37 °C		N/A
16.2	The leakage current for class I appliances not exceeding 0,5 mA (mA):		N/A
19.13	The leakage current test of 16.2 is applied in addition to the electric strength test of 16.3		N/A
Q	ANNEX Q (INFORMATIVE) SEQUENCE OF TESTS FOR THE EVALUATION OF ELECTRONIC CIRCUITS		----
	Description of tests for appliances incorporating electronic circuits		P
R	ANNEX R (NORMATIVE) SOFTWARE EVALUATION		----
	Programmable electronic circuits requiring software incorporating measures to control the fault/error conditions specified in table R.1 or R.2 validated in accordance with the requirements of this annex		N/A
R.1	Programmable electronic circuits using software		----
	Programmable electronic circuits requiring software incorporating measures to control the fault/error conditions specified in table R.1 or R.2 constructed so that the software does not impair compliance with the requirements of this standard		N/A
R.2	Requirements for the architecture		----
	Programmable electronic circuits requiring software incorporating measures to control the fault/error conditions specified in table R.1 or R.2 use measures to control and avoid software-related faults/errors in safety-related data and safety-related segments of the software		N/A
R.2.1.1	Programmable electronic circuits requiring software incorporating measures to control the fault/error conditions specified in table R.2 have one of the following structures:		----

TRF No. IEC60335_2_80E

Intertek Testing Services Shenzhen Ltd. Guangzhou Branch

Block E, No.7-2 Guang Dong Software Science Park, Caipin Road, Guangzhou Science City, GETDD, Guangzhou, China
Tel: 86 20 82139688 Fax: 86 20 32057538 www.intertek-etlsemko.com

IEC 60335-2-80			
Clause	Requirement - Test	Result - Remark	Verdict
	- single channel with periodic self-test and monitoring		N/A
	- dual channel (homogenous) with comparison		N/A
	- dual channel (diverse) with comparison		N/A
	Programmable electronic circuits requiring software incorporating measures to control the fault/error conditions specified in table R.1 have one of the following structures:		----
	- single channel with functional test		N/A
	- single channel with periodic self-test		N/A
	- dual channel without comparison		N/A
R.2.2	Measures to control faults/errors		----
R.2.2.1	When redundant memory with comparison is provided on two areas of the same component, the data in one area is stored in a different format from that in the other area		N/A
R.2.2.2	Programmable electronic circuits with functions requiring software incorporating measures to control the fault/error conditions specified in table R.2 and that use dual channel structures with comparison, have additional fault/error detection means for any fault/errors not detected by the comparison		N/A
R.2.2.3	For programmable electronic circuits with functions requiring software incorporating measures to control the fault/error conditions specified in table R.1 or R.2, means are provided for the recognition and control of errors in transmissions to external safety-related data paths		N/A
R.2.2.4	For programmable electronic circuits with functions requiring software incorporating measures to control the fault/error conditions specified in table R.1 or R.2, the programmable electronic circuits incorporate measures to address the fault/errors in safety-related segments and data indicated in table R.1 and R.2 as appropriate		N/A
R.2.2.5	For programmable electronic circuits with functions requiring software incorporating measures to control the fault/error conditions specified in table R.1 or R.2, detection of a fault/error occur before compliance with clause 19 is impaired		N/A
R.2.2.6	The software is referenced to relevant parts of the operating sequence and the associated hardware functions		N/A
R.2.2.7	Labels used for memory locations are unique		N/A

IEC 60335-2-80			
Clause	Requirement - Test	Result - Remark	Verdict
R.2.2.8	The software is protected from user alteration of safety-related segments and data		N/A
R.2.2.9	Software and safety-related hardware under its control is initialized and terminates before compliance with clause 19 is impaired		N/A
R.3	Measures to avoid errors		----
R.3.1	General		----
	For programmable electronic circuits with functions requiring software incorporating measures to control the fault/error conditions specified in table R.1 or R.2, the following measures to avoid systematic fault in the software are applied		----
	Software that incorporates measures used to control the fault/error conditions specified in table R.2 is inherently acceptable for software required to control the fault/error conditions specified in table R.1		N/A
R.3.2	Specification		----
R.3.2.1	Software safety requirements:	Software Id:	N/A
	The specification of the software safety requirements includes the descriptions listed		N/A
R.3.2.2	Software architecture		----
R.3.2.2.1	The specification of the software architecture includes the aspects listed - techniques and measures to control software faults/errors (refer to R.2.2); - interactions between hardware and software; - partitioning into modules and their allocation to the specified safety functions; - hierarchy and call structure of the modules (control flow); - interrupt handling; - data flow and restrictions on data access; - architecture and storage of data; - time-based dependencies of sequences and data	Document ref. No:	N/A
R.3.2.2.2	The architecture specification is validated against the specification of the software safety requirements by static analysis		N/A
R.3.2.3	Module design and coding		----
R.3.2.3.1	Based on the architecture design, software is suitably refined into modules		N/A
	Software module design and coding is implemented in a way that is traceable to the software architecture and requirements		N/A
R.3.2.3.2	Software code is structured		N/A

TRF No. IEC60335_2_80E

Intertek Testing Services Shenzhen Ltd. Guangzhou Branch

Block E, No.7-2 Guang Dong Software Science Park, Caipin Road, Guangzhou Science City, GETDD, Guangzhou, China
Tel: 86 20 82139688 Fax: 86 20 32057538 www.intertek-etlsemko.com

IEC 60335-2-80			
Clause	Requirement - Test	Result - Remark	Verdict
R.3.2.3.3	Coded software is validated against the module specification by static analysis		N/A
	The module specification is validated against the architecture specification by static analysis		N/A
R.3.3.3	Software validation		----
	The software is validated with reference to the requirements of the software safety requirements specification		N/A
	Compliance is checked by simulation of:		----
	- input signals present during normal operation		N/A
	- anticipated occurrences		N/A
	- undesired conditions requiring system action		N/A

TABLE R.1 – GENERAL FAULT/ERROR CONDITIONS

Component ¹⁾	Fault/error	Acceptable measures ^{2) 3)}	Definitions	Document reference for applied measure	Document reference for applied test	Verdict
1 CPU 1.1 Registers	Stuck at	Functional test, or periodic self-test using either: - static memory test, or - word protection with single bit redundancy	H.2.16.5 H.2.16.6 H.2.19.6 H.2.19.8.2			N/A
1.2 VOID						N/A
1.3 Programme counter	Stuck at	Functional test, or Periodic self-test, or Independent time-slot monitoring, or Logical monitoring of the programme sequence	H.2.16.5 H.2.16.6 H.2.18.10.4 H.2.18.10.2			N/A
2 Interrupt handling and execution	No interrupt or too frequent interrupt	Functional test, or time-slot monitoring	H.2.16.5 H.2.18.10.4			N/A

IEC 60335-2-80						
Clause	Requirement - Test			Result - Remark		Verdict
3 Clock	Wrong frequency (for quartz synchronized clock: harmonics/sub-harmonics only)	Frequency monitoring, or time slot monitoring	H.2.18.10.1 H.2.18.10.4			N/A
4. Memory 4.1 Invariable memory	All single bit faults	Periodic modified checksum, or multiple checksum, or word protection with single bit redundancy	H.2.19.3.1 H.2.19.3.2 H.2.19.8.2			N/A
4.2 Variable memory	DC fault	Periodic static memory test, or word protection with single bit redundancy	H.2.19.6 H.2.19.8.2			N/A
4.3 Addressing (relevant to variable and invariable memory)	Stuck at	Word protection with single bit redundancy including the address	H.2.19.8.2			N/A
5 Internal data path	Stuck at DC fault	Word protection with single bit redundancy Comparison of redundant CPUs by either: - reciprocal comparison - independent hardware comparator	H.2.19.8.2 H.2.18.15 H.2.18.3			N/A
5.1 VOID						N/A
5.2 Addressing	Wrong address	Word protection with single bit redundancy including the address	H.2.19.8.2			N/A
6 External communication	Hamming distance 3	Word protection with multi-bit redundancy, or CRC – single work, or Transfer redundancy, or Protocol test	H.2.19.8.1 H.2.19.4.1 H.2.18.2.2 H.2.18.14			N/A
6.1 VOID						N/A
6.2 VOID						N/A
6.3	Wrong point	Time-slot monitoring, or	H.2.18.10.			N/A

TRF No. IEC60335_2_80E

Intertek Testing Services Shenzhen Ltd. Guangzhou Branch

Block E, No.7-2 Guang Dong Software Science Park, Caipin Road, Guangzhou Science City, GETDD, Guangzhou, China

Tel: 86 20 82139688 Fax: 86 20 32057538 www.intertek-etlsemko.com

IEC 60335-2-80						
Clause	Requirement - Test			Result - Remark		Verdict
Timing	in time	scheduled transmission Time-slot and logical monitoring, or Comparison of redundant communication channels by either: - reciprocal comparison - independent hardware comparator	4 H.2.18.18 H.2.18.10.3 H.2.18.15 H.2.18.3			
	Wrong sequence	Logical monitoring, or time-slot monitoring, or Scheduled transmission (same options as for wrong point in time)	H.2.18.10.2 H.2.18.10.4 H.2.18.18			
7 Input/output periphery	Fault conditions specified in 19.11.2	Plausibility check Comparison of redundant communication channels by either: - reciprocal comparison - independent hardware comparator	H.2.18.13 H.2.18.15 H.2.18.3			N/A
7.1 VOID						N/A
7.2 Analog I/O 7.2.1 A/D and D/A-converter	Fault conditions specified in 19.11.2	Plausibility check	H.2.18.13			N/A
7.2.2 Analog multiplexer	Wrong addressing	Plausibility check	H.2.18.13			N/A
8 VOID						N/A
9 Custom chips ⁴⁾ e.g. ASIC, GAL, Gate array	Any output outside the static and dynamic functional specification	Periodic self-test	H.2.16.6			N/A
NOTE A Stuck-at fault model denotes a fault model representing an open circuit or a non-varying signal level. A DC fault model denotes a stuck-at fault model incorporating short circuit between signal lines.						

IEC 60335-2-80			
Clause	Requirement - Test	Result - Remark	Verdict

- ¹⁾ For fault/error assessment, some components are divided into their sub-functions.
- ²⁾ For each sub-function in the table, the Table R.2 measure will cover the software fault/error.
- ³⁾ Where more than one measure is given for a sub-function, these are alternatives.
- ⁴⁾ To be divided as necessary by the manufacturer into sub-functions.

10.1	TABLE: Power input deviation					P
Input deviation of/at:	P rated (W)	P measured (W)	dP (W, %)	Required dP (W, %)	Remark	
230V, 50Hz for YH-40D1-1	60	51,9	-13,5%	+20%	—	
230V, 50Hz for YH-30D1	35	30,1	-14,0%	+20%	—	
230V, 50Hz for YH-40E-0	40	35,6	-11,0%	+20%	Fan motor '6614'	
230V, 50Hz for YH-23D1-1	20	20,5	+2,5%	+20%	—	
230V, 50Hz for YH-15D	15	10,9	-27,3%	+20%	—	
230V, 50Hz for YH-40R1-0	40	42,3	+5,7%	+20%	Fan motor '6614-1'	
230V, 50Hz for YH-40R-0	40	38,7	-3,2%	+20%	Fan motor '6614-1'	
Supplementary information: For fan motor '6614-1', the fan blade quantity '3' and '5' were tested and recorded the maximum value.						

10.2	TABLE: Current deviation					N/A
Current deviation of/at:	I rated (A)	I measured (A)	dI (A, %)	Required dI (A, %)	Remark	
----	----	----	----	----	----	
Supplementary information:						

11.8-1	TABLE: Heating test, thermocouples for YH-40D1-1			P
	Test voltage (V):	254,4	—	
	Ambient (°C):	22,0 °C — 22,0°C	—	
Thermocouple locations		dT (K)	Max. dT (K)	
Enclosure		0,7	60	
Fan motor winding (point 1)		49,5	Class 130: 85	
Fan motor winding (point 2)		45,4	Class 130: 85	
Internal wire		0,5	50	
Power cord		0,6	50	
Motor capacitor		0,9	T70-25=45	
Rotor box		2,9	For reference	
Knob		0,4	60	
Speed switch ambient		0,4	T55-25=30	
Closed-end connector		0,7	For reference	
Test corner		0,9	65	
11.8	TABLE: Heating test, resistance method			P
	Test voltage (V):	254,4	—	
	Ambient, t1 (°C):	23,0	—	

	Ambient, t ₂ (°C):			23,0		—
Temperature rise of winding	R1 (Ω)	R2 (Ω)	dT (K)	Max. dT (K)	Insulation class	
Main fan motor winding	881,0	1128,1	72,2	95	130	
Aux. fan motor winding	452,7	576,4	70,3	95	130	

11.8-2	TABLE: Heating test, thermocouples for YH-23D1-1					P
	Test voltage (V):			254,4		—
	Ambient (°C):			24,0 °C — 24,0°C		—
Thermocouple locations		dT (K)		Max. dT (K)		
Enclosure		4,8		60		
Fan motor winding (point 1)		44,7		Class 130: 85		
Fan motor winding (point 2)		44,2		Class 130: 85		
Internal wire		14,6		50		
Power cord		3,3		50		
Rotor box		4,1		For reference		
Knob		3,9		60		
Speed switch ambient		2,5		T55-25=30		
Closed-end connector		3,7		For reference		
Test corner		2,9		65		
11.8	TABLE: Heating test, resistance method					P
	Test voltage (V):			254,4		—
	Ambient, t1 (°C):			24,0		—
	Ambient, t2 (°C):			24,0		—
Temperature rise of winding		R1 (Ω)	R2 (Ω)	dT (K)	Max. dT (K)	Insulation class
Main fan motor winding		306,0	375,0	57,9	95	130
Aux. fan motor winding		344,0	427,9	62,6	95	130

11.8-3	TABLE: Heating test, thermocouples for YH-30D1					P
	Test voltage (V):			254,4		—
	Ambient (°C):			24,0 °C — 24,0°C		—
Thermocouple locations		dT (K)		Max. dT (K)		
Enclosure		2,9		60		
Fan motor winding (point 1)		44,2		Class 130: 85		
Fan motor winding (point 2)		46,8		Class 130: 85		
Internal wire		14,6		50		

Modification 6: November 14, 2019

Power cord		3,1		50		
Motor capacitor		1,4		T70-25=45		
Rotor box		13,2		For reference		
Knob		2,8		60		
Speed switch ambient		1,0		T55-25=30		
Closed-end connector		3,0		For reference		
Test corner		2,1		65		
11.8	TABLE: Heating test, resistance method					P
	Test voltage (V):			254,4		—
	Ambient, t1 (°C):			24,0		—
	Ambient, t2 (°C):			24,0		—
Temperature rise of winding		R1 (Ω)	R2 (Ω)	dT (K)	Max. dT (K)	Insulation class
Main fan motor winding		746,0	877,4	45,5	95	130
Aux. fan motor winding		784,0	916,6	43,7	95	130

11.8-4	TABLE: Heating test, thermocouples for YH-15D					P
	Test voltage (V):			254,4		—
	Ambient (°C):			24,0 °C — 24,0°C		—
Thermocouple locations		dT (K)			Max. dT (K)	
Enclosure		6,3			60	
Fan motor winding (point 1)		19,8			Class 130: 85	
Fan motor winding (point 2)		40,6			Class 130: 85	
Internal wire		8,5			50	
Power cord		7,8			50	
Knob		5,1			60	
Speed switch ambient		11,3			T55-25=30	
Closed-end connector		9,9			For reference	
Test corner		5,7			65	
11.8	TABLE: Heating test, resistance method					P
	Test voltage (V):			254,4		—
	Ambient, t1 (°C):			24,0		—
	Ambient, t2 (°C):			24,0		—
Temperature rise of winding		R1 (Ω)	R2 (Ω)	dT (K)	Max. dT (K)	Insulation class
Main fan motor winding		706,0	820,5	41,9	95	130
Aux. fan motor winding		708,0	820,0	40,9	95	130

11.8-5	TABLE: Heating test, thermocouples for YH-40E-0 with fan motor '6614'					P
	Test voltage (V):			254,4		—
	Ambient (°C):			24,0 °C — 24,0°C		—
Thermocouple locations		dT (K)		Max. dT (K)		
Enclosure		3,9		60		
Fan motor winding (point 1)		43,6		Class 130: 85		
Fan motor winding (point 2)		48,8		Class 130: 85		
Internal wire		22,4		50		
Power cord		4,1		50		
Motor capacitor		4,2		T70-25=45		
Rotor box		14,7		For reference		
Knob		4,0		60		
Timer ambient		4,3		T55-25=30		
Speed switch ambient		3,8		T55-25=30		
Closed-end connector		4,4		For reference		
Test corner		3,0		65		
11.8	TABLE: Heating test, resistance method					P
	Test voltage (V):			254,4		—
	Ambient, t1 (°C):			24,0		—
	Ambient, t2 (°C):			24,0		—
Temperature rise of winding		R1 (Ω)	R2 (Ω)	dT (K)	Max. dT (K)	Insulation class
Main fan motor winding		746,0	881,4	46,9	95	130
Aux. fan motor winding		784,0	916,5	43,7	95	130

11.8-6	TABLE: Heating test, thermocouples for YH-40R1-0 with fan motor ‘6614-1’		P
	Test voltage (V):	254,4	—
	Ambient (°C):	20,8 °C — 21,1°C	—
Thermocouple locations		dT (K)	Max. dT (K)
Supply cord		4,4	50
Internal wire for motor		36,0	T105-25=80
Internal wire for other load		3,8	T80-25=55
X capacitor		7,2	T85-25=60
PCB		7,9	120
Winding of fan motor		73,0	85
Sleeving		34,9	T90-25=65
Running capacitor for fan motor		26,1	T70-25=45

Surface of Sync. motor		22,3		For reference		
Plastic enclosure		18,8		For clause 30.1		
Control panel		23,9		60		
Test corner		0,7		65		
11.8	TABLE: Heating test, resistance method					P
	Test voltage (V):			254,4		—
	Ambient, t1 (°C):			20,8		—
	Ambient, t2 (°C):			21,1		—
Temperature rise of winding		R1 (Ω)	R2 (Ω)	dT (K)	Max. dT (K)	Insulation class
Total winding of fan motor		1476	1946,2	81,0	95	130
Winding of Sync. motor		9520	12161,7	70,5	90	120

11.8-7	TABLE: Heating test, thermocouples for YH-40R-0 with fan motor ‘6614-1’					P
	Test voltage (V):			254,4		—
	Ambient (°C):			16,8 °C — 18,3°C		—
Thermocouple locations		dT (K)			Max. dT (K)	
Supply cord		6,7			50	
Internal wire for motor		33,1			T105-25=80	
Internal wire for other load		5,3			T80-25=55	
X capacitor		11,4			T85-25=60	
PCB		7,8			120	
Winding of fan motor		70,9			85	
Sleeving		35,4			T90-25=65	
Running capacitor for fan motor		12,9			T70-25=45	
Plastic enclosure		21,4			For clause 30.1	
Control panel		4,2			60	
Test corner		3,2			65	
11.8	TABLE: Heating test, resistance method					P
	Test voltage (V):			254,4		—
	Ambient, t1 (°C):			16,8		—
	Ambient, t2 (°C):			18,3		—
Temperature rise of winding		R1 (Ω)	R2 (Ω)	dT (K)	Max. dT (K)	Insulation class
Total winding of fan motor		1495	1975,6	79,3	95	130

13.2	TABLE: Leakage current		P
	Heating appliances: 1.15 x rated input (W) :	---	—
	Motor-operated and combined appliances: 1.06 x rated voltage (V) :	254,4	—
Leakage current between		I (mA)	Max. allowed I (mA)
Live parts and Knob/plastic enclosure		Max: L: 0,061/N:0,053	0,35 mA peak
Remark:			

13.3	TABLE: Electric strength		P
Test voltage applied between:		Voltage (V)	Breakdown (Yes/No)
Live parts and metal surface of motor		1000	No
Internal wire and enclosure		1750	No
Live parts and enclosure		3000	No
Supplementary information:			

14	TABLE: Transient overvoltages					N/A
Clearance between:		CI (mm)	Required CI (mm)	Rated impulse voltage (V)	Impulse test voltage (V)	Flashover (Yes/No)
----		----	----	----	----	----
Supplementary information:						

16.2	TABLE: Leakage current		P
	Single phase appliances: 1.06 x rated voltage (V) :	254,4	—
	Three phase appliances 1.06 x rated voltage divided by $\sqrt{3}$ (V) :	---	—
Leakage current between		I (mA)	Max. allowed I (mA)
Live parts and control panel/plastic enclosure		Max: 0,08	0,25
Remark:			

16.3	TABLE: Electric strength		P
Test voltage applied between:		Voltage (V)	Breakdown (Yes/No)
Live parts and metal surface of motor		1250	No
Internal wire and enclosure		1750	No
Live parts and enclosure		3000	No
Supplementary information:			

17	TABLE: Overload protection, thermocouple measurements		N/A
Temperature rise of part/at:		dT (K)	Max. dT (K)
----		----	----
Supplementary information:			

17	TABLE: Overload protection, resistance method					N/A
	Test voltage (V).....:		----		—	
	Ambient, t1 (°C)		----		—	
	Ambient, t2 (°C)		----		—	
Temperature of winding		R1 (Ω)	R2 (Ω)	dT (K)	T (°C)	Max. T (°C)
----		----	----	----	----	----
Supplementary information:						

19.7-1	TABLE: Abnormal operation, locked rotor/moving parts for fan motor ‘4815’					P
	Test voltage (V).....:			240		—
	Ambient, t1 (°C)			24,0		—
	Ambient, t2 (°C)			24,0		—
Temperature of winding		R1 (Ω)	R2 (Ω)	dT (K)	T (°C)	Max. T (°C)
Main fan motor winding		706,0	999,7	107,5	131,5	175
Aux. fan motor winding		708,0	997,2	105,6	129,6	175
Remark: Steady state and no hazards.						

19.7-2	TABLE: Abnormal operation, locked rotor/moving parts for fan motor ‘6016’					P
	Test voltage (V).....:			240		—
	Ambient, t1 (°C)			24,0		—
	Ambient, t2 (°C)			24,0		—
Temperature of winding		R1 (Ω)	R2 (Ω)	dT (K)	T (°C)	Max. T (°C)
Main fan motor winding		706,0	1001,2	108,1	133,1	175
Aux. fan motor winding		708,0	1004,9	108,4	133,4	175
Remark: Steady state and no hazards.						

19.7-3	TABLE: Abnormal operation, locked rotor/moving parts for fan motor '7118'		P
	Test voltage (V):	240	—
	Ambient, t1 (°C):	See below	—
	Ambient, t2 (°C):	See below	—

Modification 6: November 14, 2018

Temperature of winding	R1 (Ω)	R2 (Ω)	dT (K)	T ($^{\circ}\text{C}$)	Max. T ($^{\circ}\text{C}$)
Lock motor Ambient (t1- t2):23,0 $^{\circ}\text{C}$ - 23,0 $^{\circ}\text{C}$					
Main winding of fan motor	881,0	1257,8	110,1	133,1	225
Aux. winding of fan motor	454,0	627,0	98,1	121,1	225
Lock motor and open-circuit of motor running capacitor, Ambient (t1- t2): 23,0 $^{\circ}\text{C}$ – 23,0 $^{\circ}\text{C}$					
Main winding of fan motor	880,0	1275,3	115,7	138,7	225
Aux. winding of fan motor	454,0	657,0	115,1	138,1	225
Lock motor and short-circuit of motor running capacitor, Ambient (t1- t2): 23,0 $^{\circ}\text{C}$ – 23,0 $^{\circ}\text{C}$					
Main winding of fan motor	880,0	1333,2	132,2	155,2	225
Aux. winding of fan motor	454,0	682,8	130,9	153,9	225
Remark: During the tests, thermal-link in fan motor operated within 1 hour, the appliance stopped work and no hazards.					

19.7-4	TABLE: Abnormal operation, locked rotor/moving parts for fan motor '6612'				P
	Test voltage (V):	240			—
	Ambient, t1 ($^{\circ}\text{C}$):	See below			—
	Ambient, t2 ($^{\circ}\text{C}$):	See below			—
Temperature of winding	R1 (Ω)	R2 (Ω)	dT (K)	T ($^{\circ}\text{C}$)	Max. T ($^{\circ}\text{C}$)
Lock motor Ambient (t1- t2):24,0 $^{\circ}\text{C}$ - 24,0 $^{\circ}\text{C}$					
Total winding of fan motor	1530,0	2072,1	91,6	116,6	225
Lock motor and open-circuit of motor running capacitor, Ambient (t1- t2): 24,0 $^{\circ}\text{C}$ – 24,0 $^{\circ}\text{C}$					
Total winding of fan motor	1530,0	2126,5	100,8	124,8	225
Lock motor and short-circuit of motor running capacitor, Ambient (t1- t2): 24,0 $^{\circ}\text{C}$ – 24,0 $^{\circ}\text{C}$					
Total winding of fan motor	1530,0	2193,1	112,0	136,0	225
Remark: During the tests, thermal-link in fan motor operated within 1 hour, the appliance stopped work and no hazards.					

19.7-5	TABLE: Abnormal operation, locked rotor/moving parts for fan motor '6614'				P
	Test voltage (V):	240			—
	Ambient, t1 ($^{\circ}\text{C}$):	See below			—
	Ambient, t2 ($^{\circ}\text{C}$):	See below			—
Temperature of winding	R1 (Ω)	R2 (Ω)	dT (K)	T ($^{\circ}\text{C}$)	Max. T ($^{\circ}\text{C}$)
Lock motor Ambient (t1- t2):24,0 $^{\circ}\text{C}$ - 24,0 $^{\circ}\text{C}$					
Total winding of fan motor	1530,0	2151,6	105,1	129,1	225
Lock motor and open-circuit of motor running capacitor, Ambient (t1- t2): 24,0 $^{\circ}\text{C}$ – 24,0 $^{\circ}\text{C}$					

Total winding of fan motor	1530,0	2067,7	90,8	114,8	225
Lock motor and short-circuit of motor running capacitor, Ambient (t1- t2): 24,0°C – 24,0°C					
Total winding of fan motor	1530,0	2204,8	114,0	138,0	225
Remark: During the tests, thermal-link in fan motor operated within 1 hour, the appliance stopped work and no hazards.					

19.7-6	TABLE: Abnormal operation, locked rotor/moving parts for fan motor '6614-1'					P
	Test voltage (V):		240		—	
	Ambient, t1 (°C):		See below		—	
	Ambient, t2 (°C):		See below		—	
Temperature of winding		R1 (Ω)	R2 (Ω)	dT (K)	T (°C)	Max. T (°C)
Lock motor Ambient (t1- t2):16,7°C – 17,9°C						
Winding of fan motor		—	—	—	166,6	225
Lock motor and open-circuit of motor running capacitor, Ambient (t1- t2): 17,5°C – 18,0°C						
Winding of fan motor		—	—	—	165,4	225
Remark: During the tests, thermal-link in fan motor operated within 1 hour, the appliance stopped work and no hazards.						

19.7-7	TABLE: Abnormal operation, locked rotor/moving parts for Sync. motor					P
	Test voltage (V):		240		—	
	Ambient, t1 (°C):		20,8		—	
	Ambient, t2 (°C):		21,6		—	
Temperature of winding		R1 (Ω)	R2 (Ω)	dT (K)	T (°C)	Max. T (°C)
Winding of Sync. motor		9520	11658,1	56,5	78,1	165
Remark: impedance protected.						

19.13	TABLE: Abnormal operation, temperature rises		P
Thermocouple locations	Max. temperature rise measured, dT (K)	Max.temperature rise limit, dT (K)	
Plastic enclosure	65,0	For clause 30.1	
Supplementary information:			

24.1	TABLE: Components					P
Object / part No.	Manufacturer/ trademark	Type / model	Technical data	Standard	Mark(s) of conformity	

Plug	Zhongshan Chuangyi Electric Appliance Co., Ltd	CY-01	AC 250V, 2,5A	DIN VDE 0620-1	VDE 40027881
Alternative	Guangdong KaiHua Electric Appliance Co., Ltd	KH-9903	AC250V, 2,5A	DIN VDE 0620-1	VDE 138563
Alternative	Zhongshan Hongyun Electrical Appliance Co., Ltd.	HY-008	AC250V, 2,5A	DIN VDE 0620-1	VDE 40032414
Alternative	JIANGMEN GOMENTECH ELECTRICAL CO., LTD.	GM-02	AC250V, 2,5A	DIN VDE 0620-1	VDE 40022512
Alternative	SHUNDE LUNJIAO KAITE WIRE AND CABLES Co., Ltd.	KE-101	AC250V, 2,5A	DIN VDE 0620-1	VDE 40008752
Alternative	Guangdong Yincheng Electric Appliance Co. Ltd.	YC-S2.5	AC250V, 2,5A	DIN VDE 0620-1	VDE 40025273
Alternative	Jhi Wei Electric Wire & Cable Co. Ltd.	JW-05	AC250V, 2,5A	DIN VDE 0620-1	VDE 40005490
Alternative	Dongguan Kunze Electronics Co.,Ltd.	KE-121	AC250V, 2,5A	DIN VDE 0620-1	VDE 40044334
Alternative	Unirise Electric Wire & Cable Co., Ltd.	UE-211	AC250V, 2,5A	DIN VDE 0620-1	VDE 40014452
BS Plug for United Kingdom	KDJ Quality Electrical Co., Ltd.	KDJ828	AC250V, 13A	BS 1363-1	BSI KM 54583
Alternative	Dongguan Toongyeon Plastic Ind. Co., Ltd.	TY-998	AC250V, 13A	BS 1363-1	BSI KM 535718
Alternative	Fund Resources Electric Industry Co., Ltd. (Shanghang)	BS-01J	AC250V, 13A	BS 1363-1	ASTA 1049
Alternative	Guangdong Kaihua Electric Appliance Co., Ltd.	KH-9917	13A, AC250V	BS1363-1	BSI KM 500333
Alternative	Donggaun Ubill Electrical Co., LTD	UBL 8008	13A, AC250V	BS1363-1	ASTA 1183

TRF No. IEC60335_2_80E

Intertek Testing Services Shenzhen Ltd. Guangzhou Branch

Block E, No.7-2 Guang Dong Software Science Park, Caipin Road, Guangzhou Science City, GETDD, Guangzhou, China
Tel: 86 20 82139688 Fax: 86 20 32057538 www.intertek-etlsemko.com

Alternative	Shen Zhen HongShan Chuan Industry Co.,Ltd	HSC-601	13A, AC250V	BS1363-1	ASTA 1266
Alternative	Luen Tai Ip's Electrical (Shenzhen)Co.,Ltd	9518	13A, AC250V	BS1363-1	BSI KM 40790
Alternative	Jiangmen Yincheng Wire Co., Ltd	YC-185	3A/6A, AC250V	BS1363-1	DEKRA 35-105517
Supply cord for models having a mass exceeding 3 kg	Zhongshan Hongyun Electrical Appliance Co., Ltd.	H05VV-F H05VVH2-F	2x 0,75 mm ²	EN 50525-2-11	VDE 40041433
Alternative	SHUNDE LUNJIAO KAITE WIRE AND CABLES Co., Ltd.	H05VV-F H05VVH2-F	2x 0,75 mm ²	EN 50525-2-11	VDE 40004728
Alternative	JIANGMEN GOMENTECH ELECTRICAL CO., LTD.	H05VV-F H05VVH2-F	2x 0,75 mm ²	EN 50525-2-11	VDE 40018946
Alternative	Guangdong Yongrui Cable Technology Co., Ltd	H05VV-F H05VVH2-F	2x 0,75 mm ²	EN 50525-2-11	VDE 40021527
Alternative	Guangdong Yincheng Electric Appliance Co. Ltd.	H05VV-F H05VVH2-F	2x 0,75 mm ²	EN 50525-2-11	VDE 40018525
Alternative	Zhongshan ChuangYi Electric Appliance Co., Ltd	H05VV-F H05VVH2-F	2x 0,75 mm ²	EN 50525-2-11	VDE 40023207
Alternative	Guangdong KaiHua Electric Appliance Co., Ltd	H05VV-F H05VVH2-F	2x 0,75 mm ²	EN 50525-2-11	VDE 40001903
Alternative	Jhi Wei Electric Wire & Cable Co. Ltd.	H05VV-F H05VVH2-F	2x 0,75 mm ²	EN 50525-2-11	VDE 40004775
Alternative	Dongguan Kunze Electronics Co.,Ltd.	H05VV-F H05VVH2-F	2x 0,75 mm ²	EN 50525-2-11	VDE 40042009
Alternative	Unirise Electric Wire & Cable Co., Ltd.	H05VV-F H05VVH2-F	2x 0,75 mm ²	EN 50525-2-11	VDE 40017449
Alternative	Dongguan Ubill Electrical Co.,Ltd.	H05VV-F H05VVH2-F	2x 0,75 mm ²	EN 50525-2-11	VDE 40042748
Supply cord for models having a mass not exceeding 3 kg	Zhongshan Hongyun Electrical Appliance Co., Ltd.	H03VV-F H03VVH2-F	2x0,5 mm ² (length ≤2m); 2x0,75 mm ²	EN 50525-2-11	VDE 40041433

Alternative	SHUNDE LUNJIAO KAITE WIRE AND CABLES Co., Ltd.	H03VV-F H03VVH2-F	2×0,5 mm ² (length ≤2m); 2×0,75 mm ²	EN 50525-2-11	VDE 40004728
Alternative	JIANGMEN GOMENTECH ELECTRICAL CO., LTD.	H03VV-F H03VVH2-F	2×0,5 mm ² (length ≤2m); 2×0,75 mm ²	EN 50525-2-11	VDE 40018946
Alternative	Zhongshan ChuangYi Electric Appliance Co., Ltd	H03VV-F H03VVH2-F	2×0,5 mm ² (length ≤2m); 2×0,75 mm ²	EN 50525-2-11	VDE 40023207
Alternative	Guangdong KaiHua Electric Appliance Co., Ltd	H03VV-F H03VVH2-F	2×0,5 mm ² (length ≤2m); 2×0,75 mm ²	EN 50525-2-11	VDE 40001903
Alternative	Jhi Wei Electric Wire & Cable Co. Ltd.	H03VV-F H03VVH2-F	2×0,5 mm ² (length ≤2m); 2×0,75 mm ²	EN 50525-2-11	VDE 40004775
Alternative	Guangdong Yincheng Electric Appliance Co. Ltd.	H03VV-F H03VVH2-F	2×0,5 mm ² (length ≤2m); 2×0,75 mm ²	EN 50525-2-11	VDE 40018525
Alternative	Guangdong Yongrui Cable Technology Co., Ltd	H03VV-F H03VVH2-F	2×0,5 mm ² (length ≤2m); 2×0,75 mm ²	EN 50525-2-11	VDE 40021527
Alternative	Dongguan Kunze Electronics Co.,Ltd.	H03VV-F H03VVH2-F	2×0,5 mm ² (length ≤2m); 2×0,75 mm ²	EN 50525-2-11	VDE 40042009
Alternative	Unirise Electric Wire & Cable Co., Ltd.	H03VV-F H03VVH2-F	2×0,5 mm ² (length ≤2m); 2×0,75 mm ²	EN 50525-2-11	VDE 40017449
Alternative	Dongguan Ubill Electrical Co.,Ltd.	H03VV-F H03VVH2-F	2×0,5 mm ² (length ≤2m); 2×0,75 mm ²	EN 50525-2-11	VDE 40042748
Timer for model YH-40E-y	Foshan Shunde Huaxinde Industry Co.,Ltd.	DFJ60, DFJ120	AC 250V,1.6A, T55,3000 cycle	IEC 60730	TUV B 12 04 55905 002

Speed switch for models YH-40C-y, YH-40H-y, YH-40E-y, YH-40D, YH-40D1, YH-40D1-1, YH-30D, YH-30D1, YH-30D2, YH-30D1-1, YH-40S-y and YH-40A-y, YH-40A3, YH-40A3-1, YH-40A3-2, YH-40A3-0, YH-40A3-1-0, YH-40A3--2-0, YH-40I, YH-40I-0, YH-40A1, YH-40A1-1, YH-40A1-2, YH-40A1-0, YH-40A1-1-0, YH-40A1--2-0, YH-40A2, YH-40A2-1, YH-40A2-2, YH-40A2-0, YH-40A2-1-0, YH-40A2--2-0, YH-40I1, YH-40I1-0, YH-40LK-0, YH-40LK-1, YH-40LK-2	Zhongshan City Natou Town Xinting Electric Manufacturing Factory	KQ-184A	AC250V, 1A, T55,1E4 cycles	EN 61058-1	TÜV Rheinland R 50097307
Alternative	Foshan Nanhai Jingzheng Hardware Products Co.,Ltd	JZ-4	AC250V, 1A, T85, 1E4 cycles	EN 61058-1	TÜV R 50394285
Speed switch for YH-40J-0, YH-40J-1, YH-40J-2, YH-40D2, YH-30D3	Foshan Shunde Yuanfeng Metal Electrical Appliances Co., Ltd.	YX3	AC250V, 3(1)A, T125,1E4 cycles	EN 61058-1	TÜV Rheinland R 50089831
Speed switch for models YH-40S1-y	Zhongshan City Natou Town Xinting Electric Manufacturing Factory	KQ-165A	AC250V, 1A, T55,1E4 cycles	EN 61058-1	TÜV Rheinland R 50097307
Speed switch for models YH-23D, YH-23D1	Zhongshan City Natou Town Xinting Electric Manufacturing Factory	KQ-153A	AC250V, 1A, T55,1E4 cycles	EN 61058-1	TÜV Rheinland R 50097307

Speed switch for models YH-40A-y, YH-40B-y, YH-40C-y, YH-40F-y, YH-40H-y, YH-40E-x-y, YH-40D, YH-30D2, YH-23D	Zhongshan Xiaolan ChengLian Hardware Electrical Factory	CK-04	AC250V, 1(1)A, T55,1E4 cycles	EN 61058-1	TÜV Rheinland R 50087410
Speed switch for models YH-40A-x-y, YH-40H-y, YH-40E-x-y, YH-40D, YH-40D1, YH-40D1-1, YH-30D, YH-30D1, YH-30D1-1, YH-30D2, YH-40LK-0, YH-40LK-1, YH-40LK-2	Zhongshan Xiaolan Huafeng Electrical Appliance Manufactory	ZD-418	AC250V, 1(1)A, T55,1E4 cycles	EN 61058-1	TÜV Rheinland R 50082610
Speed switch for models YH-23D, YH-23D1, YH-23D1-1	Zhongshan Xiaolan Huafeng Electrical Appliance Manufactory	ZD-318	AC250V, 1(1)A, T55,1E4 cycles	EN 61058-1	TÜV Rheinland R 50082610
Alternative	Foshan Nanhai Jingzheng Hardware Products Co.,Ltd	JZ-3	AC250V, 1A, T85, 1E4 cycles	EN 61058-1	TÜV R 50394285
Speed switch for models YH-15 series	Zhongshan Xiaolan ChengLian Hardware Electrical Factory	CK-08	AC250V, 1A, T55,1E4 cycles	EN 61058-1	TÜV Rheinland R 50122282
Alternative	Zhongshan Xiaolan Huafeng Electrical Appliance Manufactory	ZD-X-22	AC250V, 1(1)A, T55,1E4 cycles	EN 61058-1	TÜV Rheinland R 50271469
Alternative	Foshan Nanhai Jingzheng Hardware Products Co.,Ltd	JZ-X1	AC250V, 1A, T85, 1E4 cycles	EN 61058-1	TÜV R 50395452
Synchronous motor for YH-40R1-0, YH-40R1-1, YH-40R1-2	Foshan Shunde retian Hardware Electrical	TYJ	220-240V~; 50Hz; 4W; Class 120	EN 60335-1 EN 60335-2-80	TÜV R 50312126 Tested with appliance

Modification 6: November 14, 2018

Fan motor for YH-40x-y, YH-40D, YH-40D1, YH-40D2, YH-30D1-1, YH-40A1, YH-40A1-1, YH-40A1-2, YH-40A1-0, YH-40A1-1-0, YH-40A1--2-0, YH-40A2, YH-40A2-1, YH-40A2-2, YH-40A2-0, YH-40A2-1-0, YH-40A2--2-0, YH-40I1, YH40I1-0, YH-40R-0, YH-40R-1, YH-40R-2, YH-40R1-0, YH-40R1-1, YH-40R1-2, YH-40J-0, YH-40J-1, YH-40J-2, YH-40LK-0, YH-40LK-1, YH-40LK-2	Zhongshan city of electrical appliance factory	6614	AC220-240V, 50Hz, 40W, Class 130	EN 60335-1 EN 60335-2-80	Tested with appliance
Alternative	Zhongshan city of electrical appliance factory	6614-1	AC220-240V, 50Hz, 40W, Class 130	EN 60335-1 EN 60335-2-80	Tested with appliance
Fan motor for YH-30D, YH-30D1, YH-30D2, YH-30D3	Zhongshan city of electrical appliance factory	6612	AC220-240V, 50Hz, 35W, Class 130	EN 60335-1 EN 60335-2-80	Tested with appliance
Fan motor for YH-23 series	Zhongshan city of electrical appliance factory	6016	AC220-240V, 50Hz, 20W, Class 130	EN 60335-1 EN 60335-2-80	Tested with appliance
Fan motor for YH-40D1-1, YH-40A3, YH-40A3-1, YH-40A3-2, YH-40A3-0, YH-40A3-1-0, YH-40A3--2-0, YH-40I, YH-40I-0	Zhongshan city of electrical appliance factory	7118	AC220-240V, 50Hz, 60W, Class 130	EN 60335-1 EN 60335-2-80	Tested with appliance
Fan motor for YH-15 series	Zhongshan city of electrical appliance factory	4815	AC220-240V, 50Hz, 15W, Class 130	EN 60335-1 EN 60335-2-80	Tested with appliance
- Thermal link for all models	Aupo Electronics Ltd.	A4-F	AC250V, 2A, Tf: 130°C	EN 60691	VDE 40008720
Alternative	Nanhai Pingzhou Changcai Electric Component Factory	C5	AC250V, 2A, Tf: 130°C	EN 60691	VDE 40018700

TRF No. IEC60335_2_80E

Intertek Testing Services Shenzhen Ltd. Guangzhou Branch

Block E, No.7-2 Guang Dong Software Science Park, Caipin Road, Guangzhou Science City, GETDD, Guangzhou, China

Tel: 86 20 82139688 Fax: 86 20 32057538 www.intertek-etlsemko.com

Alternative	Honghu Bluelight Electronic Co., Ltd.	RH 130-2	AC250V, 2A, Tf: 130°C	EN 60691	VDE 40019233
Motor running Capacitor (1,0μF for fan motor "6612"; 1,2μF for fan motor "6614", "6614-1"; 1,5μF for fan motor "7118")	Foshan City Shunde District Ronggui Sunbird Electrical Equipment Co., Ltd.	CBB61-2	AC400/450V, 50/60Hz, 1,0μF/1,2μF/1,5μF, 25/70/21, P2	EN 60252-1	TÜV Rheinland R 50283769
Alternative	Guangdong Fengming Electronic Tech. Co., Ltd.	CBB61-P2	AC400/450V, 50/60Hz, 1,0μF/1,2μF/1,5μF, 25/70/21, P2	EN 60252-1	TÜV Rheinland R 50163114
Alternative	Xunde Electrical and Electronic Co., Ltd	CBB61 P2	AC 450V, 1,0μF/1,2μF/1,5μF, 25/70/21, P2	EN 60252-1	TÜV Rheinland R 50105972
Alternative	Sheng Ye Electrical Co., Ltd	C61-P2-xy	AC450V, 1,0μF/1,2μF/1,5μF, T85, P2	EN 60252-1	TUV R 50010886
Alternative	Shunde Dahua Electric Co., Ltd.	CBB6-1 CBB61	AC450V, 1,0μF/1,2μF/1,5μF, T70, P2	EN 60252-1	TUV R 50033889
Alternative	Zhongshan Xiongli Electric Appliances Factory	CBB61	AC450V, 50/60Hz, 1,0μF/1,2μF/1,5μF, 25/70/21, S3	EN 60252-1	TUV B 1601945810 02
Internal wire	DONG GUAN YONG SHENG CABLES CO LTD	1015	600V; 105°C; 18-22AWG;	EN 60335-1 EN 60335-2-80	Tested with appliance & UL E310859
Alternative	DONG GUAN YONG SHENG CABLES CO LTD	1007	300V; 80°C; 18-22AWG	EN 60335-1 EN 60335-2-80	Tested with appliance & UL E310859
Alternative	ZHONGSHAN XIANGHE ELECTRONICS CO LTD	1015	600 V, 18-22 AWG, 105°C	EN 60335-1 EN 60335-2-80	Tested with appliance & UL E336513
Alternative	ZHONGSHAN XIANGHE ELECTRONICS CO LTD	1007	300V; 80°C; 18-22AWG	EN 60335-1 EN 60335-2-80	Tested with appliance & UL E336513
Alternative	FOSHAN CITY SHUNDE JIN SHENG LONG ELE APPL CO LTD	1015	600 V, 18-22 AWG, 105°C	EN 60335-1 EN 60335-2-80	Tested with appliance & UL E245714
Alternative	FOSHAN CITY SHUNDE JIN SHENG LONG ELE APPL CO LTD	1007	300V; 80°C; 18-22AWG	EN 60335-1 EN 60335-2-80	Tested with appliance & UL E245714

TRF No. IEC60335_2_80E

Intertek Testing Services Shenzhen Ltd. Guangzhou Branch

Block E, No.7-2 Guang Dong Software Science Park, Caipin Road, Guangzhou Science City, GETDD, Guangzhou, China
Tel: 86 20 82139688 Fax: 86 20 32057538 www.intertek-etlsemko.com

Modification 6: November 14, 2018

Alternative	ZHONGSHAN DONGFENG KESHIRUIHUA WIRE & CABLE FACTORY	1015	600V; 105°C; 18-22AWG;	EN 60335-1 EN 60335-2-80	Tested with appliance & UL E307703
Alternative	ZHONGSHAN DONGFENG KESHIRUIHUA WIRE & CABLE FACTORY	1007	300V; 80°C; 18-22AWG	EN 60335-1 EN 60335-2-80	Tested with appliance & UL E307703
Alternative	ZHONGSHAN CITY SENBAO ELECTRIC CO., LTD.	1015	600V; 105°C; 18-22AWG;	EN 60335-1 EN 60335-2-80	Tested with appliance & UL E199818
Alternative	ZHONGSHAN CITY SENBAO ELECTRIC CO., LTD.	1007	300V; 80°C; 18-22AWG	EN 60335-1 EN 60335-2-80	Tested with appliance & UL E199818
Alternative	DONGGUAN WENCHANG ELECTRONIC CO LTD	1015	600V; 105°C; 18-22AWG;	EN 60335-1 EN 60335-2-80	Tested with appliance & UL E214500
Alternative	DONGGUAN WENCHANG ELECTRONIC CO LTD	1007	300V; 80°C; 18-22AWG	EN 60335-1 EN 60335-2-80	Tested with appliance & UL E214500
Alternative	FOSHAN SHUNDE LONGHEN INDUSTRY CO., LTD.	1015	600V; 105°C; 18-22AWG;	EN 60335-1 EN 60335-2-80	Tested with appliance & UL E254394
Alternative	FOSHAN SHUNDE LONGHEN INDUSTRY CO., LTD.	1007	300V; 80°C; 18-22AWG	EN 60335-1 EN 60335-2-80	Tested with appliance & UL E254394
Alternative	SHUNDE BEIJIAO JINHUI PLASTIC METALS FACTORY	1015	600V; 105°C; 18-22AWG;	EN 60335-1 EN 60335-2-80	Tested with appliance & UL E237283
Alternative	SHUNDE BEIJIAO JINHUI PLASTIC METALS FACTORY	1007	300V; 80°C; 18-22AWG	EN 60335-1 EN 60335-2-80	Tested with appliance & UL E237283
Alternative	GUANGZHOU ZHIHE ELECTRONIC CO LTD	1015	600V; 105°C; 18-22AWG;	EN 60335-1 EN 60335-2-80	Tested with appliance & UL E251728
Alternative	GUANGZHOU ZHIHE ELECTRONIC CO LTD	1007	300V; 80°C; 18-22AWG	EN 60335-1 EN 60335-2-80	Tested with appliance & UL E251728

Modification 6: November 14, 2018

Alternative	DONGGUAN CHUANTAI WIRE PRODUCTS CO., LTD	1015	600V; 105°C; 18-22AWG;	EN 60335-1 EN 60335-2-80	Tested with appliance & UL E315628
Alternative	DONGGUAN CHUANTAI WIRE PRODUCTS CO., LTD	1007	300V; 80°C; 18- 22AWG	EN 60335-1 EN 60335-2-80	Tested with appliance & UL E315628
Alternative	ZHONGSHAN DONGFENG ZHOUSHISHENL ONG ELECTRONIC WIRE CO., LTD.	1015	600V; 105°C; 18-22AWG;	EN 60335-1 EN 60335-2-80	Tested with appliance & UL E257280
Alternative	ZHONGSHAN DONGFENG ZHOUSHISHENL ONG ELECTRONIC WIRE CO., LTD.	1007	300V; 80°C; 18- 22AWG	EN 60335-1 EN 60335-2-80	Tested with appliance & UL E257280
Alternative	GUANG DONG XIN LONG ENTERPRISE CO.,	1015	600V; 105°C; 18-22AWG;	EN 60335-1 EN 60335-2-80	Tested with appliance & UL E207567
Alternative	GUANG DONG XIN LONG ENTERPRISE CO.,	1007	300V; 80°C; 18- 22AWG	EN 60335-1 EN 60335-2-80	Tested with appliance & UL E207567
Alternative	ZHONGSHAN DONGFENG FUSHENG WIRE CABLE FACTORY	1015	600V; 105°C; 18-22AWG;	EN 60335-1 EN 60335-2-80	Tested with appliance & UL E236761
Alternative	ZHONGSHAN DONGFENG FUSHENG WIRE CABLE FACTORY	1007	300V; 80°C; 18- 22AWG	EN 60335-1 EN 60335-2-80	Tested with appliance & UL E236761
Alternative	FOSHAN SHUNDE HONGJIAN Electronic Wire Co.,Ltd.	1015	600V; 105°C; 18-22AWG	EN 60335-1 EN 60335-2-80	Tested with appliance & UL E188132
Alternative	FOSHAN SHUNDE HONGJIAN Electronic Wire Co.,Ltd.	1007	300V; 80°C; 18- 22AWG	EN 60335-1 EN 60335-2-80	Tested with appliance & UL E188132
Alternative	FOSHAN CITY SHUNDE DISTRICT BEIJIAO QINGLANG ELECTRICAL FACTORY	1015	600V; 105°C; 18-22AWG	EN 60335-1 EN 60335-2-80	Tested with appliance & UL E365204

TRF No. IEC60335_2_80E

Intertek Testing Services Shenzhen Ltd. Guangzhou Branch

Block E, No.7-2 Guang Dong Software Science Park, Caipin Road, Guangzhou Science City, GETDD, Guangzhou, China

Tel: 86 20 82139688 Fax: 86 20 32057538 www.intertek-etlsemko.com

Modification 6: November 14, 2018

Alternative	FOSHAN CITY SHUNDE DISTRICT BEIJIAO QINGLANG ELECTRICAL FACTORY	1007	300V; 80°C; 18-22AWG	EN 60335-1 EN 60335-2-80	Tested with appliance & UL E365204
Alternative	ZHONGSHAN MEITAO ELECTRIC INDUSTRIAL CO LTD	1015	600V; 105°C; 18-22AWG	EN 60335-1 EN 60335-2-80	Tested with appliance & UL E351651
Alternative	ZHONGSHAN MEITAO ELECTRIC INDUSTRIAL CO LTD	1007	300V; 80°C; 18-22AWG	EN 60335-1 EN 60335-2-80	Tested with appliance & UL E351651
PVC Tube for leader wire of fan motor	CHANGYUAN ELECTRONICS GROUP CO LTD	GX-600	90°C, Min. thickness: 1,0 mm	EN 60335-1 EN 60335-2-80	Tested with appliance
Alternative	Shunde Beijiao Lianda Co., Ltd	LHX-01	105°C, Min. thickness: 1,0 mm	EN 60335-1 EN 60335-2-80	Tested with appliance
Alternative	Foshan Shunde Kaidaxin Plastic Industry Co Ltd	KDS01	600V; 105°C	EN 60335-1 EN 60335-2-80	Tested with appliance & UL E314911
Alternative	Zhongshan Fengyu Electrical Parts Co Ltd	FY-600	600V; 105°C	EN 60335-1 EN 60335-2-80	Tested with appliance & UL E314739
Alternative	DAE CHANG ELECCOM CO LTD	DC-6	600V; 105°C	EN 60335-1 EN 60335-2-80	Tested with appliance & UL E120268
Alternative	DONG GUAN HAI SHENG PLASTIC MANUFACTURE CO LTD	QS1-600	600V; 105°C	EN 60335-1 EN 60335-2-80	Tested with appliance & UL E238728
Alternative	SHENZHEN HENG CHANG YONG ELECTRIC COLTD	HCY-6	600V; 105°C	EN 60335-1 EN 60335-2-80	Tested with appliance & UL E313826
Closed-end Connector	Heavy Power Co., Ltd.	CE1, CE2	---	EN 60335-1 EN 60335-2-80	Tested with appliance
Control panel cover (blue, gray)	YUCAU HOME APPLIANCES CO., LTD.	PC230	HB; Min. Thickness: 2,0 mm	EN 60335-1 EN 60335-2-80 AfPS GS 2014:01 PAK	Tested with appliance
Plastic enclosure / Rotor box	LG CHEMICAL (GUANGZHOU) ENGINEERING PLASTICS CO LTD	GP-3156F(#)	PP; V-0; Min. Thickness: 2,0 mm	EN 60335-1 EN 60335-2-80	Tested with appliance & UL E248280

TRF No. IEC60335_2_80E

Intertek Testing Services Shenzhen Ltd. Guangzhou Branch

Block E, No.7-2 Guang Dong Software Science Park, Caipin Road, Guangzhou Science City, GETDD, Guangzhou, China
Tel: 86 20 82139688 Fax: 86 20 32057538 www.intertek-etlsemko.com

Modification 6: November 14, 2018

Alternative	HANWHA TOTAL PETROCHEMICAL CO LTD	FB33+	PP, 94V-0; Min. Thickness: 2,5 mm	EN 60335-1 EN 60335-2-80	Tested with appliance & UL E140331
Components on PCB board for YH-40R series and YH-40R1 series:					
PCB	Shandong Jinbao Electronics Co Ltd	ZD-9F	V-0; 1,6mm thickness	EN 60335-1 EN 60335-2-80	Tested with appliance & UL E222366
Alternative	KINGBOARD LAMINATES HOLDINGS LTD	KB-3150N	V-0; 1,6mm thickness	EN 60335-1 EN 60335-2-80	Tested with appliance & UL E123995
Fuse	XC Electronics (Shen Zhen)Corp. Ltd.	3T	250V; 1A	EN 60127-1 EN 60127-3	VDE 40019614
X capacitor (C2)	GUANGDONG FENGMIN ELECTRONIC TECH. CO., LTD.	MKP-X2	275V; 1,0μF; T85	EN 60384-14	VDE 40025702
Alternative	Tenta Electric Industrial Co. Ltd.	MEX	275V; 1,0μF; T85	EN 60384-14	VDE119119
X capacitor (C1)	GUANGDONG FENGMIN ELECTRONIC TECH. CO., LTD.	MKP-X2	275V; 0,1μF; T85	EN 60384-14	VDE 40025702
Alternative	Tenta Electric Industrial Co. Ltd.	MEX	275V; 0,1μF; T85	EN 60384-14	VDE119119
1) An asterisk indicates a mark which assures the agreed level of surveillance					

28.1	TABLE: Threaded part torque test			P
Threaded part identification		Diameter of thread (mm)	Column number (I, II, or III)	Applied torque (Nm)
Screw for fan guards		2,5	II	0,4

29.1	TABLE: Clearances					P
	Overvoltage category..... :		II			—
		Type of insulation:				
Rated impulse voltage (V):	Min. cl (mm)	Basic (mm)	Supplementary (mm)	Reinforced (mm)	Functional (mm)	Verdict / Remark
330	0,2* / 0,5 / 0,8**	---	---	---	---	N/A
500	0,2* / 0,5 / 0,8**	---	---	---	---	N/A
800	0,2* / 0,5 / 0,8**	---	---	---	---	N/A
1 500	0,5 / 0,8** / 1,0***	---	---	---	---	N/A
2 500	1,5 / 2,0***	1) 3,0 2) 3,5 3) 3,5 4) 3,5	1) 5,5 2) >10 3) >10 4) >10	---	5) 5,0 6) 2,8	P
4 000	3,0 / 3,5***	---	---	>10	---	P
6 000	5,5 / 6,0***	---	---	---	---	N/A
8 000	8,0 / 8,5***	---	---	---	---	N/A

TRF No. IEC60335_2_80E

Intertek Testing Services Shenzhen Ltd. Guangzhou Branch

Block E, No.7-2 Guang Dong Software Science Park, Caipin Road, Guangzhou Science City, GETDD, Guangzhou, China
Tel: 86 20 82139688 Fax: 86 20 32057538 www.intertek-etlsemko.com

10 000	11,0 / 11,5***	---	---	---	---	N/A
Supplementary information: 1) for YH-15 series; 2) for YH-23 series; 3) for YH-30 series; 4) for YH-40 series; 5) for L, N poles on speed switch; 6) for L, N poles on PCB						

29.2	TABLE: Creepage distances, basic, supplementary and reinforced insulation										P
Working voltage (V)	Creepage distance (mm) Pollution degree							Type of insulation			
	1	2			3						
		Material group			Material group						
		I	II	IIIa/IIIb	I	II	IIIa/IIIb *)	B**)	S**)	R**)	Verdict
≤50	0,18	0,6	0,85	1,2	1,5	1,7	1,9		—	—	N/A
≤50	0,18	0,6	0,85	1,2	1,5	1,7	1,9	—		—	N/A
≤50	0,36	1,2	1,7	2,4	3,0	3,4	3,8	—	—		N/A
125	0,28	0,75	1,05	1,5	1,9	2,1	2,4		—	—	N/A
125	0,28	0,75	1,05	1,5	1,9	2,1	2,4	—		—	N/A
125	0,56	1,5	2,1	3,0	3,8	4,2	4,8	—	—		N/A
250	0,56	1,25	1,8	2,5	3,2	3,6	4,0***	1)3,0 2)3,5 3)3,5 4)3,5	—	—	P
250	0,56	1,25	1,8	2,5	3,2	3,6	4,0	—	1) 5,5 2) >10 3) >10 4) >10	—	P
250	1,12	2,5	3,6	5,0	6,4	7,2	8,0	—	—	>10	P
400	1,0	2,0	2,8	4,0	5,0	5,6	6,3		—	—	N/A
400	1,0	2,0	2,8	4,0	5,0	5,6	6,3	—		—	N/A
400	2,0	4,0	5,6	8,0	10,0	11,2	12,6	—	—		N/A
500	1,3	2,5	3,6	5,0	6,3	7,1	8,0		—	—	N/A
500	1,3	2,5	3,6	5,0	6,3	7,1	8,0	—		—	N/A
500	2,6	5,0	7,2	10,0	12,6	14,2	16,0	—	—		N/A
>630 and ≤800	1,8	3,2	4,5	6,3	8,0	9,0	10,0		—	—	N/A
>630 and ≤800	1,8	3,2	4,5	6,3	8,0	9,0	10,0	—		—	N/A
>630 and ≤800	3,6	6,4	9,0	12,6	16,0	18,0	20,0	—	—		N/A
>800 and ≤1000	2,4	4,0	5,6	8,0	10,0	11,0	12,5		—	—	N/A
>800 and ≤1000	2,4	4,0	5,6	8,0	10,0	11,0	12,5	—		—	N/A
>800 and ≤1000	4,8	8,0	11,2	16,0	20,0	22,0	25,0	—	—		N/A

TRF No. IEC60335_2_80E

Intertek Testing Services Shenzhen Ltd. Guangzhou Branch

Block E, No.7-2 Guang Dong Software Science Park, Caipin Road, Guangzhou Science City, GETDD, Guangzhou, China
Tel: 86 20 82139688 Fax: 86 20 32057538 www.intertek-etlsemko.com

Modification 6: November 14, 2018

>1000 and ≤1250	3,2	5,0	7,1	10,0	12,5	14,0	16,0		—	—	N/A
>1000 and ≤1250	3,2	5,0	7,1	10,0	12,5	14,0	16,0	—		—	N/A
>1000 and ≤1250	6,4	10,0	14,2	20,0	25,0	28,0	32,0	—	—		N/A
>1250 and ≤1600	4,2	6,3	9,0	12,5	16,0	18,0	20,0		—	—	N/A
>1250 and ≤1600	4,2	6,3	9,0	12,5	16,0	18,0	20,0	—		—	N/A
>1250 and ≤1600	8,4	12,6	18,0	25,0	32,0	36,0	40,0	—	—		N/A
>1600 and ≤2000	5,6	8,0	11,0	16,0	20,0	22,0	25,0		—	—	N/A
>1600 and ≤2000	5,6	8,0	11,0	16,0	20,0	22,0	25,0	—		—	N/A
>1600 and ≤2000	11,2	16,0	22,0	32,0	40,0	44,0	50,0	—	—		N/A
>2000 and ≤2500	7,5	10,0	14,0	20,0	25,0	28,0	32,0		—	—	N/A
>2000 and ≤2500	7,5	10,0	14,0	20,0	25,0	28,0	32,0	—		—	N/A
>2000 and ≤2500	15,0	20,0	28,0	40,0	50,0	56,0	64,0	—	—		N/A
>2500 and ≤3200	10,0	12,5	18,0	25,0	32,0	36,0	40,0		—	—	N/A
>2500 and ≤3200	10,0	12,5	18,0	25,0	32,0	36,0	40,0	—		—	N/A
>2500 and ≤3200	20,0	25,0	36,0	50,0	64,0	72,0	80,0	—	—		N/A
>3200 and ≤4000	12,5	16,0	22,0	32,0	40,0	45,0	50,0		—	—	N/A
>3200 and ≤4000	12,5	16,0	22,0	32,0	40,0	45,0	50,0	—		—	N/A
>3200 and ≤4000	25,0	32,0	44,0	64,0	80,0	90,0	100,0	—	—		N/A
>4000 and ≤5000	16,0	20,0	28,0	40,0	50,0	56,0	63,0		—	—	N/A
>4000 and ≤5000	16,0	20,0	28,0	40,0	50,0	56,0	63,0	—		—	N/A
>4000 and ≤5000	32,0	40,0	56,0	80,0	100,0	112,0	126,0	—	—		N/A
>5000 and ≤6300	20,0	25,0	36,0	50,0	63,0	71,0	80,0		—	—	N/A
>5000 and ≤6300	20,0	25,0	36,0	50,0	63,0	71,0	80,0	—		—	N/A
>5000 and ≤6300	40,0	50,0	72,0	100,0	126,0	142,0	160,0	—	—		N/A
>6300 and ≤8000	25,0	32,0	45,0	63,0	80,0	90,0	100,0		—	—	N/A
>6300 and ≤8000	25,0	32,0	45,0	63,0	80,0	90,0	100,0	—		—	N/A
>6300 and ≤8000	50,0	64,0	90,0	126,0	160,0	180,0	200,0	—	—		N/A
>8000 and ≤10000	32,0	40,0	56,0	80,0	100,0	110,0	125,0		—	—	N/A
>8000 and ≤10000	32,0	40,0	56,0	80,0	100,0	110,0	125,0	—		—	N/A
>8000 and ≤10000	64,0	80,0	112,0	160,0	200,0	220,0	250,0	—	—		N/A
>10000 and ≤12500	40,0	50,0	71,0	100,0	125,0	140,0	160,0		—	—	N/A
>10000 and ≤12500	40,0	50,0	71,0	100,0	125,0	140,0	160,0	—		—	N/A
>10000 and ≤12500	80,0	100,0	142,0	200,0	250,0	280,0	320,0	—	—		N/A

Supplementary information:
*) Material group IIIb is allowed if the working voltage does not exceed 50 V
**) B = Basic insulation, S = Supplementary insulation, R = Reinforced insulation
***) Lacquered conductors of windings are considered to be bare conductors, but creepage distances need not be greater than the associated clearance specified in table 16 taking into account 29.1.1
Remark: 1) for YH-15 series; 2) for YH-23 series; 3) for YH-30 series; 4) for YH-40 series;

29.2	TABLE: Creepage distances, functional insulation							P
Working voltage (V)	Creepage distance (mm) Pollution degree							
	1	2			3			
		Material group			Material group			
		I	II	IIIa/IIIb	I	II	IIIa/IIIb*)	Verdict / Remark
≤10	0,08	0,4	0,4	0,4	1,0	1,0	1,0	N/A
50	0,16	0,56	0,8	1,0	1,4	1,6	1,8	N/A
125	0,25	0,71	1,0	1,4	1,8	2,0	2,2	N/A
250	0,42	1,0	1,4	2,0	2,5	2,8	3,2	P/5,0mm between L, N poles on speed switch
250	0,42	1,0	1,4	2,0	2,5	2,8	3,2	P/2,8mm between L, N poles on PCB
400	0,75	1,6	2,2	3,2	4,0	4,5	5,0	N/A
500	1,0	2,0	2,8	4,0	5,0	5,6	6,3	N/A
>630 and ≤800	1,8	3,2	4,5	6,3	8,0	9,0	10,0	N/A
>800 and ≤1000	2,4	4,0	5,6	8,0	10,0	11,0	12,5	N/A
>1000 and ≤1250	3,2	5,0	7,1	10,0	12,5	14,0	16,0	N/A
>1250 and ≤1600	4,2	6,3	9,0	12,5	16,0	18,0	20,0	N/A
>1600 and ≤2000	5,6	8,0	11,0	16,0	20,0	22,0	25,0	N/A
>2000 and ≤2500	7,5	10,0	14,0	20,0	25,0	28,0	32,0	N/A
>2500 and ≤3200	10,0	12,5	18,0	25,0	32,0	36,0	40,0	N/A
>3200 and ≤4000	12,5	16,0	22,0	32,0	40,0	45,0	50,0	N/A
>4000 and ≤5000	16,0	20,0	28,0	40,0	50,0	56,0	63,0	N/A
>5000 and ≤6300	20,0	25,0	36,0	50,0	63,0	71,0	80,0	N/A
>6300 and ≤8000	25,0	32,0	45,0	63,0	80,0	90,0	100,0	N/A
>8000 and ≤10000	32,0	40,0	56,0	80,0	100,0	110,0	125,0	N/A
>10000 and ≤12500	40,0	50,0	71,0	100,0	125,0	140,0	160,0	N/A
Supplementary information:								
*) Material group IIIb is allowed if the working voltage does not exceed 50 V								

30	TABLE: Resistance to heat and fire																			
Object/ part No.	Manuf acturer / tradem ark	Type/ model	Ball pressure test °C				Glow wire test (GWT) °C					Glow-wire flammability index (GWFI) °C				Glow- wire ignition temp. (GWIT) °C		Needle - flame test (NFT)	Verdict	
			75	125	cl. 11 +40	cl. 19 +25	550	650		750		850	550	650	750	850	675	775		
								te	ti	te	ti									
Plastic enclosure	---	---	---	---	---	P 90°C	P	---	---	---	---	---	---	---	---	---	---	---	---	P
Bobbin of fan motor	---	---	---	P	---	---	---	---	---	No flame		P	---	---	---	---	---	---	---	P
Speed switch	---	---	---	P	---	---	---	---	---	No flame		P	---	---	---	---	---	---	---	P
Timer	---	---	---	P	---	---	---	---	---	No flame		P	---	---	---	---	---	---	---	
Closed-end connector	---	---	---	---	---	---	---	---	---	No flame		P	---	---	---	---	---	---	---	P
Motor capacitor	---	---	---	---	---	---	---	---	---	No flame		P	---	---	---	---	---	---	---	P
Bobbin of Synchronous motor	---	---	---	P	---	---	---	No flame		---		---	---	---	---	---	---	---	---	P
X capacitor	---	---	---	---	---	---	---	No flame		---		---	---	---	---	---	---	---	---	P
PCB	---	---	---	---	---	---	---	---	---	---		---	---	---	---	---	---	---	P	P

Photo documents:

Photos for YH-15 series:



Front view of YH-15D1



Front view of YH-15D



Side view



Back view



Bottom view



Speed switch knob



Removed fan blade



Front view of YH-15C



Front view of YH-15C1





Side view



Back view



Removed decorate cover




Internal view

Supply
cord



Cord inlet and cord anchorage for YH-15D1 and YH-15C1



Speed switch



Screw for fan guard

Photos for YH23 series



Front view



Side view



Back view




Bottom view




Speed switch knob



Internal view




Speed switch view



Cord anchorage



Fan motor view



Rotor box view



View for YH-23D1-1

Remark: The other part of YH-23D1-1 was the same as YH-23D1.

Photos for YH-30 series



Front view of YH-30D




Front view of YH-30D1




Side view



Back view



Bottom view



Internal view



Cord anchorage



Fan motor view



Front view of YH-30D1-1

Remark: The other part of YH-30D1-1 was the same as YH-30D1, except the fan motor and fan blade quantity.



Front view of YH-40D




Front view of YH-40D1



Side view



Back view





Bottom view



Speed switch knob



Cord inlet



Cord
anchorage



Neck view



Fan motor view



Fan motor view



Front view of YH-40D1-1

Remark:

- 1.The other part of YH-40D1-1 is the same as YH-40D1, except the fan motor and fan blade quantity.
- 2.The construction of YH-30D2 is the same as YH-40D, except the fan motor and the size is smaller than YH-40D.

Photos for YH-40x-y



Front view of YH-40E-0



Side view




Back view




Fan motor cover




Cord inlet and adjustor



Internal view



Timer and speed switch



Internal wire and cord anchorage




Control panel

Remark: The construction for other models of YH-40x-y is the same as YH-40E-0, except the control panel and the other models have no timer.




Control pane for YH-40A-y



Internal view of YH-40A-y




Control panel of YH40B-y



Internal view of YH-40B-y




Control panel of YH-40C-y



Internal view of YH-40C-y




Control panel of YH-40F-y



Internal view of YH-40F-y




Control panel of YH-40H-y



Internal view of YH-40H-y



Control panel of YH-40S-y




Internal view of YH-40S-y



LED lamp of YH-40S-y



Control panel of YH-40S1-y



Internal view of YH-40S1-y



LED lamp of YH-40S1-y

The following photos are for models YH-40x-y




Switch knob for swing




Rotor box view



Fan motor and motor capacitor



Neck view



Main body view



Base for YH-40x-y



Fan guard for all models

Remark: The two types of fan guard are for all models but with different size.

The following photos are for emanant type fan guard
Clip type:



Clip for fan guard



Clip for fan guard



Screw for fan guard


Remark: The same clips for rhombus type fan guard.

Hoop type:




Screw for fan guard

The following photos are for motors:
Fan motor 4815




Fan motor view




Thermal-link view

Fan motor 6016




Fan motor view




Thermal-link view


Fan motor 6612, 6614, 7118, 6614-1



Fan motor view



Internal view



Internal view

Remark:

The construction of fan motor 6612, 6614 and 7118 are similar, except winding quantity.
Fan motor 6614 and 6614-1 are similar, except the former is aluminum winding and the latter is copper winding.

The photo of other models:



The control panel for YH-40A1 series



The control panel for YH-40A2 series and YH-40A3 series



The control panel for YH-40I series and YH-40I1 series



Fan motor cover for YH-40A2 series and YH-40A3 series



Fan motor cover for YH-40A2 series and YH-40A3 series



Fan motor cover for YH-40A1 series, YH-40S1-y, YH-40I series and YH-40I1 series



Fan motor cover for YH-40A1 series, YH-40S1-y, YH-40I series and YH-40I1 series



YH-40A1



YH-40A1-0



YH-40A1-1



YH-40A1-1-0



YH-40A1-2



YH-40A1--2-0



YH-40A2



YH-40A2-0



YH-40A2-1



YH-40A2-1-0



YH-40A2-2



YH-40A2--2-0



YH-40A3



YH-40A3-0



YH-40A3-1



YH-40A3-1-0



YH-40A3-2



YH-40A3--2-0



YH-40I



YH-40I1



YH-40I1-0



YH-40I-0

The following photos are for YH-40R1 series models:




Front view(YH-40R1-0)




Rear view(YH-40R1-0)




Control panel



Internal view



PCB board bottom view



PCB board top view



Internal view

The following photos are for YH-40R1 series models:



Front view(YH-40R-0)



Rear view(YH-40R-0)



Internal view

The following photos are for YH-40J series models:



Front view(YH-40J-0)




Rear view(YH-40J-0)



Control panel



Internal view of speed switch



Speed switch

The following photos are for YH-40LK series models:



Front view(YH-40LK-0)



Rear view(YH-40LK-0)

The following photos are for other models:



Front view(YH-40D2)



Rear view(YH-40D2)



Control panel(YH-40D2)



Front view(YH-30D3)




Rear view(YH-30D3)



Control panel(YH-30D3)



YH-15D1 with alternative appearance



Alternative cross shape stand base for stand fan



Alternative circle shape stand base for stand fan



Fan blade (five blades) for stand fan



Two constructions of wiring connection for speed switch



Alternative fan motor cover for all stand fans and table fans



Alternative fan motor cover for all stand fans and table fans



Front view for model YH-15CD2



Rear view for model YH-15CD2



Front view for model YH-15CD2 (after removed decorate cover)



Side view for model YH-15CD2 (after removed decorate cover)



Front view for model YH-15D2

Remark:

- 1) Photos of model YH-15C2 is same as model YH-15CD2 except model YH-15C2 without the decorate cover.
- 2) Models YH-15C2, YH-15D2 and YH-15CD2 have the same fan motor cover.



Model YH-40D with alternative fan motor cover

IEC 60335-2-80			
Clause	Requirement - Test	Result - Remark	Verdict

Appendix to TRF No. IEC60335_2_80E

ATTACHMENT TO TEST REPORT IEC 60335-2-80 EUROPEAN GROUP DIFFERENCES AND NATIONAL DIFFERENCES (Part 2: Particular requirements for fans)	
Differences according to:	EN 60335-1:2012+A11:2014 EN 60335-2-80:2003+A1:2004+A2:2009 EN 62233:2008
Attachment Form No.:	EU_GD_IEC60335_2_80E
Attachment Originator:	DEKRA Certification B.V.
Master Attachment:	2012-09
Copyright © 2012 IEC System for Conformity Testing and Certification of Electrical Equipment (IECEE), Geneva, Switzerland. All rights reserved.	

	CENELEC COMMON MODIFICATIONS		
6.1	Delete "class 0" and "class 01"		N/A
7.1	Single-phase appliances to be connected to the supply mains: 230 V covered		P
	Multi-phase appliances to be connected to the supply mains: 400 V covered		N/A
7.10	Devices used to start/stop operational functions of the appliance distinguished from other manual devices by means of shape, size, surface texture, position, etc.		N/A
	An indication that the device has been operated is given by:		----
	• a tactile feedback, or		N/A
	• an audible and visual feedback		N/A
7.12	The instructions include the substance of the following:		----
	- this appliance can be used by children aged from 8 years and above and persons with reduced physical, sensory or mental capabilities or lack of experience and knowledge if they have been given supervision or instruction concerning use of the appliance in a safe way and understand the hazards involved		P
	- children shall not play with the appliance		P
	- cleaning and user maintenance shall not be made by children without supervision		P
7.12.Z1	The specific instructions related to the safe operation of this appliance is collated together in the front section of the user instructions		P

IEC 60335-2-80			
Clause	Requirement - Test	Result - Remark	Verdict
	The height of the characters, measured on the capital letters, is at least 3 mm		P
	These instructions are also available in an alternative format, e.g. on a website		P
8.1.1	Also test probe 18 of EN 61032 is applied		P
	The appliance being in every possible position during the test		P
	The force on the probe in the straight position is increased to 10 N when probe 18 is used		P
	When using test probe 18 the appliance is fully assembled as in normal use without any parts removed, and		P
	parts intended to be removed for user maintenance are also not removed		P
8.2	Compliance is checked by applying the test probes of EN 61032		P
	For built-in appliances and fixed appliances, the test probe B and probe 18 of EN 61032 are applied only after installation		N/A
11.8	Footnotes to "External enclosure of motor-operated appliances" to be taken into account		P
15.1.2	Appliances with an automatic cord reel tested with the cord in the most unfavourable position so that the reeling of the wet cord may affect electrical insulation during operation, the cord not being dried before reeling		N/A
20.2	When using the test probe similar to test probe B with a circular stop face, the accessories and detachable covers are removed		P
	Test probe 18 applied with a force of 2,5N on the appliance fully assembled		P
24.1	Components comply with the safety requirements specified in the relevant standards as far as they reasonably apply		P
	The requirements of Clause 29 of this standard apply between live parts of components and accessible parts of the appliance.		P
	The requirements of 30.2 of this standard apply to parts of non-metallic material in components including parts of non-metallic material supporting current-carrying connections inside components		P
	Components that have not been previously tested or do not comply with the standard for the relevant component are tested according to the requirements of 30.2		P

TRF No. IEC60335_2_80E

Intertek Testing Services Shenzhen Ltd. Guangzhou Branch

Block E, No.7-2 Guang Dong Software Science Park, Caipin Road, Guangzhou Science City, GETDD, Guangzhou, China
Tel: 86 20 82139688 Fax: 86 20 32057538 www.intertek-etlsemko.com

IEC 60335-2-80			
Clause	Requirement - Test	Result - Remark	Verdict
	Components that have been previously tested and shown to comply with the resistance to fire requirements in the standard for the relevant component need not be retested provided that:		----
	- the severity specified in the component standard is not less than the severity specified in 30.2, and		P
	- the test report for the component states whether it complied with the standard for the relevant component with or without flame, flames not exceeding 2 s during the test are ignored		N/A
	Unless components have been previously tested and found to comply with the relevant standard for the number of cycles specified, they are tested in accordance with 24.1.1 to 24.1.9		P
	For components mentioned in 24.1.1 to 24.1.9, no additional tests specified in the relevant standard for the component are necessary other than those specified in 24.1.1 to 24.1.9		P
	Components that have not been separately tested and found to comply with the relevant standard, and		N/A
	components that are not marked or not used in accordance with their marking,		N/A
	are tested in accordance with the conditions occurring in the appliance, the number of samples being that required by the relevant standard		N/A
	Lamp holders and starter holders that have not been previously tested and found to comply with the relevant standard are tested as a part of the appliance and additionally comply with the gauging and interchangeability requirements of the relevant standard under the conditions occurring in the appliance		N/A
	Where the relevant standard specifies these gauging and interchangeability requirements at elevated temperatures, the temperatures measured during the tests of Clause 11 are used		N/A
	Plugs and socket-outlets and other connecting devices of interconnection cords are not interchangeable with plugs and socket-outlets listed in IEC/TR 60083 or IEC 60906-1, or		N/A
	with connectors and appliance inlets complying with the standard sheets of IEC 60320-1,		N/A
	if direct supply to these parts from the supply mains gives rise to a hazard		N/A

IEC 60335-2-80			
Clause	Requirement - Test	Result - Remark	Verdict
24.1.7	If the remote operation of the appliance is via a telecommunication network, the relevant standard for the telecommunication interface circuitry in the appliance is EN 41003		N/A
	Compliance with Clause 8 of this standard is not impaired by connecting the appliance to a device covered by EN 41003		N/A
24.Z1	For motor running capacitors (IEC 60252-1 type P2) with a metallic enclosure having an overpressure fuse the flame testing of internal plastic parts supporting current carrying connections as required in 30.2.2 and 30.2.3.1 is not necessary		N/A
25.6	Supply cords of single-phase portable appliances having a rated current not exceeding 16 A, fitted with a plug complying with the following standard sheets of IEC/TR 60083:		----
	- for Class I appliances: standard sheet C2b, C3b or C4		N/A
	- for Class II appliances: standard sheet C5 or C6.....		P
25.7	Rubber sheathed cords (60245 IEC 53) are not suitable for appliances intended to be used outdoors or when they are liable to be exposed to significant amount of ultraviolet radiation		N/A
	Halogen-free thermoplastic compound sheathed supply cords have properties at least those of:		----
	halogen-free thermoplastic compound sheathed cords (H03Z1Z1H2-F or H03Z1Z1-F), for appliances having a mass not exceeding 3 kg		N/A
	halogen-free thermoplastic compound sheathed cords (H05Z1Z1H2-F or H05Z1Z1-F), for other appliances		N/A
	Cross-linked halogen-free compound sheathed supply cords have properties at least those of cross-linked halogen-free compound sheathed cords (H07ZZ-F)		N/A
26.11	Conductors connected by soldering are not considered to be positioned or fixed so that reliance is not placed upon the soldering alone to maintain them in position unless they are held in place near the terminals independently of the solder		N/A
29.3.Z1	Appliance constructed so that if there is a possibility of damaging the insulation during installation, the insulation withstands the scratch and penetration test of 21.2		N/A

IEC 60335-2-80			
Clause	Requirement - Test	Result - Remark	Verdict
32	Compliance regarding electromagnetic fields is checked according to EN 50366 or EN 62233		P
Annex I, 19.1.101	The appliance is supplied at rated voltage and operated under normal operation with each of the fault conditions specified		N/A
	The duration of the test is as specified in 19.7		N/A
ZA	ANNEX ZA (NORMATIVE) SPECIAL NATIONAL CONDITIONS		----
	Norway		----
19.5	The test is also applicable to appliances intended to be permanently connected to fixed wiring		N/A
	Norway		----
22.2	The second paragraph of this subclause, dealing with single-phase, permanently connected class I appliances having heating elements, is not applicable due to the supply system		N/A
	All CENELEC countries		----
25.6 and 25.25	Information concerning National plug and socket-outlets is available from the CENELEC website. Normative national requirements concerning plug and socket-outlets are shown in the relevant National standard		P
	Ireland and United Kingdom		----
25.8	In the table, the lines for 10 A and 16 A are replaced by:		----
	> 10 and ≤ 13 1,25		N/A
	> 13 and ≤ 16 1,5		N/A
ZB	ANNEX ZB (INFORMATIVE) A-DEVIATIONS		----
	Ireland		----
25.6	These regulations apply to all plugs for domestic use at a voltage of not less than 200 V and in general allow only plugs complying with I.S. 401:1997, or equivalent, to be fitted to domestic appliances		N/A

IEC 60335-2-80			
Clause	Requirement - Test	Result - Remark	Verdict
	United Kingdom		----
25.6	These regulations apply to all plugs for domestic use at a voltage of not less than 200 V and in general allow only plugs to BS 1363 to be fitted to domestic appliances. It also allows plugs to BS 4573 and EN 50075 to be fitted to shavers and toothbrushes		P
ZC	ANNEX ZC (NORMATIVE) NORMATIVE REFERENCES TO INTERNATIONAL PUBLICATIONS WITH THEIR CORRESPONDING EUROPEAN PUBLICATIONS		----
	A list of referenced documents in this standard		P
ZD	ANNEX ZD (INFORMATIVE) IEC and CENELEC CODE DESIGNATIONS FOR FLEXIBLE CORDS		----
	A table with IEC and CENELEC code designations for flexible cords		P
ZE	ANNEX ZE (INFORMATIVE) SPECIFIC ADDITIONAL REQUIREMENTS FOR APPLIANCES AND MACHINES INTENDED FOR COMMERCIAL USE		----
7.1	Business name and full address of the manufacturer and, where applicable, his authorized representative		N/A
	Model or type reference		N/A
	Serial number, if any		N/A
	Production year		N/A
	Designation of the appliance		N/A
7.12	Instructions provided with the appliance so that the appliance can be used safely		N/A
	The instructions contain at least the following information:		----
	- the business name and full address of the manufacturer and, where applicable, his authorized representative		N/A
	- model or type reference of the appliance as marked on the appliance itself, except for the serial number		N/A
	- the designation of the appliance together with its explanation in case it is given by a combination of letters and/or numbers		N/A
	- the general description of the appliance, when needed due to the complexity of the appliance		N/A

IEC 60335-2-80			
Clause	Requirement - Test	Result - Remark	Verdict
	- specific precautions if required during installation, operation, adjusting, user maintenance, cleaning, repairing or moving		N/A
	- when needed drawings, diagrams, descriptions and explanations necessary for the safe use and user maintenance of the appliance		N/A
	- the possible reasonably foreseeable misuse and, whenever relevant, a warning against the effects it may have on the safe use of the appliance		N/A
	The words "Original instructions" appear on the language version(s) verified by the manufacturer or by the authorized representative		N/A
	When a translation of the original instructions has been provided by a person introducing the appliance on the market; the meaning of the sentence "Translation of the original instructions" appear in the relevant instructions delivered with the appliance		N/A
	The instructions for maintenance/service to be done by specialized personnel, mandated by the manufacturer or the authorized representative may be supplied in only one Community language which the specialized personnel understand		N/A
	The instructions indicate the type and frequency of inspections and maintenance required for safe operation including the preventive maintenance measures		N/A
7.12.ZE1	If needed for specific appliances, the following information to be given:		----
	on use, transportation, assembly, dismantling when out of service, testing or foreseeable breakdowns, if these operations have consequences on stability of the appliance in order to avoid overturning, falling or uncontrolled movements of the appliance or of its component parts		N/A
	on how to maintain adequate mechanical stability when in use, during transportation, assembly, dismantling, scrapping and any other action involving the appliance		N/A
	on the protective measures to be taken by the user, including, where appropriate, the personal protective equipment to be provided		N/A
	on the operating method to be followed in the event of accident or breakdown; if a blockage is likely to occur the operating method to safely unblock the appliance		N/A

IEC 60335-2-80			
Clause	Requirement - Test	Result - Remark	Verdict
	on the specifications on the spare parts to be used, when these affect the health and safety of the operator		N/A
	on airborne noise emissions, determined and declared in accordance with the relevant Part 2, which includes:		----
	- the A-weighted emission sound pressure level at workstations, where this exceeds 70 dB(A)		N/A
	- where this level does not exceed 70 dB(A), this fact is indicated		N/A
	- the peak C-weighted instantaneous sound pressure value at workstations, where this exceeds 63 Pa (130 dB in relation to 20 µPa)		N/A
	- the A-weighted sound power level emitted by the machinery, where the A-weighted emission sound pressure level at workstations exceeds 80 dB(A)		N/A
7.12.ZE2	The instructions includes a warning to disconnect the appliance from its power source during service and when replacing parts		N/A
	If the removal of the plug is foreseen, it is clearly indicated that the removal of the plug has to be such that an operator can check from any of the points to which he has access that the plug remains removed		N/A
	If this is not possible, due to the construction of the appliance or its installation, a disconnection with a locking system in the isolated position is provided		N/A
19.11.4.8	The appliance continues to operate, without causing any hazard to the user, from the same point in its operating cycle at which the voltage fluctuation occurred, or		N/A
	a manual operation is required to restart it		N/A
20.1	Appliances and their components and fittings have adequate mechanical stability during transportation, assembly, dismantling and any other action involving the appliance		N/A
20.2	Dangerous moving transmission parts safeguarded either by design or guards		N/A
	When guards are used, they are fixed guards, interlocking movable guards or protective devices		N/A
	Moving parts directly involved in the function of the appliance which cannot be made completely inaccessible fitted with:		----

IEC 60335-2-80			
Clause	Requirement - Test	Result - Remark	Verdict
	- fixed guards or interlocking movable guards preventing access to those sections of the parts that are not used in the work, and		N/A
	- adjustable guards restricting access to those sections of the moving parts where access is necessary		N/A
	Interlocking movable guards used where frequent access is required		N/A
21.1	Appliances and their components and fittings have adequate mechanical strength and is constructed to withstand such rough handling that may be expected in normal use, during transportation, assembly, dismantling, scrapping and any other action involving the appliance		N/A
22.ZE.1	For appliances provided with a seat, the seat gives adequate stability		N/A
	The distance between the seat and the control devices capable of being adapted to the operator		N/A
22.ZE.2	For appliances provided with separate devices for the start and the stop functions, the stop function is unambiguously identifiable and does always override the start function		N/A
	For appliances provided with one device performing the start and the stop function, the stop function is unambiguously identifiable and does always override the start function		N/A
22.ZE.3	Appliances designed in such a way that incorrect mounting is avoided, if this can lead to an unsafe situation		N/A
	If this is not possible, information on the correct mounting is given directly on the part and/or the enclosure		N/A
22.ZE.4	Where the weight, size or shape prevents appliances from being moved manually, they are fitted with attachments for lifting gear, or		N/A
	so designed that they can be fitted with such attachments, or		N/A
	be shaped in such a way that standard lifting gear can easily be used		N/A
	Appliances to be moved manually are constructed or equipped so that they can be moved easily and safely		N/A
22.ZE.5	The fixing systems of fixed guards which prevent access to dangerous moving transmission parts only removable with the use of tools		N/A

IEC 60335-2-80			
Clause	Requirement - Test	Result - Remark	Verdict
	If such guards have to be removed by the user for routine cleaning or maintenance their fixing systems remain attached to the fixed guards or to the machine after removal		N/A
	Where possible, guards are incapable of remaining in place without their fixings		N/A
	This does not apply if, after removal of the screws, or if the component is incorrectly repositioned, the appliance becomes inoperative		N/A
	Movable guards are interlocked		N/A
	The interlocking devices prevent the start of hazardous appliance functions until the guards are fixed in their position, and give a stop command whenever they are no longer closed		N/A
	Where it is possible for an operator to reach the danger zone before the risk due to hazardous appliance functions has ceased, movable guards associated with a guard locking device in addition to an interlocking device that:		----
	- prevents the start of hazardous appliance functions until the guard is closed and locked, and		N/A
	- keeps the guard closed and locked until the risk of injury from the hazardous appliance functions has ceased		N/A
	Interlocking movable guards remain attached to the appliance when open, and		N/A
	they are designed and constructed in such a way that they can be adjusted only by means of an intentional action		N/A
22.ZE.6	Interlocking movable guards designed in such a way that the absence or failure of one of their components prevents starting or stops the hazardous appliance functions		N/A
	The guard is opened to the extent needed to cause the interlocking to operate and is then closed, the number of operations being defined in the specific Part 2 :		N/A
	After this test any defect that may be expected in normal use is applied to the interlock system, including interruption of the supply, only one defect being simulated at a time		N/A
	After these tests the interlock system is fit for further use		N/A
22.ZE.7	Adjustable guards restricting access to areas of the moving parts strictly necessary for the work are:		----
	- adjustable manually or automatically, depending on the type of work involved, and		N/A

IEC 60335-2-80			
Clause	Requirement - Test	Result - Remark	Verdict
	- readily adjustable without the use of tools		N/A
22.ZE.8	In case of interruption, re-establishment after an interruption or fluctuation in whatever manner of the power supply, the appliance does not restart		N/A
	However, automatic restarting of the operation is allowed if the appliance may continue to operate, without causing any hazard to the user, from the same point in its operating cycle at which the voltage interruption or fluctuation occurred		N/A
22.ZE.9	Appliances fitted with means to isolate them from all energy sources		N/A
	Such isolators are clearly identified, and		N/A
	they are capable of being locked if reconnection endanger persons		N/A
	After the energy source is disconnected, it is possible to dissipate any energy remaining or stored in the circuits of the appliance without risk to persons		N/A
ZF	ANNEX ZF (INFORMATIVE) CRITERIA APPLIED FOR THE ALLOCATION OF PRODUCTS COVERED BY STANDARDS IN THE EN 60335 SERIES UNDER LVD OR MD		----
	List of standards under CENELEC/TC61 with the allocation under the LVD (Low Voltage Directive) or the MD (Machinery Directive)		P
ZG	ANNEX ZG (NORMATIVE) UV APPLIANCES		----
	The following modifications to this standard apply to appliances having UV emitters		N/A
	This annex is not applicable to appliances covered by the scopes of IEC 60335-2-27, IEC 60335-2-59 or IEC 60335-2-109		N/A
7.12.ZG	The instructions for appliances incorporating UVC emitters include the substance of the following: WARNING — This appliance contains a UV emitter. Do not stare at the light source		N/A
32	For appliances incorporating UV emitters the manufacturer delivers a declaration providing evidence that the plastic material exposed to the radiation is UV resistant		N/A
ZZ	ANNEX ZZ (INFORMATIVE) COVERAGE OF ESSENTIAL REQUIREMENTS OF EC DIRECTIVES		----

IEC 60335-2-80			
Clause	Requirement - Test	Result - Remark	Verdict
	Description of the relation between this European standard and the LVD (Low Voltage Directive, 2006/95/EC) and the MD (Machinery Directive, 2006/42/EC)	Low Voltage Directive 2014/35/EU	P

Appendix to TRF No. IEC60335_2_80E

Variations to EN 60335-1:2012/A13:2017			
ZZA	ANNEX ZZA (INFORMATIVE) REALATIONSHIP BETWEEN THIS EUROPEAN STANDARD AND THE SAFETY OBJECTIVES OF DIRECTIVE 2014/35/EU [2014 OJ L96] AIMED TO BE COVERED		—
	Description relating to harmonized standards in the field of the Low Voltage Directive, M/511, to provide one voluntary means of conforming to safety objectives of Directive 2014/35/EU of the European Parliament and of the Council of 26 February 2014 on the harmonization of the laws of the Member States relating to the making available on the market of electrical equipment designed for use within certain voltage limits [2014 OJ L96]		P
	A table with correspondence between this European standard and Annex I of Directive 2014/35/EU [2014 OJ L96]		P
ZZB	ANNEX ZZB (INFORMATIVE) REALATIONSHIP BETWEEN THIS EUROPEAN STANDARD AND THE ESSENTIAL REQUIREMENTS OF DIRECTIVE 2006/42/EC AIMED TO BE COVERED		—
	Description relating to Mandate for standardisation in the field of machinery “M/396” to provide one voluntary means of conforming to essential requirements of EU Directive 2006/42/EC		N/A
	A table with correspondence between this European standard and Annex I of Directive 2006/42/E [OJ No L 157]		N/A

Annex EN 62233:2008			
Clause	Requirement + Test	Result - Remark	Verdict
EMF- ELECTROMAGNETICS FIELDS			
	The tested product also complies with the requirements of EN 62233:2008		----
	Limit 100%	Measured max.: 1,254%	P

--- END OF REPORT---